

MUSEUM PLACE ENVIRONMENTAL NOISE AND VIBRATION ASSESSMENT

San José, California

April 14, 2016

Prepared for:

**Shannon George
David J. Powers & Associates, Inc.
1871 The Alameda, Suite 200
San José, CA 95126**

Prepared by:

Dana M. Lodico, PE, INCE Bd. Cert.

ILLINGWORTH & RODKIN, INC.
//// Acoustics • Air Quality ////

**1 Willowbrook Court, Suite 120
Petaluma, CA 94954
(707) 794-0400**

Project: 16-051

INTRODUCTION

The project proposes to develop a 24-story building with 300 to 370 dwelling units, 155 hotel rooms, 176,705 square feet of office space, a 63,030 square foot museum, and 653 parking stalls. This report evaluates the project's potential to result in significant noise and vibration impacts with respect to applicable California Environmental Quality Act (CEQA) guidelines. The report is divided into three sections: 1) the Setting Section provides a brief description of the fundamentals of environmental noise, summarizes applicable regulatory criteria, and discusses the results of the ambient noise monitoring survey completed to document existing noise conditions; 2) the General Plan Consistency Section discusses noise and land use compatibility utilizing policies in the City's General Plan; and, 3) the Impacts and Mitigation Measures Section describes the significance criteria used to evaluate project impacts, provides a discussion of each project impact, and presents mitigation measures, where necessary, to provide a compatible project in relation to adjacent noise sources and land uses.

SETTING

Fundamentals of Environmental Noise

Noise may be defined as unwanted sound. Noise is usually objectionable because it is disturbing or annoying. The objectionable nature of sound could be caused by its *pitch* or its *loudness*. *Pitch* is the height or depth of a tone or sound, depending on the relative rapidity (frequency) of the vibrations by which it is produced. Higher pitched signals sound louder to humans than sounds with a lower pitch. *Loudness* is intensity of sound waves combined with the reception characteristics of the ear. Intensity may be compared with the height of an ocean wave in that it is a measure of the amplitude of the sound wave.

In addition to the concepts of pitch and loudness, there are several noise measurement scales which are used to describe noise in a particular location. A *decibel (dB)* is a unit of measurement which indicates the relative amplitude of a sound. The zero on the decibel scale is based on the lowest sound level that the healthy, unimpaired human ear can detect. Sound levels in decibels are calculated on a logarithmic basis. An increase of 10 decibels represents a ten-fold increase in acoustic energy, while 20 decibels is 100 times more intense, 30 decibels is 1,000 times more intense, etc. There is a relationship between the subjective noisiness or loudness of a sound and its intensity. Each 10 decibel increase in sound level is perceived as approximately a doubling of loudness over a fairly wide range of intensities. Technical terms are defined in Table 1.

There are several methods of characterizing sound. The most common in California is the *A-weighted sound level (dBA)*. This scale gives greater weight to the frequencies of sound to which the human ear is most sensitive. Representative outdoor and indoor noise levels in units of dBA are shown in Table 2. Because sound levels can vary markedly over a short period of time, a method for describing either the average character of the sound or the statistical behavior of the variations must be utilized. Most commonly, environmental sounds are described in terms of an average level that has the same acoustical energy as the summation of all the time-varying events. This *energy-equivalent sound/noise descriptor* is called L_{eq} . The most common averaging period is hourly, but L_{eq} can describe any series of noise events of arbitrary duration.

The scientific instrument used to measure noise is the sound level meter. Sound level meters can accurately measure environmental noise levels to within about plus or minus 1 dBA. Various computer models are used to predict environmental noise levels from sources, such as roadways and airports. The accuracy of the predicted models depends upon the distance the receptor is from the noise source. Close to the noise source, the models are accurate to within about plus or minus 1 to 2 dBA.

Since the sensitivity to noise increases during the evening and at night -- because excessive noise interferes with the ability to sleep -- 24-hour descriptors have been developed that incorporate artificial noise penalties added to quiet-time noise events. The *Community Noise Equivalent Level (CNEL)* is a measure of the cumulative noise exposure in a community, with a 5 dB penalty added to evening (7:00 pm - 10:00 pm) and a 10 dB addition to nocturnal (10:00 pm - 7:00 am) noise levels. The *Day/Night Average Sound Level (DNL or L_{dn})* is essentially the same as CNEL, with the exception that the evening time period is dropped and all occurrences during this three-hour period are grouped into the daytime period.

Effects of Noise

Sleep and Speech Interference

The thresholds for speech interference indoors are about 45 dBA if the noise is steady and above 55 dBA if the noise is fluctuating. Outdoors the thresholds are about 15 dBA higher. Steady noises of sufficient intensity (above 35 dBA) and fluctuating noise levels above about 45 dBA have been shown to affect sleep. Interior residential standards for multi-family dwellings are set by the State of California at 45 dBA DNL. Typically, the highest steady traffic noise level during the daytime is about equal to the DNL and nighttime levels are 10 dBA lower. The standard is designed for sleep and speech protection and most jurisdictions apply the same criterion for all residential uses. Typical structural attenuation is 12-17 dBA with open windows. With closed windows in good condition, the noise attenuation factor is around 20 dBA for an older structure and 25 dBA for a newer dwelling. Sleep and speech interference is therefore possible when exterior noise levels are about 57-62 dBA DNL with open windows and 65-70 dBA DNL if the windows are closed. Levels of 55-60 dBA are common along collector streets and secondary arterials, while 65-70 dBA is a typical value for a primary/major arterial. Levels of 75-80 dBA are normal noise levels at the first row of development outside a freeway right-of-way. In order to achieve an acceptable interior noise environment, bedrooms facing secondary roadways need to be able to have their windows closed, and those facing major roadways and freeways typically need special glass windows.

Annoyance

Attitude surveys are used for measuring the annoyance felt in a community for noises intruding into homes or affecting outdoor activity areas. In these surveys, it was determined that the causes for annoyance include interference with speech, radio and television, house vibrations, and interference with sleep and rest. The DNL as a measure of noise has been found to provide a valid correlation of noise level and the percentage of people annoyed. People have been asked to judge the annoyance caused by aircraft noise and ground transportation noise. There continues to be disagreement about the relative annoyance of these different sources. When measuring the

percentage of the population highly annoyed, the threshold for ground vehicle noise is about 50 dBA DNL. At a DNL of about 60 dBA, approximately 12 percent of the population is highly annoyed. When the DNL increases to 70 dBA, the percentage of the population highly annoyed increases to about 25-30 percent of the population. There is, therefore, an increase of about 2 percent per dBA between a DNL of 60-70 dBA. Between a DNL of 70-80 dBA, each decibel increase increases by about 3 percent the percentage of the population highly annoyed. People appear to respond more adversely to aircraft noise. When the DNL is 60 dBA, approximately 30-35 percent of the population is believed to be highly annoyed. Each decibel increase to 70 dBA adds about 3 percentage points to the number of people highly annoyed. Above 70 dBA, each decibel increase results in about a 4 percent increase in the percentage of the population highly annoyed.

Fundamentals of Groundborne Vibration

Ground vibration consists of rapidly fluctuating motions or waves with an average motion of zero. Several different methods are typically used to quantify vibration amplitude. One method is the Peak Particle Velocity (PPV). The PPV is defined as the maximum instantaneous positive or negative peak of the vibration wave. In this report, a PPV descriptor with units of mm/sec or in/sec is used to evaluate construction generated vibration for building damage and human complaints. Table 3 displays the reactions of people and the effects on buildings that continuous vibration levels produce.

The annoyance levels shown in Table 3 should be interpreted with care since vibration may be found to be annoying at much lower levels than those shown, depending on the level of activity or the sensitivity of the individual. To sensitive individuals, vibrations approaching the threshold of perception can be annoying. Low-level vibrations frequently cause irritating secondary vibration, such as a slight rattling of windows, doors, or stacked dishes. The rattling sound can give rise to exaggerated vibration complaints, even though there is very little risk of actual structural damage.

Construction activities can cause vibration that varies in intensity depending on several factors. The use of pile driving and vibratory compaction equipment typically generates the highest construction related groundborne vibration levels. Because of the impulsive nature of such activities, the use of the PPV descriptor has been routinely used to measure and assess groundborne vibration and almost exclusively to assess the potential of vibration to induce structural damage and the degree of annoyance for humans.

The two primary concerns with construction-induced vibration, the potential to damage a structure and the potential to interfere with the enjoyment of life, are evaluated against different vibration limits. Studies have shown that the threshold of perception for average persons is in the range of 0.008 to 0.012 in/sec PPV. Human perception to vibration varies with the individual and is a function of physical setting and the type of vibration. Persons exposed to elevated ambient vibration levels, such as people in an urban environment, may tolerate a higher vibration level.

Structural damage can be classified as cosmetic only, such as minor cracking of building elements, or may threaten the integrity of the building. Safe vibration limits that can be applied to assess the potential for damaging a structure vary by researcher and there is no general consensus as to what

amount of vibration may pose a threat for structural damage to the building. Construction-induced vibration that can be detrimental to the building is very rare and has only been observed in instances where the structure is at a high state of disrepair and the construction activity occurs immediately adjacent to the structure.

Rail operations are potential sources of substantial groundborne vibration depending on distance, the type and the speed of trains, and the type of railroad track. People's response to groundborne vibration has been correlated best with the velocity of the ground. The velocity of the ground is expressed on the decibel scale. The reference velocity is 1×10^{-6} in/sec Root mean square (RMS), which equals 0 VdB, and 1 in/sec equals 120 VdB. Although not a universally accepted notation, the abbreviation "VdB" is used in this document for vibration decibels to reduce the potential for confusion with sound decibels. Typical levels of groundborne vibration are summarized in Table 4.

One of the problems with developing suitable criteria for groundborne vibration is the limited research into human response to vibration and more importantly human annoyance inside buildings. The U.S. Department of Transportation, Federal Transit Administration has developed rational vibration limits that can be used to evaluate human annoyance to groundborne vibration. These criteria are primarily based on experience with passenger train operations, such as rapid transit and commuter rail systems. The main difference between passenger and freight operations is the time duration of individual events; a passenger train lasts a few seconds whereas a long freight train may last several minutes, depending on speed and length.

TABLE 1 Definition of Acoustical Terms Used in this Report

Term	Definition
Decibel, dB	A unit describing, the amplitude of sound, equal to 20 times the logarithm to the base 10 of the ratio of the pressure of the sound measured to the reference pressure. The reference pressure for air is 20 micro Pascals.
Sound Pressure Level	Sound pressure is the sound force per unit area, usually expressed in micro Pascals (or 20 micro Newtons per square meter), where 1 Pascal is the pressure resulting from a force of 1 Newton exerted over an area of 1 square meter. The sound pressure level is expressed in decibels as 20 times the logarithm to the base 10 of the ratio between the pressures exerted by the sound to a reference sound pressure (e. g., 20 micro Pascals). Sound pressure level is the quantity that is directly measured by a sound level meter.
Frequency, Hz	The number of complete pressure fluctuations per second above and below atmospheric pressure. Normal human hearing is between 20 Hz and 20,000 Hz. Infrasonic sound are below 20 Hz and Ultrasonic sounds are above 20,000 Hz.
A-Weighted Sound Level, dBA	The sound pressure level in decibels as measured on a sound level meter using the A-weighting filter network. The A-weighting filter de-emphasizes the very low and very high frequency components of the sound in a manner similar to the frequency response of the human ear and correlates well with subjective reactions to noise.
Equivalent Noise Level, L_{eq}	The average A-weighted noise level during the measurement period.
L_{max} , L_{min}	The maximum and minimum A-weighted noise level during the measurement period.
L_{01} , L_{10} , L_{50} , L_{90}	The A-weighted noise levels that are exceeded 1%, 10%, 50%, and 90% of the time during the measurement period.
Day/Night Noise Level, L_{dn} or DNL	The average A-weighted noise level during a 24-hour day, obtained after addition of 10 decibels to levels measured in the night between 10:00 pm and 7:00 am.
Community Noise Equivalent Level, CNEL	The average A-weighted noise level during a 24-hour day, obtained after addition of 5 decibels in the evening from 7:00 pm to 10:00 pm and after addition of 10 decibels to sound levels measured in the night between 10:00 pm and 7:00 am.
Ambient Noise Level	The composite of noise from all sources near and far. The normal or existing level of environmental noise at a given location.
Intrusive	That noise which intrudes over and above the existing ambient noise at a given location. The relative intrusiveness of a sound depends upon its amplitude, duration, frequency, and time of occurrence and tonal or informational content as well as the prevailing ambient noise level.

Source: Handbook of Acoustical Measurements and Noise Control, Harris, 1998.

TABLE 2 Typical Noise Levels in the Environment

Common Outdoor Activities	Noise Level (dBA)	Common Indoor Activities
	110 dBA	Rock band
Jet fly-over at 1,000 feet		
	100 dBA	
Gas lawn mower at 3 feet		
	90 dBA	
Diesel truck at 50 feet at 50 mph		Food blender at 3 feet
	80 dBA	Garbage disposal at 3 feet
Noisy urban area, daytime		
Gas lawn mower, 100 feet	70 dBA	Vacuum cleaner at 10 feet
Commercial area		Normal speech at 3 feet
Heavy traffic at 300 feet	60 dBA	
		Large business office
Quiet urban daytime	50 dBA	Dishwasher in next room
Quiet urban nighttime	40 dBA	Theater, large conference room
Quiet suburban nighttime		
	30 dBA	Library
Quiet rural nighttime		Bedroom at night, concert hall (background)
	20 dBA	
		Broadcast/recording studio
	10 dBA	
	0 dBA	

Source: Technical Noise Supplement (TeNS), California Department of Transportation, November 2009.

TABLE 3 Reaction of People and Damage to Buildings from Continuous or Frequent Intermittent Vibration Levels

Velocity Level, PPV (in/sec)	Human Reaction	Effect on Buildings
0.01	Barely perceptible	No effect
0.04	Distinctly perceptible	Vibration unlikely to cause damage of any type to any structure
0.08	Distinctly perceptible to strongly perceptible	Recommended upper level of the vibration to which ruins and ancient monuments should be subjected
0.1	Strongly perceptible	Virtually no risk of damage to normal buildings
0.3	Strongly perceptible to severe	Threshold at which there is a risk of damage to older residential dwellings such as plastered walls or ceilings
0.5	Severe - Vibrations considered unpleasant	Threshold at which there is a risk of damage to newer residential structures

Source: Transportation and Construction Vibration Guidance Manual, California Department of Transportation, September 2013.

TABLE 4 Typical Levels of Groundborne Vibration

Human/Structural Response	Velocity Level, VdB (re 1µinch/sec, RMS)	Typical Events (50 –foot setback)
Threshold, minor cosmetic damage	100	Blasting, pile driving, vibratory compaction equipment Heavy tracked vehicles (Bulldozers, cranes, drill rigs)
Difficulty with tasks such as reading a video or computer screen	90	Commuter rail, upper range
Residential annoyance, infrequent events	80	Rapid transit, upper range
Residential annoyance, frequent events	70	Commuter rail, typical Bus or truck over bump or on rough roads Rapid transit, typical
Approximate human threshold of perception to vibration	60	Buses, trucks and heavy street traffic
Lower limit for equipment ultra-sensitive to vibration	50	Background vibration in residential settings in the absence of activity

Source: Illingworth & Rodkin, Inc. and U.S. Department of Transportation, Federal Transit Administration, Transit Noise and Vibration Impact Assessment, May 2006, FTA-VA-90-1003-0

Regulatory Background – Noise

The State of California and the City of San José have established regulatory criteria that are applicable in this assessment. The State CEQA Guidelines, Appendix G, are used to assess the potential significance of impacts pursuant to local General Plan policies, Municipal Code standards, or the applicable standards of other agencies. A summary of the applicable regulatory criteria is provided below.

State CEQA Guidelines. The CEQA contains guidelines to evaluate the significance of effects of environmental noise attributable to a proposed project. Under CEQA, noise impacts would be considered significant if the project would result in:

- (a) Exposure of persons to or generation of noise levels in excess of standards established in the local general plan or noise ordinance, or applicable standards of other agencies;
- (b) Exposure of persons to or generation of excessive groundborne vibration or groundborne noise levels;
- (c) A substantial permanent increase in ambient noise levels in the project vicinity above levels existing without the project;
- (d) A substantial temporary or periodic increase in ambient noise levels in the project vicinity above levels existing without the project;
- (e) For a project located within an airport land use plan or where such a plan has not been adopted within two miles of a public airport or public use airport, if the project would expose people residing or working in the project area to excessive noise levels; or
- (f) For a project within the vicinity of a private airstrip, if the project would expose people residing or working in the project area to excessive noise levels.

Pursuant to recent court decisions, the impacts of site constraints such as exposure of the proposed project to excessive levels of noise and vibration are not included in the Impacts and Mitigation Section of this report. Checklist items (a), (b), (e) and (f) are discussed with respect to the compatibility of the project with noise and vibration levels at the site in a separate section addressing Noise and Land Use Compatibility for consistency with the policies set forth in the City's General Plan.

The project is not located in proximity to sensitive land uses (i.e. residential, schools, etc.) so the operational noise impacts (e.g., from project generation traffic, mechanical ventilation system, and other features) of the project on surrounding land uses are not assessed. Potential short-term proximity construction noise and vibration impacts of the proposed project on surrounding land uses is addressed with respect to Checklist Questions (a), (b), and (d) in the Impacts and Mitigation Section of this report.

CEQA does not define what noise level increase would be considered substantial. Typically, an increase in the DNL noise level resulting from the project at noise sensitive land uses of 3 dBA or greater would be considered a significant impact when projected noise levels would exceed those considered acceptable for the affected land use. An increase of 5 dBA DNL or greater would be considered a significant impact when projected noise levels would remain within those considered acceptable for the affected land use.

2013 California Building Code, Title 24, Part 2. The current (2013) California Building Code (CBC) does not place limits on interior noise levels attributable to exterior environmental noise sources. The July 1, 2015 Supplement to the 2013 CBC corrects this omission, reinstating limits on interior noise levels attributable to exterior environmental noise sources which had been contained in all prior versions of the CBC dating back to 1974. In keeping with the provisions of the 2015 supplement, this report considers interior noise levels attributable to exterior environmental noise sources to be limited to a level not exceeding 45 dBA L_{dn} in any habitable room for new dwellings other than detached single-family dwellings.

City of San José General Plan. The Environmental Leadership Chapter in the Envision San José 2040 General Plan sets forth policies with the goal of minimizing the impact of noise on people through noise reduction and suppression techniques, and through appropriate land use policies in the City of San José. The following policies are applicable to the proposed project:

EC-1.1 Locate new development in areas where noise levels are appropriate for the proposed uses. Consider federal, State, and City noise standards and guidelines as a part of new development review. Applicable standards and guidelines for land uses in San José include:

Interior Noise Levels

- The City's standard for interior noise levels in residences, hotels, motels, residential care facilities, and hospitals is 45 dBA DNL. Include appropriate site and building design, building construction and noise attenuation techniques in new development to meet this standard. For sites with exterior noise levels of 60 dBA DNL or more, an acoustical analysis following protocols in the City-adopted California Building Code is required to demonstrate that development projects can meet this standard. The acoustical analysis shall base required noise attenuation techniques on expected Envision General Plan traffic volumes to ensure land use compatibility and General Plan consistency over the life of this plan.

Exterior Noise Levels

- The City's acceptable exterior noise level objective is 60 dBA DNL or less for residential and most institutional land uses (Table EC-1). The acceptable exterior noise level objective is established for the City, except in the environs of the San José International Airport and the Downtown, as described below:

- For new multi-family residential projects and for the residential component of mixed-use development, use a standard of 60 dBA DNL in usable outdoor activity areas, excluding balconies and residential stoops and porches facing existing roadways. Some common use areas that meet the 60 dBA DNL exterior standard will be available to all residents. Use noise attenuation techniques such as shielding by buildings and structures for outdoor common use areas. On sites subject to aircraft overflights or adjacent to elevated roadways, use noise attenuation techniques to achieve the 60 dBA DNL standard for noise from sources other than aircraft and elevated roadway segments.

Table EC-1: Land Use Compatibility Guidelines for Community Noise in San José

LAND USE CATEGORY	EXTERIOR NOISE EXPOSURE (DNL IN DECIBELS (DBA))					
	55	60	65	70	75	80
1. Residential, Hotels and Motels, Hospitals and Residential Care ¹						
2. Outdoor Sports and Recreation, Neighborhood Parks and Playgrounds						
3. Schools, Libraries, Museums, Meeting Halls, Churches						
4. Office Buildings, Business Commercial, and Professional Offices						
5. Sports Arena, Outdoor Spectator Sports						
6. Public and Quasi-Public Auditoriums, Concert Halls, Amphitheaters						

¹Noise mitigation to reduce interior noise levels pursuant to Policy EC-1.1 is required.

Normally Acceptable:



- Specified land use is satisfactory, based upon the assumption that any buildings involved are of normal conventional construction, without any special noise insulation requirements.

Conditionally Acceptable:



- Specified land use may be permitted only after detailed analysis of the noise reduction requirements and needed noise insulation features included in the design.

Unacceptable:



- New construction or development should generally not be undertaken because mitigation is usually not feasible to comply with noise element policies.

EC-1.2 Minimize the noise impacts of new development on land uses sensitive to increased noise levels (Categories 1, 2, 3 and 6) by limiting noise generation and by requiring use of noise attenuation measures such as acoustical enclosures and sound barriers, where feasible. The City considers significant noise impacts to occur if a project would:

- Cause the DNL at noise sensitive receptors to increase by five dBA DNL or more where the noise levels would remain “Normally Acceptable;” or
- Cause the DNL at noise sensitive receptors to increase by three dBA DNL or more where noise levels would equal or exceed the “Normally Acceptable” level.

EC-1.3 Mitigate noise generation of new nonresidential land uses to 55 dBA DNL at the property line when located adjacent to existing or planned noise-sensitive residential and public/quasi-public land uses.

EC-1.6 Regulate the effects of operational noise from existing and new industrial and commercial development on adjacent uses through noise standards in the City’s Municipal Code.

EC-1.7 Require construction operations within San José to use best available noise suppression devices and techniques and limit construction hours near residential uses per the City’s Municipal Code. The City considers significant construction noise impacts to occur if a project located within 500 feet of residential uses or 200 feet of commercial or office uses would:

- Involve substantial noise generating activities (such as building demolition, grading, excavation, pile driving, use of impact equipment, or building framing) continuing for more than 12 months.
- For such large or complex projects, a construction noise logistics plan that specifies hours of construction, noise and vibration minimization measures, posting or notification of construction schedules, and designation of a noise disturbance coordinator who would respond to neighborhood complaints will be required to be in place prior to the start of construction and implemented during construction to reduce noise impacts on neighboring residents and other uses.

City of San José Municipal Code. The City’s Municipal Code contains a Zoning Ordinance that limits noise levels at adjacent properties. Chapter 20.30.700 states that sound pressure levels generated by any use or combination of uses on a property shall not exceed 55 dBA at any property line shared with land zoned for residential use, except upon issuance and in compliance with a Conditional Use Permit. The code is not explicit in terms of the acoustical descriptor associated with the noise level limit. However, a reasonable interpretation of this standard, which is based on policy EC-1.3 of the City’s General Plan, would identify the ambient base noise level criteria as a day-night average noise level (DNL).

Chapter 20.100.450 of the Municipal Code establishes allowable hours of construction within 500 feet of a residential unit between 7:00 am and 7:00 pm Monday through Friday unless permission is granted with a development permit or other planning approval. No construction activities are permitted on the weekends at sites within 500 feet of a residence.

Santa Clara County Airport Land Use Commission Comprehensive Land Use Plan. The Comprehensive Land Use Plan adopted by the Santa Clara County Airport Land Use Commission contains standards for projects within the vicinity of San José International Airport which are relevant to this project;

4.3.2.1 Noise Compatibility Policies

Policy N-3 Noise impacts shall be evaluated according to the Aircraft Noise Contours presented on Figure 5 (2022 Aircraft Noise Contours).

Policy N-4 No residential or transient lodging construction shall be permitted within the 65 dB CNEL contour boundary unless it can be demonstrated that the resulting interior sound levels will be less than 45 dB CNEL and there are no outdoor patios or outdoor activity areas associated with the residential portion of a mixed use residential project or a multi-unit residential project. (Sound wall noise mitigation measures are not effective in reducing noise generated by aircraft flying overhead.)

Regulatory Background – Vibration

The Federal Transit Administration and the City of San José have established vibration guidelines applicable to this analysis.

Federal Transit Administration. The Federal Transit Administration (FTA) has identified vibration impact criteria for sensitive buildings, residences, and institutional land uses near rail transit and railroads. The thresholds for residences and buildings where people normally sleep (e.g., nearby residences) are 72 VdB for frequent events (more than 70 events of the same source per day), 75 VdB for occasional events (30 to 70 vibration events of the same source per day), and 80 VdB for infrequent events (less than 30 vibration events of the same source per day).

City of San José General Plan. The Environmental Leadership Chapter in the Envision San José 2040 General Plan sets forth policies to achieve the goal of minimizing vibration impacts on people, residences, and business operations in the City of San José. The following policies are applicable to the proposed project:

EC-2.1 Near light and heavy rail lines or other sources of groundborne vibration, minimize vibration impacts on people, residences, and businesses through the use of setbacks and/or structural design features that reduce vibration to levels at or below the guidelines of the Federal Transit Administration. Require new development within 100 feet of rail lines to demonstrate prior to project approval that vibration experienced by residents and vibration sensitive uses would not exceed these guidelines.

EC-2.3 Require new development to minimize vibration impacts to adjacent uses during demolition and construction. For sensitive historic structures, a vibration limit of 0.08 in/sec PPV will be used to minimize the potential for cosmetic damage to a

building. A vibration limit of 0.20 in/sec PPV will be used to minimize the potential for cosmetic damage at buildings of normal conventional construction.

Existing Noise Environment

The project site fronts Park Avenue in the center of the block between South Almaden Boulevard and South Market Street in the downtown area of San José, California. The site is surrounded by commercial uses, including the Tech Museum of Innovation located east of the site, the City National Civic Center located south of the site, and the Hyatt Hotel located west of the site. Restaurant, office, and parking uses are located across Park Avenue.

A noise monitoring survey was performed in the vicinity of the project site beginning on Tuesday, March 8, 2016 and concluding on Thursday, March 10, 2016. The noise environment at the site and in the surrounding areas results primarily from vehicular traffic along the local roadways. Intermittent overhead aircraft associated with the Mineta San José International Airport also affect the noise environment at the site. During attended measurements at the site, approximately 4 to 5 jets flew over the site every 10-minutes, generating maximum noise levels in the range of 73 to 83 dBA L_{max} . Two Santa Clara Valley Transportation Authority (VTA) light rail train (LRT) routes run along East San Carlos Street, with trains running frequently between the hours of 4:30 am and 12:30 am daily. LRT bell soundings occur as the trains exit the stop located on San Carlos Street, east of Almaden Boulevard. The monitoring survey included two long-term noise measurements and three short-term measurements, as shown in Figure 1. Table 5 summarizes the results of the short-term measurements. The results of the long-term noise measurements are shown in Appendix A.

Long-term noise measurement LT-1 was made at a distance of about 55 feet from the center of Park Avenue. The primary noise source at this location is traffic along Park Avenue, with occasional noises generated by aircraft overflights. Hourly average noise levels ranged from 63 to 73 dBA L_{eq} at this location during daytime hours, and from 54 to 68 dBA L_{eq} at night. The day-night average noise level on Wednesday, March 9, 2016 was 68 dBA DNL. Maximum noise levels intermittently reached 90 to 93 dBA L_{max} , with daytime maximum levels typically in the range of 75 to 85 dBA L_{max} .

LT-2 was measured west of Parkside Hall, about 225 feet south of the center of Park Avenue. The primary noise sources at this location were traffic on the surrounding roadways and intermittent jet overflights. Hourly average noise levels at this location ranged from 60 to 67 dBA L_{eq} during the day and from 50 to 65 dBA L_{eq} at night. The day-night average noise level on Wednesday, March 9, 2016 was 66 dBA DNL. Maximum noise levels intermittently reached 86 to 89 dBA L_{max} , with daytime maximum levels typically in the range of 75 to 85 dBA L_{max} .

FIGURE 1 Noise Measurement Locations



TABLE 5 Summary of Short-Term Noise Measurement Data

Noise Measurement Location	Measured Noise Levels, dBA					DNL, dBA*	Primary Noise Source
	L(1)	L(10)	L(50)	L(90)	Leq		
ST-1: 75 feet east of center of Almaden Boulevard (3/10/2016, 9:50 am - 10:00 am)	78	71	64	60	68	69	Traffic on Almaden Blvd, Jets (5)
ST-2: 75 feet north of center of San Carlos Street (3/10/2016, 10:10 am - 10:20 am)	81	74	66	59	71	71	Traffic on San Carlos St, Jets (4), LRT (3)
ST-3: 75 feet west of center of Market Street (3/10/2016, 10:30 am - 10:40 am)	77	70	60	56	65	66	Traffic on Market St, Jets (4),

*DNL levels calculated through comparison between short-term and long-term noise levels.

GENERAL PLAN CONSISTENCY ANALYSIS

Noise and Land Use Compatibility

The Environmental Leadership Chapter in the Envision San José 2040 General Plan sets forth policies with the goal of minimizing the impact of noise on people through noise reduction and suppression techniques, and through appropriate land use policies in the City of San José. The applicable General Plan policies were presented in detail in the Regulatory Background section and are summarized below for the proposed project:

- The City's acceptable exterior noise level objective is 60 dBA DNL or less for the proposed residential, hotel, and museum uses and 70 dBA DNL for the proposed office uses (Table EC-1).
- The City's standard for interior noise levels in residences and hotel rooms is 45 dBA DNL.

The project would construct a 24-story building with 300 to 370 dwelling units, 155 hotel rooms, a 63,030 square foot museum, and 176,705 square feet of office space. The future noise environment at the project site would continue to result primarily from traffic along the surrounding roadways, jet overflights, LRT operations, and downtown activities. The entire site would be exposed to noise levels exceeding 65 dBA DNL, resulting from airport operations from Norman Y. Mineta San José International Airport (see discussion below). A cumulative of existing noise sources, including aircraft, vehicular traffic, and other downtown activities, generate noise levels of 65 to 68 dBA DNL at the ground level façades of the proposed building. The noise level increase for the Central/Downtown section of the City estimated in the noise assessment conducted for the Envision San José 2040 General Plan Comprehensive Update¹ was 1 dB by 2035, resulting in noise exposures of 66 to 69 dBA DNL at ground level façades. Noise levels are anticipated to be about 1 dBA higher 4th floor exposures, due to the reduction in shielding provided by the surrounding buildings. Above the 4th floor, noise levels drop off as the distance from the ground level noise source increases.

Future Exterior Noise Environment

The project proposes to landscape the rooftop area as outdoor recreational space. Noise levels throughout the rooftop area would be exposed to aircraft noise levels exceeding 65 dBA DNL (see discussion below). Additionally, traffic from adjacent roadways would result in noise levels near the edges of the rooftop of up to 69 dBA DNL under future conditions.

Aircraft noise levels cannot feasibly be mitigated in the rooftop space while keeping the rooftop open to the outside. Traffic noise levels can be reduced through site planning or the construction of parapets walls along the outer edges of the rooftop.

Future Interior Noise Environment

¹ Illingworth and Rodkin, Inc., "Envision San José 2040 General Plan Comprehensive Update Environmental Noise Assessment", December 2010.

The City of San José requires that interior noise levels be maintained at 45 dBA DNL or less for residences and hotel rooms. Hotel rooms would be located on floors 2 through 5 and residential units would be located on floors 7 through 24. Assuming a 1 dBA increase in noise levels under future conditions, the exterior noise exposure at lower levels of these façades would range from about 69 dBA DNL for the façade facing Park Avenue to about 65 dBA DNL in shielded locations. At the 4th floor exposure, where the proposed tower would not be shielded from traffic noise by the surrounding buildings, noise levels are anticipated to increase by about 1 dBA, resulting in exterior noise levels of up to about 70 dBA DNL. Above the 4th floor, noise levels drop off as the distance from the ground level noise source increases.

Interior noise levels would vary depending upon the design of the buildings (relative window area to wall area) and the selected construction materials and methods. Standard residential construction provides approximately 15 dBA of exterior-to-interior noise reduction, assuming the windows are partially open for ventilation. Standard construction with the windows closed provides approximately 20 to 25 dBA of noise reduction in interior spaces. Where exterior noise levels range from 60 to 65 dBA DNL, the inclusion of adequate forced-air mechanical ventilation is often the method selected to reduce interior noise levels to acceptable levels by closing the windows to control noise. Where noise levels exceed 65 dBA DNL, forced-air mechanical ventilation systems and sound-rated construction methods are normally required. Such methods or materials may include a combination of smaller window and door sizes as a percentage of the total building façade facing the noise source, sound-rated windows and doors, sound-rated exterior wall assemblies, and mechanical ventilation so windows may be kept closed at the occupant's discretion.

For the proposed project, the interior noise levels with standard construction and windows open would be up to 55 dBA DNL, which exceeds the City's threshold for interior noise. With windows in the closed position, interior noise levels would be in the range of 40 to 50 dBA DNL.

Aircraft Noise

Mineta San José International Airport is a public-use airport located approximately two miles northwest of the project site. Aircraft overflights occur regularly (about every 2 to 3 minutes during the day) and typically generate maximum noise levels in the range of 75 to 85 dBA L_{max}. The project site inside the 2027 65 dBA CNEL noise contour shown in the Norman Y. Mineta San José International Airport Master Plan Update Project for the airport. As a result, residential and transient lodging would be considered incompatible with the aircraft noise levels at the site, unless it can be demonstrated that the resulting interior sound levels will be less than 45 dB CNEL. There are no outdoor patios proposed for the site. The landscaped rooftop area would be considered incompatible with aircraft noise levels at the site.

Recommended Conditions of Approval

For consistency with the General Plan the following Conditions of Approval are recommended for consideration by the City:

- Methods available to reduce exterior traffic noise levels in rooftop level outdoor use areas include site planning alternatives (e.g., altering the orientation of the proposed buildings to use the proposed buildings as noise barriers) and/or the construction of parapet walls.
 - Preliminary calculations indicate that the construction of 3.5 foot high parapet walls, as measured above the base elevation of the rooftop use area, would reduce exterior noise levels to about 65 dBA DNL. Noise levels could not feasibly be reduced below 65 dBA DNL in outdoor areas at the site due to aircraft operations. Parapet walls would need to be located along all outer edges of the use areas and attach to the proposed buildings on both sides. To be effective, the parapet wall must be constructed with a solid material with no gaps in the face of the wall or at the base. Openings or gaps between sound wall materials or the ground substantially decrease the effectiveness of the sound wall. Suitable materials for sound wall construction should have a minimum surface weight of 3 pounds per square foot (such as 1-inch-thick wood, ½-inch laminated glass, masonry block, concrete, or metal one-inch). The final recommendations for mitigation shall be confirmed when detailed plans are available.
- Provide a suitable form of forced-air mechanical ventilation, as determined by the local building official, for all project residences, so that windows can be kept closed to control noise.
- Provide sound rated windows to maintain interior noise levels at acceptable levels. Preliminary calculations show that sound-rated windows with minimum STC² Ratings of 28 to 32 would be satisfactory for units to achieve acceptable interior noise levels. The specific determination of what noise insulation treatments are necessary shall be conducted on a room-by-room basis during final design of the project.
- A qualified acoustical specialist shall prepare a detailed analysis of interior residential noise levels resulting from all exterior sources during the design phase pursuant to requirements set forth in the State Building Code. The study will also establish appropriate criteria for noise levels inside the commercial and office spaces affected by environmental noise. The study will review the final site plan, building elevations, and floor plans prior to construction and recommend building treatments to reduce residential interior noise levels to 45 dBA DNL or lower and reduce levels to the established criteria for the business and commercial uses; and, address and adequately control the noise from adjacent rooftop equipment. Treatments would include, but are not limited to, sound-rated windows and doors, sound-rated wall and window constructions, acoustical caulking, protected ventilation openings, etc. The specific determination of what noise insulation treatments are necessary shall be conducted on a unit-by-unit basis during final design of the project. Results of the analysis, including the description of the necessary noise control treatments,

²**Sound Transmission Class (STC)** A single figure rating designed to give an estimate of the sound insulation properties of a partition. Numerically, STC represents the number of decibels of speech sound reduction from one side of the partition to the other. The STC is intended for use when speech and office noise constitute the principal noise problem.

shall be submitted to the City, along with the building plans and approved design, prior to issuance of a building permit.

There are no feasible methods to reduce aircraft noise to acceptable levels in the landscaped rooftop area, while keeping the rooftop area open to the outdoors. As a result, even with the Conditional of Approval, as stated above, exterior noise levels in the rooftop use area would be considered incompatible with the land use.

LRT Vibration and Land Use Compatibility

The Environmental Leadership Chapter in the Envision San José 2040 General Plan sets forth policies with the goal of minimizing the impact of heavy and light rail vibration on people through appropriate land use policies in the City of San José. Policy EC-2.1 requires new development within 100 feet of light and heavy rail lines or other sources of groundborne vibration, to use setbacks and/or structural design features that reduce vibration to levels at or below the guidelines of the FTA. The proposed building would be located more than 300 feet from the LRT track. As a result, the project would be considered compatible with the LRT vibration environment.

NOISE IMPACTS AND MITIGATION MEASURES

Significance Criteria

Paraphrasing from Appendix G of the CEQA Guidelines, a project would normally result in significant noise impacts if noise levels generated by the project conflict with adopted environmental standards or plans, if the project would generate excessive groundborne vibration levels, or if ambient noise levels at sensitive receivers would be substantially increased over a permanent, temporary, or periodic basis. The following criteria were used to evaluate the significance of environmental noise resulting from the project:

- **Groundborne Vibration from Construction:** A significant impact would be identified if the construction of the project would expose persons to excessive vibration levels. Groundborne vibration levels exceeding 0.2 in/sec PPV would have the potential to result in cosmetic damage to normal buildings. For sensitive historic structures, groundborne vibration levels exceeding 0.08 in/sec PPV would be considered significant.
- **Construction Noise:** A significant noise impact would be identified if construction-related noise would temporarily increase ambient noise levels at sensitive receptors. Hourly average noise levels exceeding 60 dBA L_{eq} at the property lines shared with residential land uses, and the ambient by at least 5 dBA L_{eq} , for a period of more than one year would constitute a significant temporary noise increase at adjacent residential land uses. Hourly average noise levels exceeding 70 dBA L_{eq} at the property lines shared with residential land uses, and the ambient by at least 5 dBA L_{eq} , for a period of more than one year would constitute a significant temporary noise increase at adjacent commercial land uses.

Impact 1: **Groundborne Vibration from Construction.** Public and commercial buildings in the vicinity of the project site would be exposed to construction-related vibration,

particularly during impact pile driving events. **This is a potentially significant impact.**

The construction of the project may generate perceptible vibration when heavy equipment or impact tools (e.g. jackhammers, hoe rams) are used. Construction activities would include site demolition work, preparation work, excavation of below-grade levels, foundation work, and new building framing and finishing. Table 6 presents typical vibration levels that could be expected from construction equipment at a distance of 25 feet.

TABLE 6 Vibration Source Levels for Construction Equipment

Equipment		PPV at 25 ft. (in/sec)	Approximate L _v at 25 ft. (VdB)
Pile Driver (Impact)	upper range	1.158	112
	typical	0.644	104
Pile Driver (Sonic)	upper range	0.734	105
	typical	0.170	93
Clam shovel drop		0.202	94
Hydromill (slurry wall)	in soil	0.008	66
	in rock	0.017	75
Vibratory Roller		0.210	94
Hoe Ram		0.089	87
Large bulldozer		0.089	87
Caisson drilling		0.089	87
Loaded trucks		0.076	86
Jackhammer		0.035	79
Small bulldozer		0.003	58

Source: Transit Noise and Vibration Impact Assessment, United States Department of Transportation, Office of Planning and Environment, Federal Transit Administration, May 2006.

According to Policy EC-2.3 of the City of San José General Plan, a vibration limit of 0.08 in/sec PPV shall be used to minimize the potential for cosmetic damage to sensitive historical structures, and a vibration limit of 0.2 in/sec PPV shall be used to minimize damage at buildings of normal conventional construction. The City National Civic and Montgomery Theater buildings, both located southeast of the site along San Carlos Street, are considered historical structures. The 0.08 in/sec PPV criteria would be applied at these structures. For the remaining adjacent buildings, a significant impact would occur if buildings were exposed to vibration levels in excess of 0.2 in/sec PPV.

Impact pile driving has the potential of generating the highest ground vibration levels and would be the primary concern to structural damage, particularly when it occurs within 100 to 200 feet of structures. Impact pile driving, which produces substantial vibrations, is anticipated to occur during grading and excavation of the site. Impact pile driving could be anticipated to generate vibration levels of 0.644 in/sec PPV but could reach levels up to 1.158 in/sec PPV at 25 feet. Other project construction activities, such as drilling, the use of jackhammers, rock drills and other high-power or vibratory tools, and rolling stock equipment (tracked vehicles, compactors, etc.) may also generate substantial vibration in the immediate vicinity. Jackhammers typically generate vibration

levels of 0.035 in/sec PPV, and drilling typically generates vibration levels of 0.09 in/sec PPV at a distance of 25 feet. Vibration levels would vary depending on soil conditions, construction methods, and equipment used.

The project site is surrounded by existing structures. The Tech Museum of Innovation and the City National Civic Center (historic) are located directly adjacent to the proposed building footprint and the parking garage to the west is located as close as 20 feet from the proposed parking below Paseo. The Hyatt Hotel is located about 120 feet southwest of the project and structures across Park Avenue are as close as 150 feet from the site.

At a distance of 20 feet, impact pile driving levels up to 1.5 in/sec PPV could be anticipated, with typical impact pile driving levels of 0.8 in/sec PPV. At a distance of 120 feet, impact pile driving levels up to 0.2 in/sec PPV could be anticipated, with typical impact pile driving levels of 0.11 in/sec PPV. Vibration levels from construction equipment, other than pile driving, would generate vibration levels up to 0.3 in/sec PPV at 20 feet and up to 0.04 in/sec PPV at 120 feet.

Due to the close proximity of the surrounding buildings to the project site, adjacent structures would be exposed to excessive vibration levels during pile driving activities. Upper range impact pile driving would exceed the 0.08 in/sec PPV historic building threshold within 275 feet of activities, with typical levels exceeding the historic building threshold within about 160 feet of activities. For buildings of normal construction, upper range pile driving vibration levels would exceed the 0.2 in/sec PPV threshold within about 120 feet of construction, with typical levels exceeding the threshold within about 75 feet of activities.

Other construction equipment, such as clam shovel drops, vibratory rollers, hoe rams, large bulldozers, caisson drillings, loaded trucks, and jackhammers would not be anticipated to cause vibration levels in excess of the City's vibration threshold for buildings of normal construction at distances exceeding 25 feet from construction. The City's vibration threshold for sensitive historic structures would be anticipated to be exceeded within about 60 feet of construction equipment other than pile driving.

Based on the scope of construction and the density of development in the downtown area, there is a potentially significant impact due to groundborne vibrations from construction during pile driving activities at the City National Civic and Montgomery Theater buildings (historic), the Tech Museum, the parking garage on South Almaden Boulevard, and the Hyatt Hotel. Other construction equipment would have the potential to generate significant vibration levels at the City National Civic (historic), the Tech Museum, and the parking garage. Vibration levels may still be perceptible in areas further from the site during periods of heavy construction, but would not be expected to cause structural damage. This is a **potentially significant** impact.

Mitigation Measure 1:

The following measures, in addition to the best construction practices specified in Mitigation Measure 2, are recommended to reduce vibration impacts from construction activities:

- Avoid impact pile driving where possible. Drilled piers or rammed aggregate piers cause lower vibration levels where geological conditions permit their use.

- A list of all heavy construction equipment to be used for this project and the anticipated time duration of using the equipment that is known to produce high vibration levels (clam shovel drops, vibratory rollers, hoe rams, large bulldozers, caisson drillings, loaded trucks, jackhammers, etc.) shall be submitted by the contractor. This list shall be used to identify equipment and activities that would potentially generate substantial vibration and to define the level of effort required for continuous vibration monitoring. Where possible, use of the heavy vibration-generating construction equipment shall be prohibited within 25 feet of any adjacent building.
- A construction vibration monitoring plan shall be implemented to document conditions prior to, during, and after vibration generating construction activities. All plan tasks shall be undertaken under the direction of a licensed Professional Structural Engineer in the State of California and be in accordance with industry-accepted standard methods. The construction vibration monitoring plan should be implemented to include the following tasks:
 - Identification of the sensitivity of nearby structures to groundborne vibration. Vibration limits should be applied to all vibration-sensitive structures located within 300 feet of any pile driving activities and 75 feet of other construction activities identified as sources of high vibration levels.
 - Performance of a photo survey, elevation survey, and crack monitoring survey for each structure of normal construction within 200 feet of pile driving activities and/or within 50 feet of other construction activities identified as sources of high vibration levels and each historic structure within 300 feet of pile driving activities and/or within 75 feet of other construction activities. Surveys shall be performed prior to any construction activity, in regular interval during construction, and after project completion, and shall include internal and external crack monitoring in structures, settlement, and distress, and shall document the condition of foundations, walls and other structural elements in the interior and exterior of said structures.
 - Development of a vibration monitoring and construction contingency plan to identify structures where monitoring would be conducted, set up a vibration monitoring schedule, define structure-specific vibration limits, and address the need to conduct photo, elevation, and crack surveys to document before and after construction conditions. Construction contingencies would be identified for when vibration levels approached the limits.
 - At a minimum, vibration monitoring should be conducted during pavement demolition, excavation, and pile driving activities. Monitoring results may indicate the need for more or less intensive measurements.
 - If vibration levels approach limits, suspend construction and implement contingencies to either lower vibration levels or secure the affected structures.

- Designate a person responsible for registering and investigating claims of excessive vibration. The contact information of such person shall be clearly posted on the construction site.
- Conduct post-survey on structures where either monitoring has indicated high levels or complaints of damage has been made. Make appropriate repairs or compensation where damage has occurred as a result of construction activities.
- The results of all vibration monitoring shall be summarized and submitted in a report shortly after substantial completion of each phase identified in the project schedule. The report will include a description of measurement methods, equipment used, calibration certificates, and graphics as required to clearly identify vibration-monitoring locations. An explanation of all events that exceeded vibration limits will be included together with proper documentation supporting any such claims.

The implementation of these mitigation measures would reduce the impact to a **less-than-significant** level.

Impact 2: Construction Noise. Existing noise-sensitive land uses would be exposed to construction noise levels in excess of the significance thresholds for a period of more than one year. **This is a potentially significant impact.**

Project construction is anticipated to occur over a period of about 40 months. Impact pile driving, which produces substantial noise levels, is anticipated to occur during grading and excavation of the site. Noise impacts resulting from construction depend upon the noise generated by various pieces of construction equipment, the timing and duration of noise-generating activities, and the distance between construction noise sources and noise-sensitive areas. Construction noise impacts primarily result when construction activities occur during noise-sensitive times of the day (e.g., early morning, evening, or nighttime hours), the construction occurs in areas immediately adjoining noise-sensitive land uses, or when construction lasts over extended periods of time.

Where noise from construction activities exceeds 60 dBA L_{eq} and exceeds the ambient noise environment by at least 5 dBA L_{eq} at noise-sensitive residential or school uses in the project vicinity for a period exceeding one year, the impact would be considered significant. For commercial uses, a significant impact would be identified if construction noise were to exceed 70 dBA L_{eq} and exceeds the ambient noise environment by at least 5 dBA L_{eq} for a period exceeding one year. Additionally, the City considers significant construction noise impacts to have occurred if a project located within 500 feet of residential uses or 200 feet of commercial or office uses would involve substantial noise-generating activities (such as building demolition, grading, excavation, pile driving, use of impact equipment, or building framing) continuing for more than 12 months, according to Policy EC-1.7 of the General Plan.

Construction activities would be carried out in stages. During each stage of construction, there would be a different mix of equipment operating, and noise levels would vary by stage and vary within stages, based on the amount of equipment in operation and the location at which the equipment is operating. Typical construction noise levels at a distance of 50 feet are shown in Tables 7 and 8. Table 7 shows the average noise level ranges, by construction phase, and Table 8

shows the maximum noise level ranges for different construction equipment. Most demolition and construction noise falls with the range of 80 to 90 dBA at a distance of 50 feet from the source.

TABLE 7 Typical Ranges of Construction Noise Levels at 50 Feet, L_{eq} (dBA)

	Domestic Housing		Office Building, Hotel, Hospital, School, Public Works		Industrial Parking Garage, Religious Amusement & Recreations, Store, Service Station		Public Works Roads & Highways, Sewers, and Trenches	
	I	II	I	II	I	II	I	II
Ground Clearing	83	83	84	84	84	83	84	84
Excavation	88	75	89	79	89	71	88	78
Foundations	81	81	78	78	77	77	88	88
Erection	81	65	87	75	84	72	79	78
Finishing	88	72	89	75	89	74	84	84
I - All pertinent equipment present at site. II - Minimum required equipment present at site.								

Source: U.S.E.P.A., Legal Compilation on Noise, Vol. 1, p. 2-104, 1973.

TABLE 8 Construction Equipment 50-foot Noise Emission Limits

Equipment Category	L _{max} Level (dBA) ^{1,2}	Impact/Continuous
Arc Welder	73	Continuous
Auger Drill Rig	85	Continuous
Backhoe	80	Continuous
Bar Bender	80	Continuous
Boring Jack Power Unit	80	Continuous
Chain Saw	85	Continuous
Compressor ³	70	Continuous
Compressor (other)	80	Continuous
Concrete Mixer	85	Continuous
Concrete Pump	82	Continuous
Concrete Saw	90	Continuous
Concrete Vibrator	80	Continuous
Crane	85	Continuous
Dozer	85	Continuous
Excavator	85	Continuous
Front End Loader	80	Continuous
Generator	82	Continuous
Generator (25 KVA or less)	70	Continuous
Gradall	85	Continuous
Grader	85	Continuous
Grinder Saw	85	Continuous
Horizontal Boring Hydro Jack	80	Continuous
Hydra Break Ram	90	Impact
Impact Pile Driver	105	Impact
Insitu Soil Sampling Rig	84	Continuous
Jackhammer	85	Impact
Mounted Impact Hammer (hoe ram)	90	Impact
Paver	85	Continuous
Pneumatic Tools	85	Continuous
Pumps	77	Continuous
Rock Drill	85	Continuous
Scraper	85	Continuous
Slurry Trenching Machine	82	Continuous
Soil Mix Drill Rig	80	Continuous
Street Sweeper	80	Continuous
Tractor	84	Continuous
Truck (dump, delivery)	84	Continuous
Vacuum Excavator Truck (vac-truck)	85	Continuous
Vibratory Compactor	80	Continuous
Vibratory Pile Driver	95	Continuous
All other equipment with engines larger than 5 HP	85	Continuous

Notes:

¹ Measured at 50 feet from the construction equipment, with a “slow” (1 sec.) time constant.² Noise limits apply to total noise emitted from equipment and associated components operating at full power while engaged in its intended operation.³ Portable Air Compressor rated at 75 cfm or greater and that operates at greater than 50 psi.

Source: Mitigation of Nighttime Construction Noise, Vibrations and Other Nuisances, National Cooperative Highway Research Program, 1999.

Construction activities generate considerable amounts of noise, especially during pile driving and earth-moving activities when heavy equipment is used. The construction of the proposed project would involve demolition of existing structures and pavement, site preparation, grading and excavation, trenching, building erection, and paving. The hauling of excavated materials and construction materials would generate truck trips on local roadways as well.

Table 9 shows the calculated construction noise levels for each phase of construction, based on the equipment specified for the project, at a distance of 50 feet from the center of the construction activity.

TABLE 9 Calculated Construction Noise Levels for Each Phase of Construction

Construction Phase		At Distance of 50 ft.	
		L _{eq} , dBA	L _{max} , dBA
Demolition, Nov to Dec 2016		87	90
Site Preparation, Jan to Feb 2017		85	85
Grading/Excavation, March to August 2017	Including Pile Driving	95	101
	Without Pile Driving	88	88
Trenching, Feb to Dec 2017		83	84
Building-Exterior, Aug 2017 to Feb 2020		85	85
Building-Interior, Dec 2017 to Feb 2020		Minimal Off-Site	Minimal Off-Site
Paving, Oct 2019 to Feb 2020		83	83

¹ Calculated using a standard drop off rate for point sources of 6 dB per doubling of distance.

At 50 feet from the noise source, maximum noise levels generated by project construction equipment would typically range from 83 to 90 dBA L_{max}. Impact pile driving generates maximum noise levels of up to about 101 dBA L_{max} at a distance of 50 feet.

Noise sensitive uses surrounding the site include the Tech Museum of Innovation located east of the site, the City National Civic Center located south of the site, and the Hyatt Hotel located to the west of the site. Restaurant, office, and parking uses are located across Park Avenue. There are no residential uses in close proximity to the site.

The Tech Museum of Innovation and the City National Civic Center (historic) are located directly adjacent to the proposed building footprint and the parking garage to the west is located as close as 20 feet from the proposed parking below Paseo. The Hyatt Hotel is located about 120 feet southwest of the project and structures across Park Avenue are as close as 150 feet from the site. At these distance, noise levels due to construction activities would exceed 70 dBA L_{eq} and ambient levels by more than 5 dBA L_{eq} over a period exceeding one year. Construction-generated noise levels drop off at a rate of about 6 dBA per doubling of the distance between the source and receptor. Shielding by buildings or terrain can provide an additional 5 to 10 dBA noise reduction from ground level construction activities at distant receptors. However, adjacent structures would not provide shielding from upper level construction. This would be considered a **potentially significant** impact.

Mitigation Measure 2:

Policy EC-1.7 of the City's General Plan states that for large or complex projects within 500 feet of residential land uses or within 200 feet of commercial land uses or offices involving substantial noise-generating activities lasting more than 12 months, a construction noise logistics plan that specifies hours of construction, noise and vibration minimization measures, posting or notification of construction schedules, and designation of a noise disturbance coordinator who would respond to neighborhood complaints will be required to be in place prior to the start of construction and implemented during construction to reduce noise impacts on neighboring residents and other uses.

Modification, placement, and operation of construction equipment are possible means for minimizing the impact on the existing sensitive receptors. Construction equipment should be well-maintained and used judiciously to be as quiet as possible. Additionally, construction activities for the proposed project should include the following best management practices to reduce noise from construction activities near sensitive land uses:


- Construction activities shall be limited to the hours between 7:00 am and 7:00 pm, Monday through Friday, unless permission is granted with a development permit or other planning approval. No construction activities are permitted on the weekends at sites within 500 feet of a residence.
- Construct solid plywood fences around ground level construction sites adjacent to operational businesses, hotels, and other noise-sensitive land uses.
- Equip all internal combustion engine-driven equipment with intake and exhaust mufflers that are in good condition and appropriate for the equipment.
- Unnecessary idling of internal combustion engines should be strictly prohibited.
- Locate stationary noise-generating equipment such as air compressors or portable power generators as far as possible from sensitive receptors. Construct temporary noise barriers to screen stationary noise-generating equipment when located near adjoining sensitive land uses. Temporary noise barriers could reduce construction noise levels by 5 dBA.
- Utilize "quiet" air compressors and other stationary noise sources where technology exists.
- Control noise from construction workers' radios to a point where they are not audible at existing residences bordering the project site.
- Notify all adjacent business, residences, and other noise-sensitive land uses of the construction schedule, in writing, and provide a written schedule of "noisy" construction activities to the adjacent land uses and nearby residences.
- A temporary noise control blanket barrier could be erected, if necessary, along building facades facing construction sites. This mitigation would only be necessary if conflicts

occurred which were irresolvable by proper scheduling. Noise control blanket barriers can be rented and quickly erected.


- Pre-drill foundation pile holes to minimize the number of impacts required to seat the pile.
- Consider the use of “acoustical blankets” for receptors located within 100 feet of the site during pile driving activities.
- Designate a "disturbance coordinator" who would be responsible for responding to any complaints about construction noise. The disturbance coordinator will determine the cause of the noise complaint (e.g., bad muffler, etc.) and will require that reasonable measures be implemented to correct the problem. Conspicuously post a telephone number for the disturbance coordinator at the construction site and include in it the notice sent to neighbors regarding the construction schedule.

Implementation of the above measures would reduce construction noise levels emanating from the site, limit construction hours, and minimize disruption and annoyance. With the implementation of these measures, and recognizing that noise generated by construction activities would occur over a temporary period, the temporary increase in ambient noise levels would be **less-than-significant**.


**Noise Levels at Noise Measurement Site LT-1
55 feet from Center of Park Avenue
Tuesday, March 8, 2016**




**Noise Levels at Noise Measurement Site LT-1
55 feet from Center of Park Avenue
Wednesday, March 9, 2016**




**Noise Levels at Noise Measurement Site LT-1
55 feet from Center of Park Avenue
Thursday, March 10, 2016**



**Noise Levels at Noise Measurement Site LT-2
West of Parkside Hall
Tuesday, March 8, 2016**



**Noise Levels at Noise Measurement Site LT-2
West of Parkside Hall
Wednesday, March 9, 2016**



**Noise Levels at Noise Measurement Site LT-2
West of Parkside Hall
Thursday, March 10, 2016**

