

Shaw Environmental, Inc.

A CB&I Company 4005 Port Chicago Highway Concord, California 94520-1120 Phone: 925.288.9898

Fax: 925.288.0888 www.CBI.com

July 19, 2013

Shaw Project No. 149327

Mr. Aaron Costa Hazardous Materials Specialist II Local Oversight Program County of Santa Clara Department of Environmental Health 1555 Berger Drive, Suite 300 San Jose, California 95112-2716

Subject: Additional Site Assessment Report

AT&T Facility

95 South Almaden Avenue San Jose, California

Dear Mr. Costa:

Please find enclosed the Additional Site Assessment Report requested in your letter dated March 11, 2013 for additional off-site investigation to delineate the extent of any underlying impact at the AT&T facility. The anticipated work plan was completed with the exception of the soil borings along West San Fernando Street. As outlined in the attached report and in a July 8, 2013 email sent to your department, boring attempts along West San Fernando Street were unsuccessful. The guidelines of our drilling/access permits, and the high volume of utilities in the area limited available areas for exploration. Attempts were made at six locations with refusal at only 9 to 13 inches below surface grade. At this time, we do not see an easy solution to collecting soil/groundwater samples in this area of the site within a reasonable time frame and cost effective manner. AT&T has deployed a tremendous amount of time and money in order to accomplish this within limits set forth in required permits for working in the area. Moving further across W. San Fernando Street or even farther south across S. Almaden would likely require new permits and traffic plans to be developed. We would like to discuss with you at your convenience.

If you have any questions regarding the information presented in this report, please contact Robert Delnagro with Shaw at (925) 288-2103, Joseph Pickard with Shaw at (925) 288-2366, or Mr. Mark Smith with AT&T EH&S at (214) 464-8173. Any written correspondence should be directed to:

Mr. Mark Smith AT&T EH&S 308 South Akard; Room 1700 Dallas, Texas 75202 Mr. Aaron Costa July 19, 2013 Page 2

Thank you for your assistance with this project.

Sincerely,

Shaw Environmental, Inc.

Joseph Pickard Project Scientist

cc: Mr. Mark Smith - AT&T EH&S

Perjury Statement

I declare, under penalty of perjury, that the information and/or recommendations contained in the attached report are true and correct to the best of my knowledge

7/18/2013

Mr. Mark Smith

AT&T EH&S

Date

ADDITIONAL SITE ASSESSMENT REPORT AT&T FACILITY 95 SOUTH ALMADEN AVENUE SAN JOSE, CALIFORNIA

Prepared for:

AT&T Environment, Health & Safety 308 South Akard, Room 1700 Dallas, Texas 75202

Prepared by:

Shaw Environmental, Inc. (a CB&I Company) 4005 Port Chicago Highway Concord, California 94520

Shaw Project No. 149327.06

July 19, 2013

Table of Contents_____

List	of Tables	ii
1.0	Introduction	1
2.0	Scope of Work	7
3.0	Soil Boring Activities 3.1 Permitting, Health and Safety and Underground Utility Location. 3.2 Almaden Boulevard Monitoring Well Borings. 3.3 West San Fernando Street Borings. 3.4 Soil Sample Analysis and Analytical Results. 3.5 Well Installation. 3.6 Wellhead Surveying. 3.7 Well Development. 3.8 Boring Abandonment.	7 9 11 11
4.0	Groundwater Sampling Activities	12
5.0	Soil Vapor Sampling Activities	13
6.0	Waste Disposal Activities	15
7.0	Conclusions	15
8 N	Signatures	17

List of Tables_____

Table	Title
1	Soil Sample Analytical Results
2	Groundwater Sample Analytical Results
3	Soil Vapor Sample Analytical Results

List of Figures_____

Figure	Title
1	Site Vicinity Map
2	Site Plan
3	West San Fernando-Attempted Soil Borings
4	Soil Analytical Results
5	Groundwater Analytical Results
6	Soil Vapor Analytical Results

List of Appendices_____

Appendix	Title						
A	Letters from CSCDEH						
В	Permits						
C	Soil Boring Logs and Well Construction Details						
D	Photographic Log						
E	Laboratory Reports and Chain-of-Custody Documents						
F	Drum Disposal Documentation						

1.0 Introduction

Shaw Environmental, Inc., a CB&I Company (Shaw), was retained by AT&T Environment, Health & Safety to execute two work plans for further assessment at the AT&T property located at 95 South Almaden Avenue in San Jose, California (**Figure 1**). These work plans were prepared and submitted to the County of Santa Clara Department of Environmental Health (CSCDEH) in December 2012 and February 2013. The original work plan was written to address soil, groundwater, and soil vapor conditions on the main subject parcel and areas along Almaden Boulevard. On January 3, 2013, CSCDEH requested that a work plan addendum be submitted which included a scope of work to define the extent of contamination in both soil and groundwater near former borings installed to address an October 2010 diesel release near San Fernando Street and Almaden Boulevard.

Copies of the CSCDEH work plan approval letters are included in **Appendix A**.

1.1 Site Description

The AT&T property is located in downtown San Jose, Santa Clara County, California, and occupies an entire city block. The surrounding area is primarily commercial-office properties. A Greyhound Bus station is located to the east of the AT&T property, across South Almaden Avenue. Guadalupe Creek lies approximately 1,000 feet to the west and flows to the north. Current and former diesel fuel underground storage tank (UST) systems occupy the southwestern margin and western corner of the city-block.

The AT&T property contains an active switching station for telephone services to portions of the southern San Francisco Bay. The above-grade structures consist of a nine-story building which contains offices and telephone switching equipment and a one-story building for maintenance personnel. The facility's in-use UST complex consists of three diesel fuel, 20,000-gallon USTs piped into the building to support backup power generation for the site's critical communication infrastructure. Most of the subject property is paved and used for parking of AT&T-owned and private vehicles.

A nine-story secured AT&T building occupies the southern portion of the site. The building dates to approximately 1950 and has been expanded several times. AT&T expanded the facility and around 1950 purchased land from the Greyhound bus lines company. The acquired land expanded the AT&T facility northward towards Post Street and along Almaden Boulevard. At

some time in the 1970s, the City of San Jose seized a portion of the AT&T property under eminent domain and widened Almaden Boulevard further northeast. This area included portions of the AT&T facility and a portion of the former Greyhound property. In the early 1990s, AT&T discovered older diesel fuel in the vicinity of a UST complex which was being relocated. The pre-1992 and post-1992 AT&T UST complexes nearly adjoin the City of San Jose's Almaden Boulevard boundary and lie between the AT&T building and Post Street (**Figure 2**). A search of historic records in the early-to-mid 1990s indicated the former Greyhound ownership and maintenance use of the acquired property.

1.2 Site Background

Previous historical information about the investigations at the subject site was summarized in the December 2012 Work Plan for Soil-Vapor Survey and Off-Site Monitoring Well Installation, submitted under separate cover.

1992 UST Removal

In October 1992, five 10,000-gallon diesel USTs and associated piping were removed from the southwest corner of the site. Soil samples collected during the UST removals were reported to contain elevated concentrations of petroleum hydrocarbons. Three 20,000-gallon diesel USTs were subsequently installed in a new excavation about 90 feet north of the UST removal area (**Figure 2**).

A total of 22 soil borings were advanced between 1992 and 1995 to characterize the extent of petroleum hydrocarbon impact to soil and groundwater beneath the site (Versar, 1995). Analytical results of samples from soil borings located in the northwestern corner of the site indicated that petroleum hydrocarbons were present at depths less than 5 feet bsg. Soil impact in the southern and western portions of the site is reported to have occurred at depths in excess of 10 feet to 15 feet bsg.

1995 Monitoring Well Installation

In July 1995, six soil borings were advanced and converted into monitoring wells to evaluate groundwater conditions. Petroleum hydrocarbons have been detected in each of the monitoring wells. During the January 1996 monitoring event, free product was reported in monitoring well MW-1, located on the southwestern portion of the site near the existing USTs.

During the October 1996 quarterly monitoring event, free product was observed floating on top of the groundwater in monitoring wells MW-1 and MW-6 at thicknesses of 3 inches and 0.25 inches, respectively. Active and passive removal of the free product was conducted between October 1996 and December 1996 using Soak-Ease absorbent socks and weekly bailing. Passive product removal was reinitiated in April 1997, with 0.01 foot and 0.02 foot of free-phase petroleum hydrocarbons encountered in MW-1 and MW-6, respectively. Subsequent product monitoring continues to be performed on a semi-annual basis.

1997 Historical Research

During the third quarter of 1997, historical research was performed to assess the source and nature of the free product discovered at the site. A review of Sanborn Fire Insurance Maps indicated that the current AT&T property originally consisted of two separate lots that were divided by a street running parallel to San Fernando Avenue. Several businesses were located on portions of both lots that are now occupied by the AT&T facility. In the 1950s, a Greyhound Bus Line service garage was located on the southwest portion of the site, which is the approximate location of the wells that have contained free product (e.g. MW-1 and MW-6).

Prior investigations had discovered petroleum hydrocarbons in borings upgradient and cross-gradient of the former and current locations of the AT&T USTs. Fingerprint sample analysis indicated that two separate hydrocarbon plumes exist on the southern and northwestern portions of the site. Samples of free product collected from monitoring well MW-1 were collected for fingerprint analysis and age dating. The laboratory analysis reported that the product was highly weathered and likely in excess of 20 years old (IT, 1997). These data indicate that the plume located on the northwestern portion of the site predates AT&T's acquisition and use of the property. Hydrocarbon impact on the northwestern portion of the site is likely related to activities performed at the former bus maintenance garage (IT, 1997).

2001 Sensitive Receptor Survey

In February 2001, a sensitive receptor survey was conducted. The nearest water supply well was determined to be located 1,300 feet away, and used for industrial purposes. City of San Jose drinking water wells are located 1,700 feet to the west, far enough away to not likely be impacted by site hydrocarbons.

2001 Corrective Action Plan and Oxygenating Compound Injection

In April 2001, IT Corporation (IT) generated a Corrective Action Plan (CAP) for remediation of

petroleum-impacted groundwater at the site in response to a request from the Santa Clara Valley Water District (IT, 2001). The CAP was approved for implementation in May 2001. Corrective actions consisted of the advancement of soil borings to depths below the water table and backfilling with oxygen-releasing compound slurry. The oxygen-releasing compound was used to promote increased biodegradation of the remaining petroleum hydrocarbons in the site groundwater.

In July 2001, approximately 980 pounds of an oxygenating compound (ORCTM) were injected into the upper 5 feet of the shallow groundwater table through 28 direct-push soil borings located in the vicinity of the former UST systems by IT.

2002 Skimmer Installation

In 2002, Hydrologue, Inc. (HI) assumed sampling responsibilities of the on-site wells. In July 2002, HI replaced the absorbent socks in wells MW-1 and MW-6 with 0.2-gallons per hour passive skimmers. Product is removed on a quarterly basis as part of the ongoing quarterly monitoring activities.

2008 Monitoring Well Installation

In March 2008, HI installed three new groundwater monitoring wells (MW-7, MW-8, and MW-9) at the site. Monitoring well MW-7 was installed within the approximate footprint of the former Greyhound Bus station, with wells MW-8 and MW-9 installed further down gradient of the former bus stations. Intermittent occurrences of minor product or immeasurably thin iridescent petroleum sheen have been observed on the water surface within well MW-7.

2008 CAP Submittal

In a letter dated August 22, 2008, the CSCDEH requested submittal of a CAP detailing remediation of hydrocarbons at the site. AT&T subsequently requested Shaw to prepare the CAP and assume sampling responsibilities of the on-site wells. In December 2008, Shaw submitted the CAP to the CSCDEH detailing completion of a pre-design investigation and subsequent excavation of vadose zone and zone of seasonal water table fluctuation ("smear zone"). In a letter dated December 19, 2011, the CSCDEH granted approval to implement the pre-design investigation.

October 2010 Diesel Fuel Release

On October 2, 2010, AT&T was alerted that a release of diesel fuel had occurred at the 95 South Almaden Avenue facility. Approximately 1,300 gallons of fuel was pumped up to a day tank on the top floor of the building which overflowed through a vent pipe onto the roof of the facility, and then migrated down through a series of drains onto two sub-roofs, continued through the roof drain and pooled along the curb and street area along West San Fernando Street. A portion of the pooled diesel fuel also migrated into the storm drain inlet at the intersection of West San Fernando Street and Almaden Boulevard and traveled through the main storm drain approximately 1,000 feet to the Guadalupe River.

In a letter dated January 11, 2011, the CSCDEH requested submittal of a work plan detailing an investigation into whether all the diesel fuel that had entered into the storm drain system had been discharged into the Guadalupe River and whether diesel fuel that had pooled along the curb of West San Fernando Street had migrated downward through the asphalt pavement. Shaw submitted a work plan detailing the proposed investigation dated March 1, 2011, and approved by the CSCDEH in a letter dated May 16, 2011.

Shaw surveyed the storm drain as part of this investigation. Due to the steep slope of the drain line, high flow rate of water in the pipe, and good condition of the sections surveyed, Shaw determined that it was unlikely any of the diesel fuel had migrated out of the storm drain system. Shaw believed that the bulk of diesel fuel that had entered into the storm drain system was either discharged to the Guadalupe River and any residual fuel was removed during subsequent cleaning activities.

On August 16, 2011, Shaw personnel performed five soil borings, labeled SB-1 through SB-5, every 20 feet along the area of West San Fernando Street where diesel fuel had pooled. Due to the presence of electrical and telecommunication lines and CSJDPW permit requirements, the borings had to be performed 3 feet from the curb, in between the utility lines. During boring advancement, concrete slurry was encountered immediately underlying the pavement in borings SB-1 and SB-2 which precluded sample collection. Based on the proximity to neighboring utilities, Shaw believed this slurry material was part of the seal around one or both of the adjacent utility lines. Soil borings SB-3, SB-4 and SB-5 were completed to depths of 2 to 3 feet below surface grade (bsg), with underlying material consisting of a sand and gravel fill material. Refusal was encountered in each of these borings by underlying concrete slurry. During boring advancement, a diesel odor was noted in the fill material retrieved from borings SB-4 and SB-5.

Results of the sample analysis detected TPH-D in sample SB-3 at a concentration of 1.9 milligrams per kilogram (mg/kg), in sample SB-4 at a concentration of 12,000 mg/kg, and in sample SB-5 at a concentration of 650 mg/kg. Ethylbenzene was detected in sample SB-5 at a concentration of 0.096 mg/kg, and xylenes in samples SB-4 and SB-5 at concentrations of 2.1 mg/kg and 0.38 mg/kg, respectively. No other analytes were detected.

2012 Soil Boring Investigation

In June 2012, Shaw oversaw the advancement of 19 Cone Penetration Test (CPT) and UVOST® borings and two direct-push soil borings at the site and along Almaden Boulevard and Post Street. Results of the investigation found that underlying petroleum hydrocarbons were generally found at depths of 15 feet to 23 feet bsg, and extended as deep as 28 feet bsg. The hydrocarbon plume also appeared to extend off-site, to the east, underneath Almaden Boulevard. In addition, some shallow contamination was found along Almaden Boulevard in an area where diesel fuel had pooled following the December 2010 release. Based on the results, Shaw determined that excavation was no longer feasible due to depth constraints and any excavation activities would leave a significant portion of impact remaining under the active UST complex and under Almaden Boulevard.

Due to the overall low permeability of underlying soils, heavy-end nature of the residual petroleum hydrocarbons, low overall groundwater gradient, and results of over 17 years of groundwater monitoring, Shaw determined that the plume underneath the AT&T property appeared to be stable and the most feasible remedial alternative was continuance of groundwater monitoring until property usage and street configuration changed. The stability of the off-site portion of the plume had not been confirmed but as soil types were not anticipated to vary greatly in the area of the plume, if no utilities are present at depths that could intercept impacted soils or groundwater (approximately 15 feet bsg), migration of this portion of the plume was also considered unlikely.

At the request of the CSCDEH, a work plan was prepared to detail completion of a soil-vapor survey to determine if there is any risk to workers at the facility, as well as completion of an off-site soil boring investigation and installation of monitoring wells to evaluate the extent of the off-site plume and monitor plume stability. The location of this work was primarily on the south and western portions of the subject site. This work plan was submitted to CSCDEH in December 2012. On January 3, 2013, CSCDEH requested that a work plan addendum be submitted to

include a scope of work to define the extent of contamination in soil and groundwater near the former boring along West San Fernando Street.

2.0 Scope of Work

This scope of work consisted of the installation of six soil borings (SB1-SB6) along Almaden Boulevard. Four of these borings were converted into groundwater monitoring wells (MW-10 through MW-13). Following installation, the wells were developed and sampled. Four soil vapor sampling points were installed on the subject site to determine if there is any risk to workers at the facility. Finally, attempts were made to collect soil and groundwater samples from six locations along West San Fernando Street to evaluate soil and groundwater conditions in the area of the former release of petroleum hydrocarbons in 2010.

3.0 Soil Boring Activities

The methods and procedures used to complete the field activities are described in the following sections:

3.1 Permitting, Health and Safety and Underground Utility Location

Prior to initiating field activities, a permit application was submitted to the Santa Clara Valley Water District (SCVWD). In addition, road encroachment, lane closure, and parking tow-away permits were secured for the project to clear the area of obstructions and to provide safe flow-through of roadway traffic. Copies of the approved permits are included in **Appendix B**.

As part of Shaw's health and safety procedures, a site-specific health and safety plan was also developed by Shaw, and was reviewed in tailgate health and safety meetings conducted each day field work was performed. Between June 11 and 12, 2013, the proposed drilling locations were marked and Underground Service Alert (USA) was notified of the anticipated drilling locations and date of drilling. Additionally, personnel from ULS Services Corp. (ULS) of Sacramento, California assisted in locating underground utilities near the anticipated drilling locations.

It should be noted that due to the heavy amount of underground utilities in the area along West San Fernando Street, proposed boring locations had to be modified. Several major telecommunication companies operate high-volume fiber optic lines in the area. Many of the telecommunication companies mobilized to the site to assist in the marking of these lines. Several companies indicated that they were not entirely sure of the precise location of each line

and instructed Shaw to avoid certain areas. The AT&T owned facility (subject site) is a terminal point for telecommunication lines and considered a business-critical hub. As a result of these directions and the results of other utility mark-outs (inclusive of ULS), the proposed boring locations were modified but remained in the general location of the proposed boring locations. Traditional drilling techniques were not able to be utilized in accordance with standard industry protocols protective of worker health and safety.

3.2 Almaden Boulevard Monitoring Well Borings

Between June 17 and June 21, 2013, Cascade Drilling advanced six soil borings at the site (**Figure 2**).

During the drilling, soil cores were collected continuously from surface grade to the bottom of each boring, and logged using the ASTM's Visual-Manual Method of Soil Classification by a Shaw field geologist working under the supervision of a California-registered geologist. Intact soil samples were evaluated for relative hydrocarbon content using a photoionization detector (PID).

Based on field observations, samples collected for laboratory analysis were sealed with plastic caps over Teflon film, taped, labeled, placed on ice and sent to a state-certified laboratory under legal chain of custody. Two soil samples from each borehole were submitted to an ELAP-certified laboratory, Kiff Analytical LLC of Davis, California (subcontracted through Pace Analytical in Seattle, Washington) under chain-of-custody protocol. The samples exhibiting the highest PID response and a sample from the capillary fringe were analyzed for total petroleum hydrocarbons as diesel (TPH-D) under EPA method 8015 (modified), and for TPH-gasoline (TPH-G), benzene, toluene, ethylbenzene and xylenes (BTEX) constituents and the fuel oxygenates MTBE, tert-butanol (TBA), di-isopropyl ether (DIPE), tert-amyl-methyl ether (TAME), and ethyl tert-butyl ether (ETBE) under EPA method 8260B. In addition, at the request of CSCDEH, naphthalene was analyzed for future site evaluation under the Low-Threat Closure Policy (LTCP).

Cascade Drilling advanced the six borings to depths up to 28 feet bsg. Native soils encountered during boring activities consisted of loose sandy silts to approximately 17 feet bsg, followed by fine sands, silts, and clays to the maximum explored depth of 28 feet bsg. Groundwater was initially encountered in the borings ranging in depths from 16 to 16.5 feet bsg. Soil boring logs are included in **Appendix C**.

Drilling equipment was steam-cleaned between borings to avoid contaminant introduction and sample cross-contamination. The soil cuttings and decontamination water generated during boring advancement were placed in labeled 55-gallon drums pending disposal at an appropriate disposal facility.

3.3 West San Fernando Street Borings

Due to the congestion of underground utilities in the area along West San Fernando Street, proposed boring locations had to be modified. Several major telecommunication companies operate high-volume fiber optic lines in the area. Many of the telecommunication companies mobilized to the site to assist in the marking of these lines. Several companies indicated that they were not entirely sure of the precise location of each line and instructed Shaw to avoid certain areas along West San Fernando Street. The AT&T owned facility (subject site) is a terminal point for telecommunication lines and considered a business-critical hub. As a result of these directions and the results of other utility mark-outs (inclusive of ULS), the proposed boring locations were modified but remained in the general location of the proposed boring locations.

Traditional drilling techniques were not able to be utilized in accordance with standard industry protocols protective of worker health and safety. Attempts at soil and groundwater sample collection had to be completed using hand tool (i.e. augur). Shaw and Cascade Drilling attempted to collect samples at six locations along West San Fernando Street (**Figure 3**). Refusal on utility encasements and concrete were encountered at all six locations at depths ranging from 9 to 13 inches below surface grade. A photographic log of the utilities encountered during boring attempts is included in **Appendix D**.

As a result of these refusals, Shaw was unable to collect suitable soil or groundwater samples from this area of the site. Moving sampling locations farther east and/or south will require additional permit modifications and traffic control plans with the City of San Jose and was not feasible within the CSCDEH timeframe for additional assessment. Shaw and AT&T will work with CSCDEH to discuss additional options for this area of the site.

3.4 Soil Sample Analysis and Analytical Results

A total of twelve soil samples were submitted to Kiff Analytical LLC, a State of Californiacertified laboratory located of Davis, California for analysis:

Boring ID	Sample Depth Below
	Surface Grade (ft)
SB1	7
SB1	14
SB2/MW10	9
SB2/MW10	15
SB3	8
SB3	14
SB4/MW11	6
SB4/MW11	15
SB5/MW12	9
SB5/MW12	15
SB6/MW13	6
SB6/MW13	15

The samples were analyzed total petroleum hydrocarbons as diesel (TPH-D) under EPA method 8015 (modified), and for TPH-gasoline (TPH-G), benzene, toluene, ethylbenzene and xylenes (BTEX) constituents and the fuel oxygenates MTBE, tert-butanol (TBA), di-isopropyl ether (DIPE), tert-amyl-methyl ether (TAME), and ethyl tert-butyl ether (ETBE) under EPA method 8260B. Copies of the chain-of-custody documents are included in **Appendix E**.

Results of the analysis detected:

- TPH-D in samples SB1-7' (1.8 mg/kg), SB2-15' (1.8 mg/kg), SB4-6' (1.8 mg/kg), SB4-15' (2.4 mg/kg), SB5-9' (800 mg/kg), SB5-15' (1,300 mg/kg), SB6-6' (8.1 mg/kg), and SB6-15' (1.5 mg/kg).
- TPH-G in samples SB5-9' (210 mg/kg) and SB5-15' (3,400 mg/kg)
- Toluene in sample SB5-9' (0.027 mg/kg)
- Ethylbenzene in samples SB5-9' (0.084 mg/kg) and SB5-15' (6 mg/kg)
- Xylenes in samples SB5-9' (0.044 mg/kg) and SB5-15' (18 mg/kg)
- Naphthalene in samples SB5-9' (0.47 mg/kg) and SB5-15' (15 mg/kg)
- Five fuel oxygenates were not detected in any of the samples.

Soil sample analytical results are summarized in **Table 1** and depicted on **Figure 4**. Copies of the laboratory analytical reports are included in **Appendix E**.

3.5 Well Installation

Following completion of the borings, monitoring wells MW-10, MW-11, MW-12, and MW-13 were installed in the boreholes. The wells were constructed using 2-inch diameter Schedule 40 PVC well casing with flush threads (ASTM F-480) and 0.010-inch slot well screen. The well screen in all four wells was installed from 12 feet to 27 feet bsg. A filter pack of #2 sand was placed around the well screen from the bottom of each boring to at least 1 foot above the top of each well screen. A 2-foot thick seal of bentonite pellets (hydrated in place) was installed above the sand filter pack, with the remaining annular space of each well then filled with cement-bentonite grout. The wells were completed at grade with water-tight locking caps and flush-mounted, traffic-rated 8-inch diameter vaults set in concrete. Copies of the well construction logs are included in **Appendix C**.

3.6 Wellhead Surveying

The new monitoring wells are scheduled to be surveyed in August 2013. The resulting survey data will be used to incorporate the new monitoring wells into the existing site well array. Sitewide groundwater monitoring is scheduled to take place in September 2013 as part of the ongoing groundwater monitoring program. A copy of the survey data will be included in the next groundwater monitoring report.

3.7 Well Development

On June 21, 2013, groundwater monitoring wells MW-10, MW-11, MW-12 and MW-13 were developed by swabbing and bailing up to 10 static well casing volumes of water until groundwater parameters including pH, temperature, specific conductivity, and turbidity had stabilized. Well development water was stored in 55-gallon drums at the AT&T facility pending characterization and transport to a licensed disposal facility.

3.8 Boring Abandonment

After the collection of soil and groundwater samples, borings not completed as monitoring wells were backfilled with concrete grout and finished at surface grade in accordance with City of San Jose and SCVWD permit requirements.

4.0 Groundwater Sampling Activities_

4.1 Groundwater Sample Collection

On June 21, 2013, groundwater samples were collected from each well using new single-use Teflon bailers. Samples were poured directly from the bailer into laboratory-provided containers. All sample bottles were supplied and preserved by the laboratory. Care was taken to ensure that no headspace was present in the sample bottles. Following collection, the sample containers were labeled, placed in an ice-packed cooler, and transported to the laboratory under chain-of-custody protocol. A copy of the chain-of-custody document is included in **Appendix E**.

Groundwater samples were submitted to an ELAP-certified laboratory (Kiff) for analysis under chain-of-custody protocol.

4.2 Groundwater Sample Analysis and Analytical Results

A total of four groundwater samples were submitted to Kiff Analytical LLC, a State of California-certified laboratory located of Davis, California for analysis. The samples were analyzed for TPH-D under EPA method 8015 (modified), and for TPH-G, BTEX constituents, and the fuel oxygenates MTBE, TBA, DIPE, TAME, and ETBE under EPA method 8260B.

Results of the analysis detected:

- TPH-D in MW-10 (2,400 μ g/L), MW-11 (3,200 μ g/L), MW-12 (4,700 μ g/L), and MW-13 (5,300 μ g/L)
- Benzene in MW-12 at 91 μg/L
- Toluene in MW-12 at 7 μg/L
- Ethylbenzene in MW-12 at 14 μg/L
- Xylenes in MW-12 at 27 μg/L

Groundwater sample analytical results are summarized in **Table 2** and depicted on **Figure 5**. Copies of the laboratory analytical reports are included in **Appendix E**.

5.0 Soil Vapor Sampling Activities

5.1 Soil Vapor Sample Collection

On June 18 and 19, 2013, soil vapor samples were collected from four points which were advanced at the site using direct-push to 5 feet below surface grade (**Figure 2**). Before and after each use, all reusable components were properly decontaminated.

The drive rod was advanced to the selected depth and then pulled back to expose the inlets of the soil vapor probe. During installation of the probe, hydrated bentonite was used to seal around the drive rod at ground surface to prevent ambient air intrusion from occurring. The inner soil vapor pathway from probe tip to the surface was continuously sealed (e.g., a sampling tube attached to a screw adapter fitted with an O-ring and connected to the probe tip) to prevent infiltration.

Before purging and sample collection, each sample collection set up was tested for surface fitting leaks that could dilute the sample collected. Shaw utilized standard DTSC soil vapor sampling practices including the use of a sampling shroud and 70% isopropyl alcohol tracer. Just before the laboratory canister valve was opened for sample collection, a cloth was wrapped around the connections between the sampling tube leading from the well and the canister and vacuum gauge, and the isopropyl alcohol tracer was applied to the cloth. When the samples were submitted to the laboratory, analysis for isopropyl alcohol was requested.

To ensure stagnant or ambient air was removed from the sampling system and to assure samples collected were representative of subsurface conditions, the soil vapor sampling locations were purged after installation and before sampling. At minimum, the volume of air in the hole was removed during development. The appropriate number of purge volumes was evacuated at a rate of between 100 and 200 milliliters per minute (mL/min). The probes and tubing were purged by attaching clean Teflon[®]-lined tubing to the wellhead fitting, well tubing or other sample port from which the sample was drawn, and connecting to a vacuum pump. After purging was complete, the tubing was disconnected from the vacuum pump.

The vacuum in each SUMMA[™] canister was verified by attaching a vacuum gauge to the canister, prior to sample collection. The vacuum was recorded. Note: on June 18, 2013, upon attempting to collect a soil vapor sample from SV-4, Shaw recorded no measurable vacuum

pressure on the SUMMATM canister. Sampling at this location was aborted and a new canister was requested from the laboratory via overnight courier. A new, appropriately evacuated canister was received on June 19, 2013 at which time sampling at SV-4 was completed.

After the vacuum gauge has been removed, a sample tube was attached to the SUMMATM canister. The canister valve was opened to draw in soil vapor until the vacuum in the canister was reduced from approximately 30 inches to approximately 5 inches of mercury. At 150 to 200 mL/min, approximately 5 liters (L) were collected in the 6-L SUMMATM canisters. When the canister vacuum reached approximately 5 inches of mercury, the canister valves were closed and the canisters were placed inside appropriate shipping containers for delivery to the analytical laboratory.

The sampling technician recorded the final vacuum in the canister in the project logbook and on the chain-of-custody documents. The vacuum in the sample canister was checked in the laboratory and used to determine whether the canister leaked during transport. After the collection of samples from each probe, tubing in the surface sample apparatus which came in contact with the sample was replaced to eliminate the possibility of cross-contamination.

The purge volume test, leak test, and soil vapor sampling was conducted at least 48 hours after the soil vapor probe installation. Soil vapor sampling was not conducted during or immediately after a significant rain event or onsite watering. Upon completion of soil vapor sampling, each of the four borings was properly abandoned.

5.2 Soil Vapor Sample Analysis

The four soil vapor samples collected were submitted to an ELAP-certified laboratory for analysis for benzene and MTBE using EPA method TO-15. In addition, at the request of CSCDEH, naphthalene was analyzed for future site evaluation under the LTCP.

Results of the analysis indicated:

- Benzene was detected in SV-1 (6.3 μ g/m³), SV-2 (7.6 μ g/m³), SV-3 (7.6 μ g/m³), and SV-4 (20.5 μ g/m³)
- Naphthalene was detected in SV-4 at a concentration of 7.0 μg/m³
- MTBE was not detected in any of the four soil vapor samples

Soil vapor sample analytical results are summarized in **Table 3** and depicted on **Figure 6**. Copies of the laboratory analytical reports are included in **Appendix E**.

6.0 Waste Disposal Activities

Nine 55-gallon drums of soil cuttings and four 55-gallon drums of decontamination water were generated during field activities and were temporarily stored on-site in labeled, DOT-approved 55-gallon drums pending transport to an approved disposal facility.

One July 17, 2013, Environmental Logistics transported the drums to Filter Recycling Services in Rialto, California for disposal. A copy of the Non-Hazardous Waste Manifest NH32530 for the drums is included in **Appendix F**.

7.0 Conclusions

In June 2013, Shaw performed additional off-site investigation to delineate the extent of any underlying impact at the AT&T facility along Almaden Boulevard and West San Fernando Street. In addition, soil vapor samples were collected on the AT&T property.

The anticipated work plan was completed with the exception of the soil borings along West San Fernando Street. As outlined within this report, boring attempts along West San Fernando Street were unsuccessful. The guidelines of available drilling/access permits, applicable health and safety procedures associated with subsurface exploration (drilling), and the high volume and uncertainty of utility location in the area, prevented additional investigation in this area. Attempts were made at six locations with refusal at 9 to 13 inches below surface grade at each location.

Six soil borings along Almaden Boulevard were successfully completed. Laboratory analytical data were compared to the SFRWQCB's Environmental Screening Level (ESL) for shallow soils (groundwater is a potential drinking water source):

- TPH-D in SB5-9' (800 mg/kg) and SB5-15' (1,300 mg/kg) exceeded the ESL of 83 mg/kg.
- TPH-G in SB5-9' (210 mg/kg) and SB5-15' (3,400 mg/kg) exceeded the ESL of 83 mg/kg.
- Ethylbenzene in SB5-15' (6 mg/kg) exceeded the residential and commercial ESLs of 2.3 mg/kg and 3.3 mg/kg respectively.

- Xylene in SB5-15' (18 mg/kg) exceeded the ESLs of 2.3 mg/kg.
- Naphthalene in SB5-15' (15 mg/kg) exceeded the residential and commercial ESLs of 1.3 mg/kg and 2.8 mg/kg respectively.

Groundwater samples from the four new groundwater monitoring wells were collected following well development. Laboratory analytical data indicates TPH-G and TPH-D in all four wells exceeds the SFRWQCB's ESL (100 μ g/L) for groundwater (groundwater being a potential drinking water source). Benzene (91 μ g/L) and xylene (27 μ g/L) in MW-12 also exceeded the ESLs of 1 μ g/L and 20 μ g/L respectively.

Laboratory analytical reports included in Appendix E indicate some anomalies in the concentrations of TPH-D detected in some samples. The anomalies include petroleum peaks/boiling points observed in ranges outside the typical diesel fingerprint range.

Soil vapor sampling was conducted at four locations at the subject site. Benzene was detected in all four soil vapor points ranging from 6.3 (in SV-1) to 20.5 (in SV-4) $\mu g/m^3$. Naphthalene was detected in SV-4 at 7.0 $\mu g/m^3$. These values do not exceed the SFRWQCB's Shallow Soil Gas Screening Level for Evaluation of Potential Vapor Intrusion Concerns (Table E-3) for either the lowest residential (84 $\mu g/m^3$ benzene or 72 $\mu g/m^3$ naphthalene) or lowest commercial/industrial (280 $\mu g/m^3$ benzene or 240 $\mu g/m^3$ naphthalene) property uses.

Although TPH-G and TPH-D were detected in subsurface soil and groundwater along Almaden Boulevard, at this time, it does not appear that these concentrations pose a threat to worker safety at the subject site or other nearby properties. Historical groundwater data for the subject property has been consistent with a release of diesel fuel. The presence of TPH-G detected in soil and groundwater at SB5/MW-12 may be attributable to another source in the area. A registered UST is located across Almaden Boulevard to the south (55 Almaden Boulevard) however, GeoTracker does not indicate the type of fuel located at this location nor is there an open release associated with this registered UST system.

The new monitoring wells will be surveyed in August 2013 and incorporated into future groundwater contours for the subject site. The new wells will be sampled again in September 2013 during the next semi-annual groundwater monitoring event.

8.0 Signatures

The interpretations and conclusions contained in this report represent our professional opinions. These opinions are based on currently accepted engineering practices at this time and for this specific site. No additional warranty is implied or intended.

Prepared by:

Reviewed by:

Joe Pickard Project Scientist

Shaw Environmental, Inc.

A. DELNAGRO

No.7793

PHOF CALIF

Rob Delnagro, P.G.

Project Manager

Shaw Environmental, Inc.




Table 1 Soil Sample Analytical Results AT&T Facility 95 South Almaden Avenue San Jose, California

Sample I.D.	Sample	Date	Sample Depth	TPH-D	TPH-G	Benzene	Toluene	Ethyl- benzene	Xylenes	MTBE	DIPE	ETBE	TAME	TBA	Naphthalene
	Location	Collected	(in feet bsg)			(all results reported in milligrams per kilogram)									
SB1-7'	SB-1	06/17/13	7	1.8	ND_1	ND _{0.005}	ND _{0.005}	ND _{0.005}	ND _{0.005}	ND _{0.005}	ND _{0.005}	ND _{0.005}	$ND_{0.005}$	ND _{0.005}	ND _{0.005}
SB1-14'	SB-1	06/17/13	14	ND ₁	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}
SB2-9'	SB-2/MW-10	06/17/13	9	ND_1	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}
SB2-15'	SB-2/MW-10	06/17/13	15	1.8	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$
SB3-8'	SB-3	06/17/13	8	ND_1	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$
SB3-14'	SB-3	06/17/13	14	ND_1	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$
SB4-6'	SB-4/MW-11	06/18/13	6	1.8	ND_1	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$
SB4-15'	SB-4/MW-11	06/18/13	15	2.4	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}
SB5-9'	SB-5/MW-12	06/19/13	9	800	210	$ND_{0.025}$	0.027	0.084	0.044	$ND_{0.025}$	$ND_{0.025}$	$ND_{0.025}$	$ND_{0.025}$	$ND_{0.15}$	0.47
SB5-15'	SB-5/MW-12	06/19/13	15	1300	3400	$ND_{0.25}$	$ND_{0.25}$	6	18	$ND_{0.25}$	$ND_{0.25}$	$ND_{0.25}$	$ND_{0.25}$	$ND_{1.5}$	15
SB6-6'	SB-6/MW-13	06/19/13	6	8.1	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$
SB6-15'	SB-6/MW-13	06/19/13	15	1.5	ND_1	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}	ND _{0.005}	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	$ND_{0.005}$	ND _{0.005}
San Francisco RWQCBs Environmental Screening Levels for Residential/Commercial Properties (May 2008; shallow soils, ≤ 3 meters, groundwater is a potential drinking water source)			83	83	0.044	2.9	2.3 - res 3.3 · com	2.3	0.023	N/A	N/A	N/A	0.075	1.3 - res 2.8 - com	

Notes:

bsg - below surface grade

TPH-D - total petroleum hydrocarbons as diesel TPH-G - total petroleum hydrocarbons as gasoline

MTBE - methyl-t-butyl-ether DIPE - diisopropyl ether ETBE - ethyl-t-butyl ether

TAME - tert-amyl methyl ether

TBA - tert-butanol

N/A - Not Applicable

 $\ensuremath{\text{ND}_{x}}\xspace$ - not detected above "x" laboratory detection limits

Table 2 Groundwater Sample Analytical Results AT&T Facility 95 South Almaden Avenue San Jose, California

Sample I.D.	Sample Location	Date Collected	TPH-D	TPH-G	Benzene	Toluene	Ethyl Benzene	Xylenes	MTBE	DIPE	ЕТВЕ	TAME	TBA
		Conecteu	(all results reported in micrograms per liter)										
MW-10	Monitoring Well MW-10	06/21/13	2400	760	ND _{0.5}	ND _{0.5}	$ND_{0.5}$	$ND_{0.5}$	$ND_{0.5}$	ND _{0.5}	$ND_{0.5}$	$ND_{0.5}$	ND_5
MW-11	Monitoring Well MW-11	06/21/13	3200	550	ND _{0.5}	$ND_{0.5}$	ND _{0.5}	ND_5					
MW-12	Monitoring Well MW-12	06/21/13	4700	2400	91	7	14	27	ND _{0.5}	ND _{0.5}	$ND_{0.5}$	ND _{0.5}	ND_5
MW-13	Monitoring Well MW-13	06/21/13	5300	290	ND _{0.5}	ND _{0.5}	$ND_{0.5}$	ND _{0.5}	ND _{0.5}	ND _{0.5}	$ND_{0.5}$	ND _{0.5}	ND_5
San Francisco RWQCBs Environmental Screening Levels (May 2008, groundwater is a potential drinking water source)		100	100	1	40	30	20	5	N/A	N/A	N/A	12	

Notes:

TPH-D - total petroleum hydrocarbons as diesel TPH-G - total petroleum hydrocarbons as gasoline

MTBE - methyl-t-butyl-ether DIPE - diisopropyl ether ETBE - ethyl-t-butyl ether

TAME - tert-amyl methyl ether

TBA - tert-butanol N/A - Not Applicable

ND_x - not detected above "x" laboratory detection limits


Table 3 Soil Vapor Sample Analytical Results AT&T Facility 95 South Almaden Avenue San Jose, California


Sample I.D.	Sample Location	Date Collected	Benzene	MTBE	Naphthalene		
		Conected	micrograms/cubic meter				
SV-1	Soil Vapor Point 1	06/18/13	6.3	ND_7	ND _{5.1}		
SV-2	Soil Vapor Point 2	06/18/13	7.6	ND _{6.7}	ND _{4.9}		
SV-3	Soil Vapor Point 3	06/18/13	7.6	ND_7	ND _{5.1}		
SV-4	Soil Vapor Point 4	06/19/13	20.5	ND _{5.1}	7.0		
San Francisco RWQCBs Shallow Soil Gas Screening Le Instrusion Concerns - Table E-2 (May 2008; lowerst Resi	84 - res 280 - com	9,400 - res 31,000 - com	72 - res 240 - com				


Notes:


MTBE - methyl-t-butyl ether


ND_x - not detected above "x" laboratory detection limits

















APPENDIX A LETTERS FROM THE CSCDEH

County of Santa Clara

Department of Environmental Health

1555 Berger Drive, Suite 300 San Jose, California 95112-2716 (408) 918-3400 www.EHinfo.org



January 3, 2013

Mr. Mark Smith AT&T Services, Inc. 308 South Akard Street, Room 1700 Dallas, Texas 75202-5399

Subject: Fuel Leak Investigation, Pacific Bell, 95 South Almaden Avenue, San Jose, CA;

Case No. 14-281, SCVWDID No. 07S1E08N03f

Dear Mr. Smith:

The Department of Environmental Health (DEH) has reviewed the *Work Plan for Soil-Vapor Survey and Off-Site Monitoring Well Installation* submitted by Shaw Environmental Inc. (Shaw) and dated December 19, 2012.

As mentioned in the DEH's October 18 and December 12, 2012 letters, you are required to perform additional investigation to fully delineate the nature and extent of contamination associated with the October 2010 diesel spill near San Fernando Street and Almaden Boulevard. Elevated soil contamination was previously reported in this area as well as shallow subsurface utilities. In order to be protective of utility workers and determine if these utilities have created a lateral conduit for migration, you are required to define contamination in this area. No scope of work was included in this work plan to address this requirement. Please submit an addendum to this work plan which includes a scope of work to define the extent of contamination in both soil and groundwater near borings SB-1 through SB-5.

TECHNICAL REPORT REQUEST

Please submit the following document to the DEH (Attention: Mr. Aaron Costa), according to the following schedule:

Work Plan Addendum for Additional Site Assessment February 15, 2013

This technical report is requested pursuant to our authority under Sections 25289 and 25296.10 of the California Health and Safety Code. Each report, including Quarterly Groundwater Monitoring Reports, shall include conclusions and recommendations for the next phases of work required to protect water resources, human health and safety, and the environment at the site. We request that all required work be performed in a prompt and timely manner. Revisions to the

Mr. Smith January 3, 2013 Page 2 of 2

proposed schedule shall be requested at least two weeks prior to the due date in writing with appropriate justification for the anticipated delays.

The California Business and Professions Code (Sections 6735, 7835, and 7835.1) require that work plans and technical or implementation reports containing geologic or engineering evaluations and/or judgments must be performed under the direction of an appropriately registered or certified professional.

PERJURY STATEMENT

All proposals and reports submitted to this office must be accompanied by a cover letter from the responsible party which states, at a minimum, the following:

"I declare, under penalty of perjury, that the information and/or recommendations contained in the attached proposal or report is true and correct to the best of my knowledge."

This letter must be signed by an officer or legally authorized representative of your company. Future submittals made without the perjury statement may be returned as insufficient, which could affect your eligibility for reimbursement from the State Cleanup Fund. Please note that further delays in investigation, late reports, or enforcement actions may also result in your becoming ineligible to receive grant money from the California State Cleanup Fund (SB2004) to reimburse you for the cost of the cleanup.

If you have any questions, please feel free to contact me at (408) 918-1954 or via email.

Sincerely,

Aaron Costa

Hazardous Materials Specialist II

Local Oversight Program

aaron.costa@deh.sccgov.org

cc: Rob Delnagro, Project Manager, Shaw Environmental, Inc. (Rob.Delnagro@shawgrp.com) File



County of Santa Clara

Department of Environmental Health

1555 Berger Drive, Suite 300 San Jose, California 95112-2716 (408) 918-3400 www.EHinfo.org



March 11, 2013

Mr. Mark Smith AT&T Services, Inc. 308 South Akard Street, Room 1700 Dallas, Texas 75202-5399

Subject: Fuel Leak Investigation, Pacific Bell, 95 South Almaden Avenue, San Jose, CA;

Case No. 14-281, SCVWDID No. 07S1E08N03f

Dear Mr. Smith:

The Department of Environmental Health (DEH) has reviewed the *Work Plan for Soil-Vapor Survey and Off-Site Monitoring Well Installation* and the *Work Plan Addendum for Additional Site Assessment* submitted by Shaw Environmental Inc. (Shaw) and dated December 19, 2012 and February 15, 2013 respectively.

The work plan proposes to drill six borings along Almaden Boulevard, four of which will be converted into groundwater monitoring wells, install four soil vapor probes, and collect soil gas samples at each location. Additionally, in order to evaluate soil and groundwater conditions near the eastern portion of the property, the work plan proposes to drill four soil borings along San Fernando Street and collect soil and groundwater samples at each location. The DEH reminds you that in order to fulfill all of the criteria listed in the State Water Resources Control Board's Low Threat Underground Storage Tank Case Closure Policy (LTCP); naphthalene must be analyzed in both soil and soil gas samples. The DEH concurs with the proposed scope of work and asks that you proceed with implementation.

TECHNICAL REPORT REQUEST

Please submit the following document to the DEH (Attention: Mr. Aaron Costa), according to the following schedule:

Site Assessment Report

July 19, 2013

This technical report is requested pursuant to our authority under Sections 25289 and 25296.10 of the California Health and Safety Code. Each report, including Quarterly Groundwater Monitoring Reports, shall include conclusions and recommendations for the next phases of work required to protect water resources, human health and safety, and the environment at the site. We request that all required work be performed in a prompt and timely manner. Revisions to the

Mr. Smith March 11, 2013 Page 2 of 2

proposed schedule shall be requested at least two weeks prior to the due date in writing with appropriate justification for the anticipated delays.

The California Business and Professions Code (Sections 6735, 7835, and 7835.1) require that work plans and technical or implementation reports containing geologic or engineering evaluations and/or judgments must be performed under the direction of an appropriately registered or certified professional.

PERJURY STATEMENT

All proposals and reports submitted to this office must be accompanied by a cover letter from the responsible party which states, at a minimum, the following:

"I declare, under penalty of perjury, that the information and/or recommendations contained in the attached proposal or report is true and correct to the best of my knowledge."

This letter must be signed by an officer or legally authorized representative of your company. Future submittals made without the perjury statement may be returned as insufficient, which could affect your eligibility for reimbursement from the State Cleanup Fund. Please note that further delays in investigation, late reports, or enforcement actions may also result in your becoming ineligible to receive grant money from the California State Cleanup Fund (SB2004) to reimburse you for the cost of the cleanup.

If you have any questions, please feel free to contact me at (408) 918-1954 or via email.

Sincerely,

Aaron Costa

Hazardous Materials Specialist II Local Oversight Program

aaron.costa@deh.sccgov.org

cc: Rob Delnagro, Project Manager, Shaw Environmental, Inc. (Rob.Delnagro@shawgrp.com) File



APPENDIX B PERMITS

Santa Clara Valley Water District

5750 Almaden Expressway San Jose, CA 95118-3686 (408) 265-2600

WELL CONSTRUCTION APPLICATION

FC 158 (03-28-13) Page 1 of 2

_				TO BE CO	MPLETED I	BY DISTRICT				
Dis	trict Permit No.:	13w00	267	Date Is	ssued:	6-14-13	Well Registr	and the second second second	100	
Ge	ologic Setting:	01		Expirati	tion Date:	12.14-1	3 Driller's Log	No.: e0	1779	167
			TO BE	COMPLE	TED BY OW	NER AND DRILL	ER			
	II Owner: &T Services Inc.		Property City of S	y Owner San Jose		Name of Business at Well Site: City of San Jose- Public road				
308	Il Owner's Mailing S. Akard St., Room J. State, Zip		Property City, Sta		Mailing Add	ress:	Address of Well Site: Almaden Boulevard City, State, Zip			
7.30	las, TX 75202						San Jose, CA			
	ephone No. & Co -567-1578/Mark Si		Telepho	one No. &	Contact Nan	ne:	Telephone N	Vo. ;		
Ow	ner's/Consultant's	s Well No.: MW-10)	Assess	sor's Parcel N	lo. of Well Site:	Book 259	Page 3	2 Parce	500
Consultant (Company): Shaw Environmental Inc.			10.00	ling Company: cade Drilling LP				(034)		
Address: 4005 Port Chicago HWY					Ad	dress: 120 South				
-	City, State, Zip Concord, CA 94520						chmond, Ca 94804	I m am.		
Telephone No.: 925-288-2366				510	ephone No.: -478-0858		C-57 Licens 938110	se No.:		
		or phone number h				No. of Contract of	or phone number t	has changed		
			FOR ALL MONITOR	NG WELL		The state of the s				
-			aden /07S1E08N03f	Obstance of		seworker Name; /		1051		
OV	ersight Agency;	County of Santa Cia	ara-Department of Envir	ronmental i	Hearth Ca		ne No.: 408-918-			W. W. T. S.
	Signature of Res	sponsible Professio	nal		Date	F THIS INGI	ne	Pier	signature accepted	will be
-	Signature of Res Civil Engineer R timated Depth of the list to be construed.	egistration No. Completed Well:	☑ Less than 50 fo	OR -	Geologist Re	6/30 gistration No. feet □ Over	r 300 feet	Other:_		r/easement
We	Civil Engineer R	egistration No. Completed Well:	☑ Less than 50 f	eet [public ros	Geologist Re	gistration No. feet Over	r 300 feet	Other:_ orty On Di *See Ge	istrict property	//easement
-	Civil Engineer R timated Depth of the construction of the construc	egistration No. Completed Well; cted:	☑ Less than 50 folic sidewalk ☑ In a 50 feet of the top of a	OR I public ros creek ban	Geologist Re 50 to 300 ad On p nk or District f	gistration No. feet	r 300 feet On private prope	Other:_ rty On Di *See Ge	istrict property	//easement on F, page :
WELL TYPE/USE	Civil Engineer R timated Depth of the construction WATER PRODUCTION Agricultural Domestic Industrial	egistration No. Completed Well; cted:	Less than 50 for the top of a Communication of the top o	OR I public ros creek ban	Geologist Re 50 to 300 ad On p nk or District 1 DEWATERIN Permane Tempora	gistration No. feet	r 300 feet On private prope INJECT Groundwate Reinjection Stormwater Water Supp	Other:_ rty On Di *See Ge	istrict property	r/easement on F, page
as and on the state of the stat	Civil Engineer R timated Depth of fall is to be construed WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on moderstand and agricultural agricultural construction of the moderstand and agricultural	egistration No. Completed Well; cted:	Less than 50 for the top of a Communication of the top o	eet [public ros creek ban public ros creek	Geologist Re 50 to 300 ad On p nk or District 1 DEWATERIN Tempora Signatur Uired to be do not permit (see electronic, or	gistration No. feet	Groundwate Reinjection Stormwater Water Supp Other Abandoned with Santa Clara that the information uthorized and valide the purpose of this	Other:crty	District (District permit is comed with the interpretation)	ct) Well ect to the ent to be se differ,
Signature of Melt Typeruse	Civil Engineer R timated Depth of call is to be constructed WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on onderstand and agricultural stof my knowledge forceable. I also so understand the plication.	egistration No. Completed Well: cted:	□ Less than 50 for the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet	eet [public ros creek ban public ros creek ban public ros creek ban public ros creek ban public ros of this roriginal, ct agreement, to notify Date:	Geologist Re 50 to 300 ad On p nk or District 1 DEWATERIN Permane Tempora Signature Uired to be do s permit (see electronic, or	gistration No. feet	Groundwate Reinjection Stormwater Water Supp Other Abandoned with Santa Clara that the information uthorized and valident the well owner at the purpose of this ROBE IZT	Other:	District (District permit is commer, if parties hich, is indication)	ct) Well ect to the ent to be sed on this
Si S	Civil Engineer R timated Depth of or all is to be construe WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on Inderstand and agricultural agricultural and agricultural	egistration No. Completed Well: cted:	□ Less than 50 for the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet	eet [] public ros creek ban public ros creek ban public ros creek ban public ros creek ban public ros of this roriginal, ct agreeme r, to notify Date:	Geologist Re 50 to 300 ad On p ok or District 1 DEWATERIN Tempora Signatur Uired to be di permit (see electronic, or ont has been the District of	gistration No. feet	Groundwate Reinjection Stormwater Water Supp Other Abandoned with Santa Clara that the information ulthorized and valident the well owner at the purpose of this triangle.	Other: Inty On Di See Ge ION Pr Cleanup Oly Recharge Valley Water In given in this Id, and is affixed In given in this Id, and is af	District (District permit is comed with the intowner, if partie hich, is indicated)	ct) Well ect to the ent to be sed on this
S NETT TYPE/USE	Civil Engineer R timated Depth of call is to be constructed WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on onderstand and agricultural stof my knowledge forceable. I also so understand the plication.	egistration No. Completed Well: cted:	□ Less than 50 for the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet of the top of a less than 50 feet	eet [public roaccreek ban cement n yes, statu mit is requons of this r or original, c t agreeme r, to notify Date:	Geologist Re 50 to 300 ad On p ok or District 1 DEWATERIN Tempora SiGNATUF uired to be do signatuf uired to be do signatuf uired to be do signatuf the District of	gistration No. feet	Groundwate Reinjection Stormwater Water Supp Other Abandoned with Santa Clara that the information uthorized and valident the well owner at the purpose of this ROBE IZT	Other: Inty On Di See Ge ION Pr Cleanup By Recharge Valley Water In given in this Id, and is affixed In given in this Id, and is aff	District (District permit is comed with the intowner, if partie hich, is indicated)	ct) Well ect to the ent to be sed on this

5750 Almaden Expressway San Jose, CA 95118-3686 (408) 265-2600

WELL CONSTRUCTION APPLICATION

FC 158 (03-28-13) Page 2 of 2

DISTRICT WELL PERMIT NO .:

13400267

Based on information on this application and attachment(s) hereto (if any) and subject to approval noted below, permission is hereby granted to construct (drill) the described well. Permission to start work may be withheld until a field check verifies all statements made on application by permittee and is also subject to the "General" and "Special" Conditions stated below.

	SANTA CLARA COUNTY DEPARTMENT OF ENVIRONMENTAL HEALTH APPRO	OVAL (Water Supply Well Only)
NO	TE: Department of Environmental Health approval must be granted before this application will be acc	cepted by Santa Clara Valley Water District.
App	proved by: , R.E.H.S	☐ Approved as submitted ☐ Approved as corrected Date:
SIT	'E PLAN	24(4)
-	1/2" x 11" paper site plan must be attached to this application, including:	
1.	Location of site features, including major buildings, landscaped areas, tank fields, existing wells, etc. North arrow and scale	i.
3.	Location of proposed well with dimensions in feet from well to nearest cross streets.	
GE	NERAL CONDITIONS	
A.	District (telephone 408-265-2607, ext. 2660) must be notified a minimum of one working day be authorized District representative must be on site to witness the construction of the annular seal. To District representative. If the District waives the inspection requirement, the District may request the perjury, that the well was constructed in accordance with the District Well Standards and with the pergustion.	his requirement may be waived by an authorized e permittee(s) to furnish certification, under penalty of
B.	Permittee agrees to construct, operate, and maintain the well according to provisions of the latest D of District Well Standards to the end that this well will not cause pollution or contamination of ground welfare of the people of the District.	histrict Ordinance and the latest published revisions dwater or otherwise jeopardize the health, safety, or
C,	This permit is valid only for the purpose specified herein. Well construction methods authorized und approval of an authorized District representative, and only if the District believes that such a change District and State Well Standards (e.g., if the District representative finds that site conditions warrant	will result in equal or superior compliance with the
D.	This permit is only valid for the Assessor's Parcel No. indicated on it.	
E.	This permit may be voided if it contains incorrect information. If the permit is voided after work has this permit must be destroyed in accordance with District and State Well Standards.	begun, the well or boring that was constructed under
F.	If any work associated with this permit will take place on District property/easement, an encroachment District's Community Projects Review Unit (telephone 408-265-2607, ext. 2589).	
G.	Before the well constructed under this permit can be used as a drinking water source, its use must over such use (typically the Santa Clara County Department of Environmental Health or the State of completed Well Inventory Form must also be approved.	be approved by the regulatory agency with authority f California Department of Public Health). A
H.	If the well constructed under this permit cannot be or is not being used for its intended purpose, per according to the District Well Standards and under permit from the District. Any test holes drilled ur completion of testing activities. Destruction activities must be completed according to District stand 24 hours prior to destruction.	nder this permit must be destroyed within 24 hours of
ķ	Within 30 days of the completion of the well construction activities, the driller or consultant identified DWR Form 188 and mail the original to the District's Wells and Water Production Unit.	on this permit shall fully complete State of California
J.	The permittee(s) shall assume entire responsibility for all activities and uses under this permit and sofficers, agents, and employees, free and harmless from any and all expense, cost, and liability in exercise of this permit including, but not limited to, property damage, personal injury, and wrongful of	connection with or resulting from the granting or
K.	Permittees are required to be in full compliance with Cal/OSHA California Labor Code Section 6300).
L.	A current C-57 Water Well Drilling Contractor's License is required for the construction of all wells.	
M.	Permittee, permittee's contractors, consultants, or agents shall be responsible to assure that all ma construction, well development, pump testing, or other activities associated with this permit will be according to all applicable federal, state, and local statutes regulating such. In no case shall these potentially enter, on- or off-site storm sewers, dry wells, or waterways. Such materials/waters must work is being completed.	safely handled, properly managed, and disposed of materials and/or waters be allowed to enter, or
N.	The driller and consultants (if applicable) shall have an active copy of their Worker's Compensation	
0.	This permit shall expire if not exercised within 180 calendar days of its approval, unless an extension authorized District representative.	on of the permit expiration date is granted by an
P.	This permit must be kept on site during all activities associated with it and shall immediately be pre- request.	sented to an authorized District representative upon
SP	PECIAL CONDITIONS	
Co	ommunity Projects Review Unit Approval (if needed):	CPRU Permit No.:
	proved by:	Date:
4 16	15 Cra	6-14-12

Please allow 10 working days to process this application.

Santo Claro Valley Water District 5750 Almaden Expressway San Jose, CA 95118-3686 (408) 265-2600

WELL CONSTRUCTION APPLICATION

FC 158 (03-25-13)

	TO BE COMPLETED BY DISTRICT											
Dis	strict Permit No.:	13400	2248		s issued:		14-1	*************	Well Registration No.:			
Ge	ologic Setting:	()			iration Dat	400 PC for some serious	was commenced to the second street of the second				- <u> </u>	4,9
				TO BE COMP	LETED BY	Y OWNE	R AND D	/ - <u>/</u> 	E Dimare coë	A Maria Commission		1-2, V
We	ell Owner:		TO COMME		Property Owner:			Name of Business at Well Site:				
AT	&T Services Inc.			City of Sun Jose	3			٠.		City of San Jose- Public road		
We	ell Owner's Mailing	g Address:		Property Own	er's Mailind	Addres	S:		Address of			
308	3 S. Akard St., Rooi	m 1700				, , , , , , , , , ,	-		Almaden Bou			
Cit	y, State, Zip			City, State, Zip)				City, State, 2	7ip		
Dallas, TX 75202								San Jose, CA				
Telephone No. & Contact Name: Telepho 214-567-1578/Mark Smith			Telephone No	& Contac	t Name:		er en	Telephone N	ło.:	**************************************	***************************************	
Ow	ner's/Consultant'	s Well No.: MW-11		Ass	essor's Pa	rcel No.	of Well S	ře'	Book 259	رگ Page		el <i>500</i>
Co	nsultant (Compan	iy):					Compan		2001	1 494	1010	7500
Shr	w Environmental I	ne.				_	e Drilling	•				(52)
Ad	dress: 4005 Port	Chicago HWY	(~~~		ss: 120 S		ard Street		Market of the Control	
	A	oncord, CA 94520				City, S	itate, Zip	Rici	mond, Cr 94804			
	lephone No.:					Teleph	rone No.:			C-57 Licen	se No.:	erammentarion (1.000) (1666) agrificio quandidade
	5-288-2566		and the second s		WW feet conductions	510-47		**************************************		938110		
		or phone number							r phone number h	ias changed		
		BE COMPLETED			LLS OR E	1						
		icific Bell- 95 S Alm	A	- 12 #55 # common to 1		Casew	orker Na	me: A	iron Costa	A CALLY O	· ·	
Ov	ersight Agency:	County of Santa Cla	ua-Departmen	t of Environment	al Health	Casew	orker Tel	ephon	e No.: 408-918-1	954		e accuration
	1	or for			~ /m/	110		. أو من		0.	. (No subs	ritution of
, -			eresi		3/2"	٠/ ، ۵		> <u> </u>	ar con mo.	11854	C signature	will be
Signature of Responsible Professional Date Print Name (No substitution of signature will be accepted)												
	Signature or Res	ponsible i roressio	i icii		Date				3		accepted	
	neen jardistiin makka sa na	rice come a constant and a consistence of the constant and a	nesionalmonth and a second	OR OR	-	6	130	>			accepted	()
	Civil Engineer R	egistration No.			Geologia	ි st Regist	ノ <i>3C</i> tration No	2			- eccepted)
********	Civil Engineer Retimated Depth of (egistration No. Completed Well:	⊠ Less t	han 50 feet	Geologia	st Regist 300 feet	/ 3 C tration No	Over :	300 feet	☐ Other:_		3.000
********	Civil Engineer R	egistration No. Completed Well: cted:	⊠ Less t	han 50 feet	Geologia 50 to	st Regist 300 feet On publi	/ 3 C tration No U D	Over :		Other:_ty On D		//easement*
We	Civil Engineer Ritimated Depth of (all is to be constru	egistration No. Completed Well: cted: In a put Within 5	⊠ Less t	han 50 feet ⊠ In a public	Geologia 50 to	st Regist 300 feet On publitrict tacili	/ 3 C tration No U D	Over :	300 feet	Other:_ty On D	 istrict property	//easement*
We	Civil Engineer Retimated Depth of (all is to be constructed) Water	egistration No. Completed Well: cted:	Less to lic sidewalk to feet of the	han 50 feet In a public top of a creek b	Geologia 50 to road 1 ank or Dist	st Regist 300 feet On publitrict tacill	/ 3 C tration No c property ty	Over:	300 feet On private proper	Other:_ ty On D *See Ge	istrict property neral Condition	//easement* on F, page 2.
We	Civil Engineer Ritimated Depth of (bill is to be construing) WATER PRODUCTION	egistration No. Completed Well: cted;	☑ Less to Les	han 50 feet In a public top of a creek b CHATION	Geologia 50 to road [] ank or Dist Dewart	st Regist 300 feet On publit trict tacili] ERING	ration No property ty HEAT EXCHAIN	Over:	SOO feet On private proper	☐ Other: _ ty ☐ On D *See Ge	istrict property	//easement* on F. page 2.
We	Civil Engineer Ritimated Depth of Call is to be constru WATER PRODUCTION Agricultural	egistration No. Completed Well: cted;	⊠ Less to Les	han 50 feet In a public top of a creek b EDIATION ge	Geologis 50 to road ank or Dist DEWATI	st Regist 300 feet On public trict tacill ERING	ration No c property ity HEA* EXCHAP	Over:	300 feet On private proper	☐ Other: _ ty ☐ On D *See Ge	istrict property neral Condition	//easement* on F. page 2.
TYPE/USE §	Civil Engineer Ritimated Depth of (bill is to be construing) WATER PRODUCTION	egistration No. Completed Well: cted:	⊠ Less to Les	han 50 feet In a public top of a creek b EDIATION ge raction	Geologia 50 to road [] ank or Dist Dewart	st Regist 300 feet On public trict tacill ERING	ration No property ty HEAT EXCHAIN	Over:	GOO feet On private proper INJECTIO Groundwater Reinjection	☐ Other: _ ty ☐ On D *See Ge	istrict property neral Condition	//easement* on F. page 2.
We	Civil Engineer Ritimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic	egistration No. Completed Well: cted;	☑ Less to Les	han 50 feet In a public top of a creek b Charlon ge raction Emplacement	Geologis 50 to road ank or Dist DEWATI	st Regist 300 feet On public trict tacill ERING	rration No c property tity HEA- EXCHAP	Over:	Groundwater Groundwater Reinjection Stormwater	☐ Other:_ ty ☐ On D *See Ge	istrict property neral Condition	//easement* on F. page 2.
TYPE/USE §	Civil Engineer Retimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial	egistration No. Completed Well: cted:	⊠ Less to Les	han 50 feet In a public top of a creek b Charlon ge raction Emplacement	Geologis 50 to road ank or Dist DEWATI	st Regist 300 feet On public trict tacill ERING	rration No c property ty HEAT EXCHAP Closs Loop Ope	Over:	GOO feet On private proper INJECTIO Groundwater Reinjection	☐ Other:_ ty ☐ On D *See Ge	istrict property neral Condition	//easement* on F. page 2.
S JENNET LYPE/USE	Civil Engineer Retimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial	egistration No. Completed Well: cted:	☑ Less to Les	hen 50 feet In a public top of a creek b Charlion ge raction Emplacement extraction	Geologia 50 to road ank or Dist DEWATI	st Regist 300 feet On public trict tacill] ERING nanent	rration No c property ty HEAT EXCHAP Closs Loop Ope	Over:	Groundwater Reinjection Stormwater Water Suppl	☐ Other:_ ty ☐ On D *See Ge	istrict property neral Condition	//easement* on F. page 2.
S WELL TYPE/USE S	Civil Engineer Retimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on	egistration No. Completed Well: cted:	□ Less to the state of the Remi □ Air Spat □ GW Ext □ Materia □ Vapor E □ Other ▼Yes □ No	han 50 feet In a public top of a creek b Charlon ge rection Emplacement extraction If yes, sta	Geologic 50 to road ank or Dist DEWATT Perm Tem	st Regist 300 feet On public trict tacill J ERING nanent porary Active	ration No ration No ration No represents represents HEAT EXCHAN Loop Loop Loop Inactive	Over:	Groundwater Reinjection Stormwater Water Suppl Other Abandoned	Other:_ ty On D *See Ge on Cleanup y Recharge	Istrict property neral Condition CATHODIC PROTECTION	v/easement* on F. page 2. GTHER
S S MELL TYPE/USE	Civil Engineer Retimated Depth of Call is to be constructed by MATER PRODUCTION Agricultural Domestic Industrial Municipal ther wells exist on inderstand and agricultural and agricultural material material material material material and agricultural material material material material and agricultural material material material and agricultural material materi	egistration No. Completed Well: cted:		han 50 feet In a public top of a creek b CHATION ge raction Emplacement extraction If yes, state this permit is re	Geologis 50 to road ank or Dist Dewart Tem Tem	St Regist 300 feet On publishing tracities I ERING nament porary Active	ration No ration No ration No ration No ration No ration Rear Exchar Loop Loop Loop Inactiv in according	Over:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned	Other:_ ty	istrict property neral Condition CATHODIC PROTECTION	//easement* on F. page 2. OTHER
Ø = Ø MELL TYPE/USE	Civil Engineer Retimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on	egistration No. Completed Well: cted:	Less to lic sidewalk to feet of the Remi Air Spa GW Ext Materia Vapor E Other Yes Notation Nota	han 50 feet In a public top of a creek b CHATION ge rection Emplacement extraction If yes, states conditions of the	Geologis 50 to road ank or Dist Dewatt Tem stus: Signa	st Regist 300 feet On public trict racill ERING nament porary Active	#EACHAR Closs Loop Chock Closs Loop Cope Loop Inactiv	Over:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned	Other:_ Ty	istrict property neral Condition CATHODIC PROTECTION District (District	//easement* on F. page 2. CTHER.
MELL TYPE/USE	Civil Engineer Ritimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on nderstand and agricultural agr	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	hen 50 feet In a public top of a creek b CONTROL TON THE TON THE TON THE TON If yes, standard this permit is reconditions of the conditions of the acceptance of the conditions are the conditions of the co	Geologic Geolog	st Regist 300 feet On public trict tacill ERING nament porary. Active TURES be done see pagr c, or pho	ration No ration No ration No representation repres	Cover:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned with Santa Clara Ver the information	Other: ty	District (District permit is correct with the parties)	Ct) Well ed to the ent of the ent
MELL TYPE/USE	Civil Engineer Ritimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on nderstand and agricultural agr	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	hen 50 feet In a public top of a creek b CONTROL TON THE TON THE TON THE TON If yes, standard this permit is reconditions of the conditions of the acceptance of the conditions are the conditions of the co	Geologic Geolog	st Regist 300 feet On public trict tacill ERING nament porary. Active TURES be done see pagr c, or pho	ration No ration No ration No representation repres	Cover:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned with Santa Clara Ver the information	Other: ty	District (District permit is correct with the parties)	Ct) Well ed to the ent of the ent
WELL TYPE/USE	Civil Engineer Ritimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on nderstand and agricultural agr	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	han 50 feet In a public top of a creek b CHATION THE PROPOSE TO	Geologis 50 to road ank or Dist DEWATI Tem atus: SIGNA equired to take permit (I, electroniment has being the Dist	st Regist 300 feet On publishing tracities I BERING nament porary Active TURES be done see pagic, or pho	ration No ration	Cover:	Groundwater Reinjection Stormwater Water Suppli Other Abandoned with Santa Clara Versit the information horized and valid, the well owner are purpose of this	Other: ty	District (District permit is correctly when the intervence of the control of the correctly	Ct) Well ed to the ent of the ent
WELL TYPE/USE	Civil Engineer Retimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on nderstand and agridinance 90-1, the st of my knowledge forceable. I also to understand that	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	hen 50 feet In a public top of a creek b CONTROL TON THE TON THE TON THE TON If yes, standard this permit is reconditions of the conditions of the acceptance of the conditions are the conditions of the co	Geologis 50 to road ank or Dist DEWATI Tem atus: SIGNA equired to take permit (I, electroniment has being the Dist	st Regist 300 feet On publishing tracities I BERING nament porary Active TURES be done see pagic, or pho	ration No ration	Cover:	Groundwater Reinjection Stormwater Water Suppl Other Abandoned with Santa Clara Vet the information horized and valid, the well owner are purpose of this	Other: ty On D *See Ge on Cleanup y Recharge /alley Water given in this and is affixed ind property of wwell, from which Owner/Ageel	District (District (Distri	Ct) Well ed to the ent of the ent
Ott Constant	Civil Engineer Retimated Depth of Cell is to be constructed by WATER PRODUCTION Agricultural Domestic Industrial Municipal Municipal her wells exist on Inderstand and agricultural and agricultural Industrial	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	han 50 feet In a public top of a creek become a cr	Geologis 50 to road ank or Dist DEWATI Tem atus: SIGNA equired to take permit (I, electroniment has being the Dist	st Regist 300 feet On publishing tracities I BERING nament porary Active TURES be done see pagic, or pho	ration No ration	Over:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned with Santa Clara Ver the information horized and valid the well owner are purpose of this storm of Property	Other:_ ty	District (District (Distri	Ct) Well ed to the ent of the ent
Ott Constant	Civil Engineer Ritimated Depth of Call is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal her wells exist on nderstand and agricultural agr	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	han 50 feet In a public top of a creek b CHATION THE PROPOSE TO	Geologis 50 to road ank or Dist DEWATI Tem atus: SIGNA equired to take permit (I, electroniment has being the Dist	st Regist 300 feet On publishing tracities I BERING nament porary Active TURES be done see pagic, or pho	ration No ration No ration No property HEA- EXCHAP Closs Loop Loop Inactiv In according 2) certocopied, nalized being change	Over:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned with Santa Clara Vet the information horized and valid the well owner are purpose of this wante of Property Name of Property	Other:_ ty	District (District (Distri	Ct) Well ed to the ent of the ent
Sign Sign Sign Sign Sign Sign Sign Sign	Civil Engineer Retimated Depth of Cell is to be constructed by WATER PRODUCTION Agricultural Domestic Industrial Municipal Municipal her wells exist on Inderstand and agricultural and agricultural Industrial	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	han 50 feet In a public top of a creek become a cr	Geologis Geologis Geologis Geologis For to	st Regist 300 feet On public frict racill ERING nament porary Active TURES be done see pagre c, or pho-	ration No ration No ration No property HEA- EXCHAP Closs Loop Loop Inactiv In according 2) certocopied, nalized being change	Cover:	Groundwater Reinjection Stormwater Water Suppi Other Abandoned with Santa Clara Ver the information horized and valid the well owner are purpose of this storm of Property	Other:_ ty	District (District (Distri	Ct) Well ed to the ent of the ent
Ott Ore on also ap Sig	Civil Engineer Retimated Depth of Cell is to be constructed by the Construction of Cell is to be constructed by the Cell is to be constructed by the Cell is to my knowledge forceable. I also conderstand that plication of Properting apartire of Well Organiture	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	han 50 feet In a public top of a creek become a condition of the conditions of t	Geologis 50 to road ank or Dist DewATI Pern Tem Tem SiGNA equired to to the permit (all, electroniment has being the Dist Company of the Dist Company	st Regist 300 feet On publishing tracities I BERING nament porary Active TURES be done see pagic, or pho	ration No ration No ration No property HEA- EXCHAP Closs Loop Loop Inactiv In according 2) certocopied, nalized being change	Cover: Cover:	Groundwater Reinjection Stormwater Water Supplication Abandoned with Santa Clara Valid the well owner are purpose of this supplication work of Property Name of Property Name of Diller/Ag	Other:_ ty	District (District (Distri	Ct) Well ed to the ent of the ent
Ott Ore on also ap Sig	Civil Engineer Ritimated Depth of Cell is to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal Mer wells exist on Inderstand and agricultural agricultural and agricultural agricultur	egistration No. Completed Well: cted:	□ Less to the solic sidewalk to feet of the Remi □ Air Spath GW Ext GW Ext GW Capper E GW Ca	han 50 feet In a public top of a creek become a cr	Geologis 50 to road ank or Dist DewATI Pern Tem Tem SiGNA equired to to the permit (all, electroniment has being the Dist Company of the Dist Company	st Regist 300 feet On public trict tacill I ERING nament porary Active TURES be done see pagr c, or phoeen form rict of ar	ration No ration No ration No representation Coproperty HEAN EXCHAN Loop Loop Loop Inactive in according 2) certain copied, nalized beiny change	Over: Over: Tover:	Groundwater Reinjection Stormwater Water Supplication Abandoned with Santa Clara Vert the information horized and valid, the well owner are purpose of this same of Property Name of Property Name of Well Ow Acres B D S	Other: ty On D *See Ge The Cleanup y Recharge (alley Water given in this and is affixed froperty owell, from whether the control of the	District (District (Distri	Ct) Well ed to the ent of the ent

IMPORTANT:

A minimum 24-hour notice must be given to Santa Clara Valley Water District Well Inspection Department prior to installing the annular seat. Call (408) 255-2507, ext. 2550. Please allow 10 working they to process permit application.

5750 Almaden Expressway San Jose, CA 95118-3686 (408) 265-2600

WELL CONSTRUCTION APPLICATION

FC 158 (03-28-13) Page 2 of 2

ì,	DISTRICT WELL PERMIT NO.	13400768
	sed on information on this application and attachment(s) hereto (if any) and subject to approval noted ill) the described well. Permission to start work may be withheld until a field check verifies all statems bject to the "General" and "Special" Conditions stated below.	below, permission is hereby granted to construct ents made on application by permittee and is also
	SANTA CLARA COUNTY DEPARTMENT OF ENVIRONMENTAL HEALTH APPRI	OVAL (Water Supply Well Only)
VO	TE: Department of Environmental Health approval must be granted before this application will be acc	cepted by Santa Clara Valley Water District
App	proved by:	
	, R.E.H.S	☐ Approved as submitted ☐ Approved as corrected
SIT	TE PLAN	Date:
_	3½" x 11" paper site plan must be attached to this application, including:	
	Location of site features, including major buildings, landscaped areas, tank fields, existing wells, etc.	
2.	North arrow and scale	4
3.	Location of proposed well with dimensions in feet from well to nearest cross streets.	
GΕ	NERAL CONDITIONS	
3.	District (telephone 408-265-2607, ext. 2660) must be notified a minimum of one working day brauthorized District representative must be on site to witness the construction of the annular seal. The District representative. If the District waives the inspection requirement, the District may request the perjury, that the well was constructed in accordance with the District Well Standards and with the permittee agrees to construct, operate, and maintain the well according to provisions of the latest D of District Well Standards to the end that this well will not cause pollution or contamination of ground welfare of the people of the District.	his requirement may be waived by an authorized a permittee(s) to furnish certification, under penalty of ermit conditions.
3.	This permit is valid only for the purpose specified herein. Well construction methods authorized und approval of an authorized District representative, and only if the District believes that such a change District and State Well Standards (e.g., if the District representative finds that site conditions warranted.	
ο.	This permit is only valid for the Assessor's Parcel No. indicated on it.	
	This permit may be voided if it contains incorrect information. If the permit is voided after work has this permit must be destroyed in accordance with District and State Well Standards.	
	If any work associated with this permit will take place on District property/easement, an encroachme District's Community Projects Review Unit (telephone 408-265-2607, ext. 2589).	
3,	Before the well constructed under this permit can be used as a drinking water source, its use must be over such use (typically the Santa Clara County Department of Environmental Health or the State of completed Well Inventory Form must also be approved.	California Department of Public Health). A
ł.	If the well constructed under this permit cannot be or is not being used for its intended purpose, per according to the District Well Standards and under permit from the District. Any test holes drilled un completion of testing activities. Destruction activities must be completed according to District standards hours prior to destruction.	refere their meanable married that the state of the state
٦	Within 30 days of the completion of the well construction activities, the driller or consultant identified DWR Form 188 and mail the original to the District's Wells and Water Production Unit.	on this permit shall fully complete State of California
	The permittee(s) shall assume entire responsibility for all activities and uses under this permit and si officers, agents, and employees, free and harmless from any and all expense, cost, and liability in continuous exercise of this permit including, but not limited to, property damage, personal injury, and wrongful damage.	onnection with or resulting from the granting or
ζ.	Permittees are required to be in full compliance with Cal/OSHA California Labor Code Section 6300.	
+	A current C-57 Water Well Drilling Contractor's License is required for the construction of all wells.	
Λ.	Permittee, permittee's contractors, consultants, or agents shall be responsible to assure that all mate construction, well development, pump testing, or other activities associated with this permit will be sa according to all applicable federal, state, and local statutes regulating such. In no case shall these notentially enter, on- or off-site storm sewers, dry wells, or waterways. Such materials/waters must work is being completed.	afely handled, properly managed, and disposed of
1	monities sound completed.	
).	The driller and consultants (if applicable) shall have an active copy of their Worker's Compensation I. This permit shall expire if not exercised within 180 calendar days of its approval, unless an extension authorized District representative.	Insurance on file with District. n of the permit expiration date is granted by an
	This permit must be kept on site during all activities associated with it and shall immediately be preserequest.	
PE	ECIAL CONDITIONS	STEEDS IN COURT A STEED STEED STEEDS
_	mmunity Projects Review Unit Approval (if needed):	CPRU Permit No.:
pp	proved by:	Date:

Sonta Clara Valley Water District

5750 Almaden Expressway San Jose, CA 95118-3666 (408) 265-2600

WELL CONSTRUCTION APPLICATION

FC 158 (03-28-13) Page 1 of 2

			1	OBEC	OMPLET	ED BY D	DISTRUCT					
Dist	rict Permit No.:	134-00	169	Date (sayad)			Weil Registration No.:					
Geo	logic Setting:	01		Expire	tion Date	1 1 5	1/4.	12	Driller's Log I	No.: € &	1779	69
			TO BE	COMPLE	ETED BY	OWNER	AND DRIL	LER				
	Owner: ET Services Inc.	A CONTRACTOR OF THE CONTRACTOR	Property City of S	Owner:					Name of Business at Well Site: City of Sm Jose- Public road			
-	Owner's Mailing	Address:	The second second	manager (Antonomyce)	s Malling	Address	:		Address of			
200	S. Akard St., Roon	n 1700	127.2						Almaden Bou			
100	, State, Zip as, TX 75202		City, Sta	ate, Zip					City, State, 2 San Jose, CA			
Tele	aphone No. & Co. 567-1578/Mark St		Telepho	ne No. 8	& Contact	Name:			Telephone N	10.:		
Ow	ner's/Consultant's	Well No.:MW-12		Asses	sors Pa	rcel No. o	of Well Site:		Book 259	Page 3	9 Parce	500
	sultant (Compan w Environmental II						Company: Drilling LP	7				(039)
Add	lress: 4005 Port	Chicago HWY				Addres	e: 120 Sout	h 23r	d Street			
City	State Zip Co	oncord, CA 94520				City, St	late, Zip	Richr	ninid, Ca 94804			
Telephone No.: 925-288-2366					Teleph 510-478	one No.: 5-0858			C-57 Licens 938110	e No.:		
	Check if address	or phone number h	as changed			Che	eck if address	s or	phone number t	as changed		-
,	the second secon	CALLEY OF A MANAGEMENT OF STREET	OR ALL MONITORI	NG WEL	LSORE	XTRAC	TION/RECO	VER	Y WELLS			
	AND ADD DESCRIPTION OF THE PARTY OF THE PART	cific Bell- 95 S Alm					orker Name					
Ove	ersight Agency:	County of Santa Cla	ra-Department of Envir	onmental	Health	Casew	orker Telep	hone	No.: 406-918-1	954		
-	Civil Engineer R imated Depth of It is to be constru	Completed Well:	Less than 50 folio sidewalk	public re	50 to	st Regist 300 feet On publi	c property		00 feet On private prope		strict property	
USE	WATER PRODUCTION	MONITORING	REMEDIATION		DEWAT		HEAT EXCHANG	E	INDECKI		OATHODIC PROTECTION	OTHER
WELL TYPE/USE	Agricultural Domestic Industrial Municipal	GW Level GW Quality Inclinometer Vapor Other	Air Sparge GW Extraction Material Emplace Vapor Extractio Other	Add Carried A.	☐ Peri	manent	Closes Loop Open Loop	7	Groundwate Reinjection Stormwater Water Supp Other	r Cleanup ly Recharge		
Ot	her wells exist on	this property?	Yes No If	yes, sta	-	Active	☐ Inactive		Abandoned			
Or be en als	dinance 90-1, the st of my knowled forceable. Laiso	District Well Stand ge and that the sign certify that a right of	isociated with this per iards, and the condition alture below, whether of entry/encroachmen- lility, as the well owne	ons of the original tacreer	quired to is permit , electron	(see pag ilc, or pho seen form	in accordar le 2) certi otocopied, in nalized betw	fy the s auth veen	it the information norized and valid the well owner a	n given in this i, and is affixe and property c	permit is corr ad with the into wner, if partie	ed to the ent to be as differ. I
Si	phature of Proper	ty Owner gent		Date		-30.	11 1000	Print j	LUB D	y Owner Age	6720	
SI	gnature of Well C	wner/Sueni		Date	OS	-30	1-13	X1117.	Pame of Well Ov	ELNA	900	
Si	gnature of West	William I		Date		0/2013		Print I	vame of Driller/A	Agent: Raiph	McGahey	
Si	gnature of Const	mant/Appht:		Date	203	-30	-13	Prince	Name of Bonsul	iani/Agent:	5720	

IMPORTANT: A minimum 24-hour notice must be given to Santa Clara Valley Water District Well Inspection Department prior to installing the smuller social. Call (408) 265 2607, ext. 2660. Please allow 30 working they see process permit application.

5750 Almaden Expressway San Jose, CA 95118-3686 (408) 265-2600

WELL CONSTRUCTION APPLICATION

FC 158 (03-28-13) Page 2 of 2

DISTRICT WELL PERMIT NO .:

13 woo 260

Based on information on this application and attachment(s) hereto (if any) and subject to approval noted below, permission is hereby granted to construct (drill) the described well. Permission to start work may be withheld until a field check verifies all statements made on application by permittee and is also subject to the "General" and "Special" Conditions stated below. SANTA CLARA COUNTY DEPARTMENT OF ENVIRONMENTAL HEALTH APPROVAL (Water Supply Well Only) NOTE: Department of Environmental Health approval must be granted before this application will be accepted by Santa Clara Valley Water District. ☐ Approved as submitted Approved by: ☐ Approved as corrected , R.E.H.S Date: SITE PLAN A 81/2" x 11" paper site plan must be attached to this application, including: Location of site features, including major buildings, landscaped areas, tank fields, existing wells, etc. North arrow and scale Location of proposed well with dimensions in feet from well to nearest cross streets. 3. **GENERAL CONDITIONS** District (telephone 408-265-2607, ext. 2660) must be notified a minimum of one working day before construction of the annular seal. An authorized District representative must be on site to witness the construction of the annular seal. This requirement may be waived by an authorized District representative. If the District waives the inspection requirement, the District may request the permittee(s) to furnish certification, under penalty of perjury, that the well was constructed in accordance with the District Well Standards and with the permit conditions. Permittee agrees to construct, operate, and maintain the well according to provisions of the latest District Ordinance and the latest published revisions of District Well Standards to the end that this well will not cause pollution or contamination of groundwater or otherwise jeopardize the health, safety, or welfare of the people of the District. This permit is valid only for the purpose specified herein. Well construction methods authorized under this permit may not be changed except by written approval of an authorized District representative, and only if the District believes that such a change will result in equal or superior compliance with the District and State Well Standards (e.g., if the District representative finds that site conditions warrant such a change). This permit is only valid for the Assessor's Parcel No. indicated on it. This permit may be voided if it contains incorrect information. If the permit is voided after work has begun, the well or boring that was constructed under this permit must be destroyed in accordance with District and State Well Standards. If any work associated with this permit will take place on District property/easement, an encroachment or construction permit must be granted by the District's Community Projects Review Unit (telephone 408-265-2607, ext. 2589). G. Before the well constructed under this permit can be used as a drinking water source, its use must be approved by the regulatory agency with authority over such use (typically the Santa Ciara County Department of Environmental Health or the State of California Department of Public Health). A completed Well Inventory Form must also be approved. If the well constructed under this permit cannot be or is not being used for its intended purpose, permittee is hereby required to destroy the well according to the District Well Standards and under permit from the District. Any test holes drilled under this permit must be destroyed within 24 hours of completion of testing activities. Destruction activities must be completed according to District standards. District must be notified a minimum of 24 hours prior to destruction. Within 30 days of the completion of the well construction activities, the driller or consultant identified on this permit shall fully complete State of California I. DWR Form 188 and mail the original to the District's Wells and Water Production Unit. The permittee(s) shall assume entire responsibility for all activities and uses under this permit and shall indemnify, defend, and hold the District, its officers, agents, and employees, free and harmless from any and all expense, cost, and liability in connection with or resulting from the granting or exercise of this permit including, but not limited to, property damage, personal injury, and wrongful death. Permittees are required to be in full compliance with Cal/OSHA California Labor Code Section 6300. A current C-57 Water Well Drilling Contractor's License is required for the construction of all wells. Permittee, permittee's contractors, consultants, or agents shall be responsible to assure that all materials or waters generated during drilling, well construction, well development, pump testing, or other activities associated with this permit will be safely handled, properly managed, and disposed of according to all applicable federal, state, and local statutes regulating such. In no case shall these materials and/or waters be allowed to enter, or potentially enter, on- or off-site storm sewers, dry wells, or waterways. Such materials/waters must not be allowed to move off the property where the work is being completed. The driller and consultants (if applicable) shall have an active copy of their Worker's Compensation Insurance on file with District. This permit shall expire if not exercised within 180 calendar days of its approval, unless an extension of the permit expiration date is granted by an authorized District representative. This permit must be kept on site during all activities associated with it and shall immediately be presented to an authorized District representative upon request. SPECIAL CONDITIONS CPRU Permit No.: Community Projects Review Unit Approval (if needed): Date: Approved by: -14-13

Sonto Coro Volley Water District San Jose, CA 95118-3686 (408) 285-2600

WELL CONSTRUCTION APPLICATION FC 158 (03-25-13) Page 1 012

-			TO SE C	OMPLETE.	Savo	ISTRICT				
istric	Permit No.;	13 W00		ssues 🗢	1.78	1119	Well Registra	dipp (Va =		
-	gic Setting:	101		sijon Dale	15	A DIGITAL	Sriller allog	4.00	17799	3/47
	314 4411113		TO BE COMPLE	ETED EY C	WIKER	AND DRILLE				
ell C	wner:		Property Owner				Name of Bus	iness at Well	Site:	
T&T	Services Inc.		City of San Jose		City of San Jose- Public road					
	Owner's Mailing Akard St., Room		Property Owner	's Mailing A	daress		Address of Almaden Bou			
	State, Zip	100	City, State. Zip				City, State, Z	lip .		
4.0	TX 75202		12027				San Jose, CA	95113		
	hone No. & Con		Telephone No. (& Comact N	dame:		Telephone N	10.:		
wne	r's/Consultant's	Well No.: MW-13	Asse	ssor's Parce	el No. c	Well Site:	Book 259	Page 3	9 Parce	500
Consultant (Company): Shaw Environmental Inc					Company: Drifting LP			(039	
Andrews Name	ess: 4005 Port C				Appres	g: 120 Sout 23	nd Street			
2010		2.219								
ity, S	State, Zip Co	ncord, CA 94520			Sept. 19	Telephone Community	minne La 94804		- 11	
CONT.	hone No.:				200	one No.:		C-67 Licens 935:110	E MO.:	
	88-2366		No. of the second secon	Firm and a second	510-478	and the second district to the second distric	shame promised to	1177777		
C	neck if address	or phone number h	as changed		Petition		phone number h	ree enembed		
			OR ALL MONITORING WE	LLS OR EX		orker Name: A				
		cific Bell- 95 S Alma	ra-Department of Environmenta				E No.: 408-916-	180.54		
Vell	Civil Engineer Renated Depth of Cis to be constru WATER PRODUCTION Agricultural Domestic Industrial Municipal	Completed Well:	□ Less than 50 feet So feet of the top of a creek bit	50 to 3	300 feel On publicitation rict facil RING	c property	On private proper INJECT Groundwate Reinjection Stormwaler	"See Ge	istrict property neral Condition CATHODIC PROTECTION	
Othe	er wells exist on		Yes No If yes, sta	atus: 🖾 A	Active	☐ Inactive ☐	Absnooned			
-				SIGNA	TURES		- 11 - 11 - 11 - 11 - 11 - 11 - 11 - 1			
Ordi besi enfo also app Sign	inance 90-1, the tof my knowled proeable. I also understand the lication.	e District Well Stand ge and that the sign certify that a right of at it is my responsibility Owner/Agant	esociated with this permit is reduced, and the conditions of the nature below, whether original of entry/encroachment agreer willty, as the well owner, to not part of the par	nis permit (tal, electronic ment has be lify the District.	see pay c, or ph	otocopied, is at malized between the changes in the	thorized and valid in the well owner he purpose of the	d, and is affixed and property of swell, from with Owner/Apenii	ed with the initiowner, if partitioning in inches in indication in indication in inches in inche	ent to be
Sig	nature of Cons	771 /	Da	te: OS -	30	~13 Png	Name of String	ELNA		
IM	PORTANT:	Am. simum 244 amular seal. G	nour motice must be given b all (400) 265-7607 and 2660	o Santa Ch). Phase a	ara Val New W	ley Water Dist Lever long days	nct (vie) (Inspect No process (ven	ion Departme nii symbostic	an) grior 10 m m	ista)liir

/50 Almaden Expressway San Jose, CA 95118-3686 (408) 265-2600

Approved by:

WELL CONSTRUCTION APPLICATION

FC 158 (03-28-13) Page 2 of 2


DISTRICT WELL PERMIT NO .:

13400270

	sed on information on this application and attachment(s) hereto (if any) and subject to approval noted b ill) the described well. Permission to start work may be withheld until a field check verifies all statement pject to the "General" and "Special" Conditions stated below.	ts made on application by permittee and is also
	SANTA CLARA COUNTY DEPARTMENT OF ENVIRONMENTAL HEALTH APPROV	VAL (Water Supply Well Only)
NO	TE: Department of Environmental Health approval must be granted before this application will be acce	pted by Santa Clara Valley Water District
App	proved by: , R.E.H.S	☐ Approved as submitted ☐ Approved as corrected
	, , , , , , , , , , , , , , , , , , ,	Date:
SIT	E PLAN	Dato.
A 8	½" x 11" paper site plan must be attached to this application, including:	
1.	Location of site features, including major buildings, landscaped areas, tank fields, existing wells, etc.	
2.	North arrow and scale	
3.	Location of proposed well with dimensions in feet from well to nearest cross streets.	
	NERAL CONDITIONS	
Α.	District (telephone 408-265-2607, ext. 2660) must be notified a minimum of one working day befine authorized District representative must be on site to witness the construction of the annular seal. This District representative. If the District waives the inspection requirement, the District may request the perjury, that the well was constructed in accordance with the District Well Standards and with the permitted to the permitted of the permitt	requirement may be waived by an authorized permittee(s) to furnish certification, under penalty of mir conditions
B.	Permittee agrees to construct, operate, and maintain the well according to provisions of the latest Dist of District Well Standards to the end that this well will not cause pollution or contamination of groundwwelfare of the people of the District.	fried Challenger and the first of the first
C.	This permit is valid only for the purpose specified herein. Well construction methods authorized under approval of an authorized District representative, and only if the District believes that such a change we District and State Well Standards (e.g., if the District representative finds that site conditions warrant state of the District representative finds that site conditions warrant states are set of the District representative.	all remarks in a manual control of the control of t
D.	This permit is only valid for the Assessor's Parcel No. indicated on it.	
Ε.	This permit may be voided if it contains incorrect information. If the permit is voided after work has be this permit must be destroyed in accordance with District and State Well Standards.	
F.	If any work associated with this permit will take place on District property/easement, an encroachment District's Community Projects Review Unit (telephone 408-265-2607, ext. 2589).	
G.	Before the well constructed under this permit can be used as a drinking water source, its use must be over such use (typically the Santa Clara County Department of Environmental Health or the State of Completed Well Inventory Form must also be approved.	California Department of Public Health). A
H.	If the well constructed under this permit cannot be or is not being used for its intended purpose, permit according to the District Well Standards and under permit from the District. Any test holes drilled under completion of testing activities. Destruction activities must be completed according to District standard 24 hours prior to destruction.	er this permit must be destroyed within 24 hours of ds. District must be notified a minimum of
I.	Within 30 days of the completion of the well construction activities, the driller or consultant identified or DWR Form 188 and mail the original to the District's Wells and Water Production Unit.	
J.	The permittee(s) shall assume entire responsibility for all activities and uses under this permit and sha officers, agents, and employees, free and harmless from any and all expense, cost, and liability in con exercise of this permit including, but not limited to, property damage, personal injury, and wrongful des	
K.	Permittees are required to be in full compliance with Cal/OSHA California Labor Code Section 6300	
L.	A current C-57 Water Well Drilling Contractor's License is required for the construction of all wells	
М.	construction, well development, pump testing, or other activities associated with this permit will be safe according to all applicable federal, state, and local statutes regulating such. In no case shall these ma potentially enter, on- or off-site storm sewers, dry wells, or waterways. Such materials/waters must no work is being completed.	ely handled, properly managed, and disposed of sterials and/or waters be allowed to enter, or to be allowed to move off the property where the
N.	The driller and consultants (if applicable) shall have an active copy of their Worker's Compensation ins	surance on file with District
	authorized District representative.	of the permit expiration date is granted by an
P.	This permit must be kept on site during all activities associated with it and shall immediately be presen request.	ted to an authorized District representative upon
SPE	CIAL CONDITIONS	·
Com	nmunity Projects Review Unit Approval (if needed):	

Date:


6-14-13





Almaden Blvd./Post St.





Well Annotations- 13 Wells Selected

No	Well_nbr	Permit	Consultnum	Status	Easting	Northing
1	07S01E08N006	85W0442	GX-19A	Other-Active	6156985	1946948
2	07S01E08N007	85W0443	GX-19	Other-Active	6156983	1946965
3	07S01E08N008	85W1588	No Data	Other-Active	6156337	1946900
4	07S01E08N015	87W0696	MW-2	Other-Active	6156309	1946960
5	07S01E08N021	92W0637	MW-2	Other-Active	6156680	1946744
6	07S01E08N022	92W0638	MW-3	Other-Active	6156586	1946935
7	07S01E08N023	92W0640	MW-5	Other-Active	6156467	1946758
8	07S01E08N029	95W00447	MW 1	Other-Active	6156448	1946784
9	07S01E08N030	95W00446	MW 4	Other-Active	6156512	1946669
10	07S01E08N031	95W00445	MW 6	Other-Active	6156416	1946785
11	07S01E08N037	08W00033	MW-9	Other-Active	6156517	1946726
12	07S01E08N038	08W00034	MW-8	Other-Active	6156512	1946776
13	07S01E08N039	08W00035	MW-7	Other-Active	6156439	1946841


WELLS.shp

- Water Supply Active
- Water Supply Standby
- Water Supply Inactive
- Extraction (Env) Active
- Extraction (Env) Inactive
- Other Active
- Other Inactive
- Abandoned
- Destroyed Status Undetermined
 - PARCELS.SHP

Approximate Scale 100 Feet

O:\Post_GPS_Check\gpschkbc.apr

APPROVED FOR THE








Downtown Lane Closure Request Form

Complete the form below with all the relevant information. Provide with this form a traffic control plan (see attached examples). A separate form is required for each lane closure. Please fax to (408) 292-6090 or e-mail to noe.veloso@sanjoseca.gov the completed form 10 days prior to start of closure. For more information regarding this form, please contact CSJ Downtown Traffic Operations Program Manager Noe Veloso @ 408-975-3246

Requestor's Name:	Rob Delnagro OR SHELLA KENHEDT AT GIT-910-6058 GUI
Company:	AT&T Services/Shaw Environmental
Daytime Phone #:	925-288-2103
Fax #:	
Project Name:	95 S. Almaden AT&T Facility
DPW Encroachment Permit #:	3-05666
Inspector Name & #	MARTY WORMOUTH 408-975-7436
Locations:	West San Fernando Street between South Almaden Avenue and Almaden Boulevard; And Almaden Boulevard between West San Fernando Street and Post Street.
Activities:	Utility Location and Soil Boring/ Well installation.
Closure:	Partial closures, lane reductions to one lane eastbound and one lane westbound on West San Fernando Street.
Timeline:	Two lanes on Almaden Boulevard. June 11, 2013 through June 28, 2013
Work Hours:	09:00 AM to 3:00 PM - <60 hours
Detours (if any):	
Note:	
Lead Agency:	PW DEVELOPMENT
Requestor's Name:	Sample Request John Smith
Company:	ABC Constructions Inc.
Daytime Phone #:	(408) 1234568
Fax #:	(408) 1234569
Project Name:	Utility conduit installation
Permit #:	X12345-67
Locations:	Reed St. between S. Market St. and Almaden Ave.
Activities:	Installing a utility conduit.
Closure:	One eastbound lane on Reed St. will be closed between Market St. and Almaden Ave.
Timeline:	Thursday, September, 18th through October 31st
Work Hours:	9:00 a.m. to 3:00 p.m.
Detours (if any):	From EB: NB Almaden Ave. to EB Balbach St to SB Market ST to Reed St
Note:	Police officers will be helping to direct traffic, local access will be maintained.
Lead Agency:	DPW – Utilities
Inspector Name & #:	Robert Jordan @ 408-123-4567







SAN JOSE DOT PERMITS SAN JOSE, CA 95113

TOW-AWAY PERMIT NO.: 13-813

TERMINAL ID: MERCHANT #:	003979739 329074612998		
		ORTATION	
₩ ₩ ₩ ₩ X X X X X X X X X X X X X X X X	×××1339	it Applicant ("PERMITTEE")	
SALE BATCH: 000942 DATE: JUN 11, 13 SQ: 001	INVOICE: 0420720100 IIME: 09:19 AUTH NO: 121907	Kennedy	Title: En Scientist al / CB+ I City: En Francisco State: CA Zip: 94107
	\$454.35	2.2419 Cell: 61	7-910-6058 Pager:
PO: (NONE)			name and contact information on the posting log)
- Garage	MER COPY INC THE SPECIFIC C 7 Stall So	The state of the s	pe performed within the street right-of-way:
		tow-away signs will be posted a	
Street Street		an Fernando St ^b etween between	A Lmaden Blod and 5. Almaden Are and
Total Meter 3. The e Effect Effect Effect 4. City J	Number of Parking Number (cont.): _ ffective days, date ive Days: M ive Date(s): ive Hour(s):	Metered Spaces (if any): 12 SFW207, SFW209, es, and times to be shown on the on. Tues. Wed. From: June 12, From: 7 am	7013 To: June 21, 2017 To: 5pm
Section C			n plus tax, \$5/day lost meter revenue if applicable)
Total amou	unt due: \$_	458.35 Tota	Il # of signs: 12
Section D	: Permittee's Sta	atement of Understanding	*
POSTING spaces wil and poles parked wi	INSTRUCTIONS". I be charged if me may also be chargethin the tow-away	This Tow-Away permit is issue ters are affected by the tow away ged under separate cover if applic	instruction sheet entitled "TOW AWAY PERMIT CONDITIONS AND downwith the understanding that a fee covering lost revenue on metered zone. Additional fees for the removal and replacement of meter heads cable. A copy of this permit must be displayed on all work vehicles Date:
Section E	: Department of	Transportation Authorization	
	times, and locat		sion to the applicant to post temporary Tow-Away/No Stopping signs for ance with the "TOW AWAY PERMIT CONDITIONS AND POSTING
	half of Hans F. Lar		THANSPORTATION
Depar	tment of Transport	ation	CITY OF SAN JOSE
Date: Cashi		//5_	200 EAST SANTA CLARA STREET SAN JOSE, CA 95113
Recei	pt No.:		/01
Data			(Stamp Here)



TOW-AWAY PERMIT FEE CALCULATION WORKSHEET

(office use only)

DEPARTMENT OF TRANSPORTATION

SHAW ENVIROMENTAL / CB & I PERMIT NO. 13-813

I. TOW AWAY PERMIT FEES

Description	Quantity	Unit Cost	# of Days	Sales Tax	Sub-Total
Permit Application - Processing Fee	1	\$30.00			\$30.00
Tow-Away Sign - Material Fee	12	\$0.64			\$7.68
Tow-Away Sign – Sales Tax				8.75%	\$0.67
Lost Meter Revenue Fee (daily)	12	\$5.00	7		\$420.00
Meter Head Removal	0	\$25.00			\$0.00
Meter Pole Removal	0	\$75.00	Y		\$0.00
				Total Cost:	\$458.35
			Approved by	(enter initials):	MV

- A \$30.00 administrative processing fee is assessed for each permit application issued. One permit application is required per job
 contract, which can include multiple streets, as long as the same work activity is performed on these streets under a single
 contract.
- A \$0.64 (plus tax) material fee is assessed for each Tow-Away sign issued.
- A \$5.00/day fee is assessed for <u>each</u> parking meter that is affected by tow away sign posting. This fee covers lost revenue to the City while meters are temporarily out of service.
- No fee is assessed for extending the dates on an existing permit. However, if work is being done on new street locations not
 originally included on the permit or new work activities are occurring, then a new permit must be processed and all fees assessed.

II. PARKING METER FEE INFORMATION

- Customer is responsible for providing meter I.D. numbers for all meters that need to be removed and replaced.
- In addition to all other fees, a \$25.00 fee is assessed for <u>each</u> meter head that needs to be removed. Meter heads may need to be removed from the pole if the work involves oversized equipment that may damage the meter.
- In addition to all other fees a \$75.00 fee is assessed for <u>each</u> meter pole (pole + meter head) that needs to be removed. Meter poles may need to be removed if the work involves oversized equipment that may damage the meter pole.

Customer is responsible for contacting the, Parking Division at (408) 534-2922 to schedule parking meter removal/replacement. Customer will be billed under separate cover by Parking Division staff.

Customer may rent a meter hood at \$5.00/day per meter hood. A meter hood is a bag that a customer can place over a meter to
exempt him/her from having to pay the meter, but this does not reserve a metered parking space. There is a \$50.00 deposit for
each meter hood rented. This is a convenience service available to contractors working on job sites located within metered zones.
Meter hoods cannot be used within the boundaries of the Tow Away Permit.

- 8. Permittee must remove all tow-away signs and fastening materials from poles and meters upon completion of work on a particular street. Permittee shall pay for the repair of any damage caused to any public property to which the temporary tow-away sign was attached. Permittee shall pay the actual cost to the City of having to remove any signs the Permittee fails to remove.
- 9. Permittee must remove any posted tow-away signs if work on any particular street has been delayed or suspended for any reason and shall make good faith efforts to not unnecessarily restrict public parking.
- 10. In the event that the Department of Transportation approves the original permit for extension, Permittee shall post new temporary tow-away signs with the extended term in accordance with conditions 1-9 stated above. Permittee must also fax a revised posting log to Parking Compliance immediately after reposting new signs.
- 11. Permittee shall be responsible for properly initiating all tows under the permit. A copy of the Tow Away Posting log sheet must have been faxed to the Parking Compliance Office at (408) 288-7322.
- 12. Permittee may initiate a tow request by contacting the Parking Compliance Unit at (408) 534-2900 during the hours of 8:00am to 5:00pm Mon. through Fri. For all other times call the non-emergency number 311(City Communication Center), or (408) 277-8900, if using a mobile phone. Permittee MAY NOT contact a towing company directly since a law enforcement officer must issue the tow request.
- 13. When initiating a tow request, the Permittee shall provide the law enforcement officer with a copy of the permit along with the completed original Documentation in Support of Tow-Away form and a record of the time, date, and location of when the signs were posted, as well as the name of the person posting the signs. Photocopies of signed declarations will not be accepted.
- 14. The Permittee will indemnify and hold harmless the City from all damages, losses or claims arising out of or resulting from a tow initiated by Permittee pursuant to his/her tow-away permit. Permittee must pay for all costs associated with invalid tows.
- 15. The Department of Transportation reserves the right to revoke tow-away permits or revise the approved days, hours or street locations on any Tow Away permit application at any time.
- 16. Unless specifically stated on the permit, this permit is not to reserve parking space(s) for personal use. Only construction related vehicle(s) that are continuously used are allowed in the tow-away zone.
- 17. A valid copy of the Tow-Away permit must be clearly visible on the dashboard of all vehicles parked within a tow-away zone. Absolutely no personal vehicles will be allowed to park within the tow-away zone. Any personal vehicles parked within the restricted area regardless of displaying a valid Tow-away permit will be subject to a citation.

I acknowledge that I have read and understand the above "Tow-Away Permit Conditions and Posting Instructions"

Permittee Name (signature): She By Burly

Permit No: 13-813

Permittee Name (printed): Sheila Kennely

Permittee Phone Number: 97.90.60.58

Date: 6/11/13

* Permittee must sign above prior to permit being issued



City of San Jose

Department of Public Works • Development Services Division 200 E. Santa Clara St. • San Jose, California 95113 (408) 535-3555

Permit and Required Inspections

Revocable	Encroachment	Permit	(D-Soil Boring	1)

Permit Number: 13 104288 RV (3-05666)

Project Name: 3-05666RV

Permit Expires: 09/05/2013 *

Description: 6 SOIL BORINGS ALONG (N/S) OF ALMADEN BLVD & 4 SOIL BORINGS ALONG (W/S) OF W. SAN

FERNANDO ST. (10 SOIL BORINGS ON PUBLIC RIGHT OF WAY)

Location / Address: (N/W) CORNER OF W. SAN FERNANDO ST & ALMADEN BLVD

95 S ALMADEN AV

Applicant / Permittee	Property Owner	Contractor	Engineer / Architect
WILLIAM WERNER CB&I (Chicago Bridge & Iron Co.) 185 BERRY ST Suite 2200	PACIFIC BELL	NONE	NONE
SAN FRANCISCO CA (415)512-2426/(415)512-2424	(925)699-1631		

Additional Information

Allowable Working Hours

ding Hours

Total # of Borings/Wells/Potholes/N Amount of Surety

Surety Issued by (Bank Name)

Surety provided by:

8:00AM-4:30PM

10 6000

REGIONS BANK

APPLICANT (CB&I/SHAW INVIRONN

Downtown (RDA)?

Street Closure Needed? Type of Surety

Surety Reference No.

Yes

No Cashier's Check

5501038125

Permit Fees

Fee Description	Amount	Receipt No.	Fee Description	Amount	Receipt No.
PW-Record Retention Fee	\$105.00	711320	PW-Revocable Encroachment Permit F€	\$2,026.00	711320
PW-NR-Underground Service Alert Fee	\$600.00	711320			

Required Inspections

6032 - Site Inspection

The Contractor shall notify the Public Works Project Inspector Marty Wormuth at least 24 hours prior to starting work: Voicemail: (408) 975-7436 Main Office: (408) 535-3555 E-mail: martin.wormuth@sanjoseca.gov

Conditions: CONTRACTOR SHALL CONFORM TO THE ATTACHED PLAN, DETAIL & CONDITIONS.

CONTRACTOR SHALL COORDINATE WITH PW INSPECTOR PRIOR TO START OF ANY WORK AND COORDINATE TRAFFIC/PEDESTRIAN SAFETY CONTROL.

Permit Expires: 09/05/2013 *

Permit Issued: June 07, 2013

Project Engineer: Vivian Tom


By signing below, I agree that the information provided is true and correct, and that the construction will conform to the approved plans, attached conditions and the San Jose Municipal Code.

Applicant/Permittee:

- .

06-10-2013

^{*} IF THE WORK CANNOT BE COMPLETED BY THIS DATE, YOU SHOULD DISCUSS THE POTENTIAL OF EXTENDING THE PERMIT WITH THE CITY PROJECT ENGINEER. THIS MAY REQUIRE THE PAYMENT OF ADDITIONAL FEES.



O DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	BORING NO. SB-1 COORDINATES: N. E. FIELD GEOLOGIST S.B.Kennedy CHECKED BY J. Pickard APPROVED BY TOTAL DEPTH 28.0' DESCRIPTION
 5 -	- 1320		1.8 3.1 2.1 3.5 3.1		sm		SILTY SAND; brown, moist, loose, trace medium gravel and organics At 4.5': Trace fine gravel. At 11.0': Medium dense.
- 15 -			3.3		sc		14.0
- 20	J		5.4 316	<u>ड</u> ू 16.5'	ml		SILT; gray, saturated, medium dense, little fine sand, trace fine gravel, petrol odor. At 20': Trace fine sand, fine gravel, petrol odor.
- 25 - - 2 - 			13 4.1		cl		CLAY; gray, saturated, medium dense, petrol odor.
- 30							TOTAL DEPTH OF BORING IS 28.0 FEET

DRILLING CO. : Cascade

DRILLING METHOD : DPT/Hand Auger

SAMPLING METHOD : PROJECT : AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A5
DATE	7-18-13	APPROVED BY	DRAWING NO. : 14932/-A5



O DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	SOSO	PROFILE	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
			3.9	Cement/	sp		SAND; brown, dry, loose, medium to fine grained, trace organics. At 1.0': Moist, medium grained, trace fine grained, sand and silt.
			2.2 3.1	Bentonite Grout 2" Dia. PVC Casing	sm		SILTY SAND; brown, moist, loose, trace organics, fine gravel.
 	1435		4.2 2.1	Bentonite Seal—	5		9.0
- 10 - 	1433				cl		CLAY; brown, moist, medium dense.
 	1445		5.1	Silica Sand—	sm		SANDY SILT; brown, moist, medium dense.
- 15 - 	1443			0.010" Slots — □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	sp		16.0 SAND; brown to gray, saturated, medium dense, fine grained, little silt, trace medium sand and coarse to medium gravel, petrol odor.
20 -			694 42 5.1		cl		19.0 SILTY CLAY; gray, saturated, medium dense, petrol odor.
- 25			5.2		sp		23.0 SAND; gray, saturated, medium dense, medium grained, trace fine grained sand and coarse to medium gravel, petrol odor.
- 30				Participation of the Control of the			TOTAL DEPTH OF BORING IS 28.0 FEET

DRILLING CO. : Cascade

DRILLING METHOD : DPT/Hand Auger

SAMPLING METHOD: PROJECT: AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO. : 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A6
DATE	7-18-13	APPROVED BY	DRAWING NO. : 149327-A6



O DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	BORING NO. SB-3 COORDINATES: N. E. FIELD GEOLOGIST S.B.Kennedy CHECKED BY J. Pickard APPROVED BY SURFACE ELEV. TOTAL DEPTH 28.0' DESCRIPTION
			1.0		sp		SAND; light brown, dry, loose, medium to fine grained, At 2.0': Brown, trace silt and organics. 3.5
- 5 -			1.6		sm		SILTY SAND; brown, moist, loose.
 	1520		4.1		sm		SANDY SILT; brown, moist, loose.
- 10			3.4	T-10 0'	ml		SILT; brown, moist, medium dense, trace fine sand. At 11.0': Blackish brown, trace fine gravel and organics (peat). At 12.0': Brown to gray.
- 20			3.2	<u>호</u> 16.0'	sc		SILTY CLAY; brown to gray, wet, dense, petrol odor.
- 25			5.6 143		sp	2222	SAND; gray, saturated, loose, medium to fine grained, trace coarse gravel, petrol odor. At 23.0': Medium dense, trace silt and medium to fine gravel, petrol odor.
- 30							TOTAL DEPTH OF BORING IS 28.0 FEET

DRILLING CO. : Cascade

DRILLING METHOD : DPT/Hand Auger

SAMPLING METHOD : PROJECT : AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A7
DATE	7-18-13	APPROVED BY	DRAWING NO. : 149327-A7



TO DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	($\begin{array}{c ccccccccccccccccccccccccccccccccccc$
<u> </u>	1		1.8		fill		ा	SAND; brown, dry, loose, medium to fine grained, trace silt and coarse to
├ -	-				sp			medium gravel. 2.0
			2.1	Cement/ Bentonite Grout	ml			SILT; brown, dry, medium dense.
- 5 -			4.2	2" Dia. PVC Casing	sm			SILTY SAND; brown, dry, loose, trace organic.
	1015		4.3					7.0
	1		3.8 2.4	Bentonite Seal				SILT; brown, moist, loose, medium dense.
 - 15 -	1030		7.2	Silica Sand————————————————————————————————————	ml			
F =	1			10.0		Ш	ill	At 16.0': Brownish black, wet, trace organics (peat).
 	1		416		cl		3	CLAY; gray, medium dense, saturated, petrol odor.
<u> </u>	1		1,162					SILTY CLAY; dark gray, saturated, medium dense, petrol odor.
- 20 - - 20 - 			440		sc			SAND; dark gray, saturated, medium dense, fine grained, trace silt, petrol
 					sp			odor.
25-			5.7					SANDY SILT: dark gray, saturated, medium dense, fine sand, trace silt, petrol odor.
 			7.1		sm			petrol odor.
F =			.,,,	15, 5, 5, 5, 5, 1				TOTAL DEPTH OF BORING IS 28.0 FEET
- 30								

DRILLING CO. : Cascade

DRILLING METHOD : DPT/Hand Auger

SAMPLING METHOD: PROJECT: AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A8
DATE	7_10_13	ADDROVED BY	DRAWING NO. : 149327-46



DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
0 =					fill	. 4.	Asphalt (~10").
‡ :	1		63				SAND; brown, dry, loose, fine grained, trace silt, coarse to fine gravel, slight petrol odor.
			395	Cement/ Bentonite Grout	sc		At 2.5': Trace medium sand and silt, medium to fine gravel, petrol odor.
F 5 -			496	2" Dia. PVC Casing			5.0 SANDY SILT; gray, moist, medium dense, petrol odor.
-			190 442	casing			
	1						
<u> </u>	1		244		sm		
<u> </u>	1545		420	Bentonite Seal			
F., =	1545		720				10.0
10 -							SILTY CLAY; gray, moist, medium dense, petrol odor.
	1		861		sc		
<u> </u>	1			Silica Sand—			
-	1						SILT; gray, moist, medium dense, petrol odor.
F =	1			2" Dia. PVC ==			
15-	1600		862	Screen w/ == 0.010" Slots — == 0.010"	ml		
<u> </u>	1			0.010 Siots			16.0
<u> </u>	1		1,088		sm		SANDY SILT; gray, saturated, medium dense, trace medium to fine gravel (petrol odor). 17.0
F -	1		1,000				SILTY SAND; gray, wet, medium dense, petrol odor.
	1						
-	1		863				
20-	1				sm		
	1				3111		
F =	1		450				
	1						
<u> </u>	1						24.0
L	-		9.8				SANDY SILT; gray, saturated, medium dense, petrol odor.
F ²⁵ -	-		3.0				
F :	1				sm		
<u> </u>	1						
			5.1				TOTAL DEPTH OF BORING IS 28.0 FEET
F =	-						
30	1						
† :	1						
<u>t</u> :	1						
F =]						
 	1						
L 35_						1	1

DRILLING CO. : Cascade

DRILLING METHOD : DPT/Hand Auger

SAMPLING METHOD : PROJECT : AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO. : 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A9
DATE	7-18-13	APPROVED BY	DIAWING NO. : 149327-A9



DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
°					fill	. 4.	Asphalt.
			17.5				SAND: brownish gray, dry, loose, fine grained, some silt, trace coarse to fine gravel.
				Cement/ Bentonite Grout	sp		At 2.0': Petrol odor.
<u> </u>			533	Bentonite Grout			3.5
Ŀ :			2.7				SILTY SAND; grayish brown, dry, medium dense.
5 -				2" Dia. PVC Casing			
F =	1450		3.1		sm		
F =							
			2				
				Bentonite Seal			9.0 SILTY CLAY; gray, moist, medium dense, slight petrol odor.
L 10 -			2.1				SELT SEAT, gray, moist, median dense, signit petrol duoi.
<u> </u>					sc		
<u> </u>			1.8				
F =				Silica Sand			13.0
F =							SILT; dark gray, moist, medium dense, slight petrol odor.
			4.8	2" Dia. PVC	ml		
- 15 -	1500			Screen w/ 0.010" Slots————————————————————————————————————			At 15.0': Dark brown, moist to wet, trace organics (peat), slight petrol odor.
<u> </u>			336	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□			SILTY SAND; gray, saturated, medium dense, petrol odor.
Ŀ :							
F -			380				
F =							
20-					sm		
			460				
<u> </u>							23.0
Ŀ :			458				SILTY CLAY; gray, saturated, medium dense, petrol odor.
					sc		
F ²³ -							26.0
F =							SILTY SAND: gray, saturated, medium dense, trace medium to fine gravel, petrol odor.
			7.3		sm		
			7.3	Productivity		1111111	TOTAL DEPTH OF BORING IS 28.0 FEET
<u> </u>							
30-							
<u> </u>							
- -							
F =							
L 75 -							

DRILLING CO. : Cascade

DRILLING METHOD : DPT/Hand Auger

SAMPLING METHOD: PROJECT: AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO. : 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A10
DATE	7-18-13	APPROVED BY	DIAWING NO 149327-A10



ET	lat.		9				BORING NO. S	5V1 coordinates: <u>N.</u>
DEPTH IN FEET	LE TIME	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	FIELD GEOLOGIST <u>S.B.Kennedy</u> CHECKED BY <u>J. Pickard</u>	Ł.
표	SAMPLE	REC	_i		ے ا	PR	CHECKED BY <u>J. Pickard</u>	_ DATE FINISHED <u>6-18-13</u>
DEF	N)		<u>a</u> .				APPROVED BY TOTAL DEPTH 5.0'	_ SURFACE ELEV CORF SIZE 2"
L							DESCRI	PTION
F ° -				Cement/	fill	, 4.	Asphalt.	10
t <u>-</u>	1		9.9	Bentonite Grout			SAND; brown, dry, loose, trace coarse	to medium gravel.
├ -					sc			2.5
t :	1		4.0		sm		SANDY SILT; brown, dry, medium dense	2.5 3.0
<u>-</u>				Bentonite Seal			SILTY SAND; brown, dry, loose.	
<u> </u>			2.8		sm			
- 0							TOTAL DEPTH OF BO	ORING IS 5.0 FEET
ΓΞ				Probe Tip 6"—/				
L :	1							
F -								
t :	1							
<u> </u>								
10 -	1							
ļ	1							
├ -								
Γ Ξ	1							
L -								
15-								
<u> </u>	1							
<u> </u>	1							
	1 1							
Γ Ξ	1							
L 20 -	1							
├ ॅॅ-								
L	1							
├ -								
Ι.	1							
- 25 -	1							
25-								
F =								
t :	1							
├ -								
ļ								
-								
F ₃₀ -								
Ŀ -								
- 30								
<u> </u>								
├ -								
ļ :								
35-								
							<u> </u>	

DRILLING CO. : Cascade

DRILLING METHOD : Hand Auger

SAMPLING METHOD: PROJECT: AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A11
DATE	7 10 13	ADDDOVED BY	DRAWING NO. : 149327-ATT



_							BORING NO. SV2	
DEPTH IN FEET	TIME	.R≺	P.I.D. READING		,,	Ш	COORDINATES: <u>N.</u> <u>E.</u>	
Z ⊤	SAMPLE	RECOVERY	. RE/	DRILLING REMARKS	nscs	PROFILE	FIELD GEOLOGIST S.B.Kennedy DATE BEGAN 6-18-13 CHECKED BY J. Pickard DATE FINISHED 6-18-13	_
EPT	SAM	RE	.i.D.			ď	APPROVED BY SURFACE ELEV. TOTAL DEPTH 5.0' CORE SIZE 2"	_
			"				TOTAL DEPTH 5.0' CORE SIZE 2"	_
				Cement/	fill	4.	DESCRIPTION Asphalt.	10
			10.6	Bentonite Grout	sp		SAND; brown, dry, loose, fine grained, little medium, trace coarse to medium gravel.	10
			0.9	Bentonite Seal—	sm		At 2.5': Red brick. SILTY SAND; brown, dry, medium dense, trace fine gravel and organics.	3.5
			0.9		sp	111111111	SAND; light brown, dry, loose, fine grained, little silt, trace organics.	_ 5.5
- 10			0.9	Probe Tip 6"	sp		TOTAL DEPTH OF BORING IS 5.0 FEET	

DRILLING CO. : Cascade

DRILLING METHOD : Hand Auger

SAMPLING METHOD: PROJECT: AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A12
DATE	7 10 13	ADDDOVED BY	DRAWING NO. : 149327-A12



O DEPTH IN FEET	SAMPLE TIME	RECOVERY	P.I.D. READING 0.7	DRILLING REMARKS Cement/ Bentonite Grout— Bentonite Seal—	SOSD fill sp	PROFILE	BORING NO. SV3 COORDINATES: N. E. FIELD GEOLOGIST S.B.Kennedy CHECKED BY J. Pickard APPROVED BY TOTAL DEPTH 5.0' DESCRIPTION Asphalt. SAND; brown, dry, loose, fine grained, little medium sand, trace silt and medium to fine gravel (red brick fragments). SANDY SILT; brown, dry, medium dense, trace fine gravel.
- 10				Probe Tip 6"			TOTAL DEPTH OF BORING IS 5.0 FEET

DRILLING CO. : Cascade

DRILLING METHOD : Hand Auger

SAMPLING METHOD: PROJECT: AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY	DRAWING NO. : 149327-A13
DATE	7-18-13	APPROVED BY	DRAWING NO. : 149327-A13



_							BORING NO. SV4	
DEPTH IN FEET	TIME	>	NG				COORDINATES: N.	_
Ĭ Z	<u> </u>	RECOVERY	P.I.D. READING	DRILLING REMARKS	nscs	PROFILE	E. FIELD GEOLOGIST S.B.Kennedy DATE BEGAN 6-19-13	-
E	SAMPLE	ECO	R		SN	280	FIELD GEOLOGIST <u>S.B.Kennedy</u> DATE BEGAN <u>6-19-13</u>	_
EP.	SAI	œ	P.I.			"	APPROVED BY SURFACE ELEV TOTAL DEPTH 5.0' CORE SIZE2"	_
							TOTAL DEPTH 5.0 CORE SIZE 2"	-
- 0 -				Cement/	fill	, s. A.	DESCRIPTION Asphalt.	_
]		1.2	Bentonite Grout			SAND; brown, dry, loose, fine grained, trace silt and coarse to fine grave	10' el.
	1							
F =]						At 2.0': Some silt, trace red brick fragments and concrete and/or terracotta fragments.	
-	1		0.4	Bentonite Seal—	sp			
F =]							
- _	1		0.5				At 4.5': Rebal/metal.	
5 -							TOTAL DEPTH OF BORING IS 5.0 FEET	
-				Probe Tip 6"				
[]								
-								
10-	1							
1								
	1							
-								
 	1							
 	1							
	1							
-15-	1							
	1							
	1							
	1							
Ι.	1							
-	1							
20-	1							
	1							
Ι.	1							
	1							
25-	1							
- -								
t :	1							
<u> </u>								
-								
<u> </u>								
30 -								
<u> </u>								
<u> </u>								
- -								
<u> </u>								
- -								
- 35 -	$\overline{}$			l			<u>I</u>	

DRILLING CO. : Cascade

DRILLING METHOD : Hand Auger

SAMPLING METHOD : PROJECT : AT&T San Jose

LOCATION: 95 S. Almaden Ave., San Jose

PROJECT NO.: 149327

DRAWN BY	SCHAEFFER	CHECKED BY		DRAWING NO. : 149327-A14
DATE	7_10_13	ADDDOVED BY	·	DIVAMING NO 14932/-A14



APPENDIX D PHOTOGRAPHIC LOG

Photographic Documentation

Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 1

Direction:

SW

Description:

Almaden Boulevard utility locations near SB4/MW11.



Photograph No. 2

Direction:

W

Description:

Almaden Boulevard utility locations near SB2/MW10 and SB3.





Photographic Documentation

Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc. **Photograph Date:** June 2013

Project No: 149327

Photograph No. 3

Direction:

NE

Description:

Almaden Blvd near corner of Post Street, utility locations.



Photograph No. 4

Direction:

Ν

Description:

Almaden Blvd near Post Street, utility locations.





Photographic Documentation

Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 5

Direction:

SE

Description:

Almaden Blvd fiber optic vault in sidewalk; in line with shed at facility.



Photograph No. 6

Direction:

S

Description:

Almaden Blvd utility locations; numerous fiber optic lines.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 7

Direction:

SSE

Description:

Almaden Blvd utility locations; numerous fiber optic lines.




Photograph No. 8

Direction:

Ε

Description:

Utility locations near cross walk on W San Fernando. Approximate area of several SB7 installation attempts, encountered concrete refusal approximately 9 and 13 inches bsg.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 9

Direction:

ESE

Description:

Utility locations near cross walk on W San Fernando on west bound side of road. Approximate area of several SB7 installation attempts, encountered concrete refusal approximately 9 and 13 inches bsg. Note traffic sensors in center of road and electric and fiber optic lines.




Photograph No. 10

Direction:

ESE

Description:

Traffic sensor locations near cross walk on W. San Fernando.



Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 11

Direction:

Е

Description:

Utility locations on W San Fernando in right turn lane near cross walk on west bound side of road; note 12V electric lines and fiber optics.



Photograph No. 12

Direction:

9

Description:

Utility locations near cross walk and right turn lane on W San Fernando, and SB7 installation attempts that encountered concrete refusal at 9 inches.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 13

Direction:

S

Description:

Utility locations near crosswalk in bike lane on W San Fernando on west bound side of road; note traffic sensor and fiber optic line.



Photograph No. 14

Direction:

9

Description:

Utility locations near crosswalk on W San Fernando at Almaden Blvd; note traffic sensor, fiber optic line, and electric.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 15

Direction:

W

Description:

Utility locations near W San Fernando and Almaden Blvd intersection; note electric and fiber optic line partially marked out.



Photograph No. 16

Direction:

SSW

Description:

Utility locations partially marked out at W San Fernando and Almaden Blvd; note electric and fiber optics partially marked out and manhole covers in intersection.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 17

Direction:

NNE

Description:

Utility locations in sidewalk and street near release location on W San Fernando.




Photograph No. 18

Direction:

Ε

Description:

Utility locations in sidewalk/right turn lane on W San Fernando, near several large subsurface utility vaults near release area.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 19

Direction:

S

Description:

Utility locations in center of W San Fernando on west bound side of road; note electric, fiber optic, storm lines



Photograph No. 20

Direction:

W

Description:

Utility locations near release area and several large utility vaults.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 21

Direction:

S

Description:

Utility locations on W San Fernando from sidewalk to center of road on west bound side.



Photograph No. 22

Direction:

9

Description:

Utility locations on W San Fernando from sidewalk to center of road on west bound side.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 23

Direction:

S

Description:

Utility locations on W San Fernando partially marked out; note electric, fiber optic, storm, and some unknown utility lines identified.




Photograph No. 24

Direction:

ΝE

Description:

Utility locations only partially marked out on W San Fernando from sidewalk to center of road on east bound side.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc.

Photograph Date: June 2013

Project No: 149327

Photograph No. 25

Direction:

Ν

Description:

Utility locations partially marked out on W San Fernando from sidewalk to center of road on west bound side; note fiber optic lines do not follow a straight path.



Photograph No. 26

Direction:

Ν

Description:

Utility locations partially marked out on W San Fernando from sidewalk to center of road on west bound side; note fiber optic and electric lines partially identified.





Client: AT&T

Location: 95 S Almaden Avenue, San Jose, CA

Prepared by: Shaw Environmental & Infrastructure, Inc. **Photograph Date:** June 2013

Project No: 149327

Photograph No. 27

Direction:

Description:

Concrete refusals on W San Fernando between 9 and 13 inches below grade; attempted 6 locations.





APPENDIX E

LABORATORY ANALTYICAL REPORTS AND CHAIN-OF-CUSTODY DOCUMENTS



(612)607-1700



July 16, 2013

Rob Delnagro Shaw Environmental 4005 Port Chicago Hwy Concord, CA 94520

RE: Project: ATT San Jose - 95 S. Almaden

Pace Project No.: 10234206

Dear Rob Delnagro:

Enclosed are the analytical results for sample(s) received by the laboratory on June 21, 2013. The results relate only to the samples included in this report. Results reported herein conform to the most current TNI standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

Some analyses have been subcontracted outside of the Pace Network. The subcontracted laboratory report has been attached.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Jennifer Gross

jennifer.gross@pacelabs.com Project Manager

ENNI (-POSS

Enclosures

cc: Sheila Richgels, Shaw Environmental





Minneapolis, MN 55414 (612)607-1700

SAMPLE SUMMARY

Project: ATT San Jose - 95 S. Almaden

Pace Project No.: 10234206

Lab ID	Sample ID	Matrix	Date Collected	Date Received	
10234206001	Subbed to Kiff	Water	06/17/13 13:20	06/21/13 17:50	

REPORT OF LABORATORY ANALYSIS



Date: 07/15/2013

Laboratory Results

Jenni Gross Pace Analytical Services, Inc. 940 South Harney Street Seattle, WA 98108

Subject: 12 Soil Samples
Project Name: ATT San Jose
Project Number: 149327

P.O. Number: N1011/WOTS13CB1010T2

Dear Ms. Gross,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed. Testing procedures comply with the 2003 NELAC and TNI 2009 standards. Laboratory results relate only to the samples tested. This report may be freely reproduced in full, but may only be reproduced in part with the express permission of Kiff Analytical, LLC. Kiff Analytical, LLC is certified by the State of California under the National Environmental Laboratory Accreditation Program (NELAP), lab # 08263CA. If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,

Troy Turpen

Troy D. Turpen



Date: 07/15/2013

Subject: 12 Soil Samples Project Name: ATT San Jose

Project Number: 149327

P.O. Number: N1011/WOTS13CB1010T2

Case Narrative

A version of this report was previously issued on 06/28/2013. This revised version replaces that report. Results for Benzene, Toluene, Ethylbenzene, Total Xylenes, and Naphthalene by method EPA 8260B have been added to samples SB1-7'-(06-17), SB1-14' (06-17), SB2-9' (06-17), SB2-15' (06-17), SB3-8' (06-17), SB3-14' (06-17), SB4-6' (06-18), SB4-15' (06-18), SB5-9' (06-19), and SB5-15' (06-19). Results for TPH as Gasoline and Naphthalene by method EPA 8260B have been added to samples SB6-6' (06-19) and SB6-15' (06-19).

All soil samples were reported on a total weight (wet weight) basis.

Matrix Spike/Matrix Spike Duplicate results associated with sample SB4-15' (06-18) for the analytes Naphthalene and Toluene were outside of control limits. This may indicate a bias for the sample that was spiked. Since the LCS recoveries were within control limits, no data are flagged.

Surrogate Recovery for sample SB5-9' (06-19) for test method Mod. EPA 8015 was outside of control limits. This may indicate a bias in the analysis due to the sample's matrix or an interference from compounds present in the sample.



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample: SB1-7'-(06-17) Matrix : Soil Lab Number: 85220-01

Sample Date .00/17/2013	Measured	Method Reporting	11.50	Analysis	Date/Time
Parameter	Value	Limit	Units	Method	Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 00:51
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 00:51
4-Bromofluorobenzene (Surr)	104		% Recovery	EPA 8260B	06/26/13 00:51
1,2-Dichloroethane-d4 (Surr)	104		% Recovery	EPA 8260B	06/26/13 00:51
Toluene - d8 (Surr)	98.0		% Recovery	EPA 8260B	06/26/13 00:51
TPH as Diesel (Note: Hydrocarbons are higher-boiling	1.8 than typical Diese	1.0 el Fuel.)	mg/Kg	M EPA 8015	06/27/13 16:37
Octacosane (Diesel Surrogate)	89.2		% Recovery	M EPA 8015	06/27/13 16:37



Date: 07/15/2013

Project Name : ATT San Jose

Project Number: 149327

Sample : **SB1-14' (06-17)** Matrix : Soil Lab Number : 85220-02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 01:26
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 01:26
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	06/26/13 01:26
1,2-Dichloroethane-d4 (Surr)	99.4		% Recovery	EPA 8260B	06/26/13 01:26
Toluene - d8 (Surr)	97.8		% Recovery	EPA 8260B	06/26/13 01:26
TPH as Diesel	< 1.0	1.0	mg/Kg	M EPA 8015	06/27/13 18:13
Octacosane (Diesel Surrogate)	85.1		% Recovery	M EPA 8015	06/27/13 18:13



Date: 07/15/2013

Project Name : ATT San Jose

Project Number: 149327

Sample : **SB2-9' (06-17)** Matrix : Soil Lab Number : 85220-03

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Toluene	< 0.0050	0.0050		EPA 8260B	06/26/13 02:02
			mg/Kg		
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 02:02
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:02
4-Bromofluorobenzene (Surr)	102		% Recovery	EPA 8260B	06/26/13 02:02
1,2-Dichloroethane-d4 (Surr)	106		% Recovery	EPA 8260B	06/26/13 02:02
Toluene - d8 (Surr)	97.5		% Recovery	EPA 8260B	06/26/13 02:02
TPH as Diesel	< 1.0	1.0	mg/Kg	M EPA 8015	06/27/13 18:42
Octacosane (Diesel Surrogate)	86.4		% Recovery	M EPA 8015	06/27/13 18:42



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample: **SB2-15' (06-17)** Matrix : Soil Lab Number: 85220-04

Sample Date :06/17/2013

Outilpic Date :00/17/2010		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 02:37
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 02:37
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	06/26/13 02:37
1,2-Dichloroethane-d4 (Surr)	101		% Recovery	EPA 8260B	06/26/13 02:37
Toluene - d8 (Surr)	97.6		% Recovery	EPA 8260B	06/26/13 02:37
TPH as Diesel (Note: Discrete peaks in Diesel range, aty	1.8 pical for Diesel	1.0 Fuel.)	mg/Kg	M EPA 8015	06/27/13 19:11
Octacosane (Diesel Surrogate)	94.4		% Recovery	M EPA 8015	06/27/13 19:11

Octacosane (Diesel Surrogate) % Recovery M EPA 8015 94.4



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample : **SB3-8' (06-17)** Matrix : Soil Lab Number : 85220-05

Sample Date .00/17/2013	Measured	Method Reporting	11.5	Analysis	Date/Time
Parameter	Value	Limit	Units	Method	Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 03:13
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:13
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	06/26/13 03:13
1,2-Dichloroethane-d4 (Surr)	107		% Recovery	EPA 8260B	06/26/13 03:13
Toluene - d8 (Surr)	97.8		% Recovery	EPA 8260B	06/26/13 03:13
TPH as Diesel	< 1.0	1.0	mg/Kg	M EPA 8015	06/27/13 19:40
Octacosane (Diesel Surrogate)	83.3		% Recovery	M EPA 8015	06/27/13 19:40



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample : **SB3-14' (06-17)** Matrix : Soil Lab Number : 85220-06

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 03:48
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 03:48
4-Bromofluorobenzene (Surr)	99.7		% Recovery	EPA 8260B	06/26/13 03:48
1,2-Dichloroethane-d4 (Surr)	101		% Recovery	EPA 8260B	06/26/13 03:48
Toluene - d8 (Surr)	98.2		% Recovery	EPA 8260B	06/26/13 03:48
TPH as Diesel	< 1.0	1.0	mg/Kg	M EPA 8015	06/27/13 20:09
Octacosane (Diesel Surrogate)	89.5		% Recovery	M EPA 8015	06/27/13 20:09



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample: SB4-6' (06-18) Matrix : Soil Lab Number: 85220-07

Sample Date :06/18/2013

Campio Bato 100/10/2010		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 04:23
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 04:23
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	06/26/13 04:23
1,2-Dichloroethane-d4 (Surr)	101		% Recovery	EPA 8260B	06/26/13 04:23
Toluene - d8 (Surr)	98.0		% Recovery	EPA 8260B	06/26/13 04:23
TPH as Diesel (Note: Discrete peaks in Diesel range, a	1.8 atypical for Diesel	1.0 Fuel.)	mg/Kg	M EPA 8015	06/27/13 20:38
Octacosane (Diesel Surrogate)	91.4		% Recovery	M EPA 8015	06/27/13 20:38

91.4 % Recovery M EPA 8015 06/27/13 20:38 Octacosane (Diesel Surrogate)



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample: **SB4-15' (06-18)** Matrix : Soil Lab Number: 85220-08

Sample Date .00/10/2013	Measured	Method Reporting		Analysis	Date/Time
Parameter	Value	Limit	Units	Method	Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/27/13 01:06
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/27/13 01:06
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	06/27/13 01:06
1,2-Dichloroethane-d4 (Surr)	102		% Recovery	EPA 8260B	06/27/13 01:06
Toluene - d8 (Surr)	91.1		% Recovery	EPA 8260B	06/27/13 01:06
TPH as Diesel (Note: Discrete peaks in Diesel range, at	2.4 ypical for Diesel	1.0 Fuel.)	mg/Kg	M EPA 8015	06/27/13 21:08
Octacosane (Diesel Surrogate)	90.0		% Recovery	M EPA 8015	06/27/13 21:08



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample: SB5-9' (06-19) Matrix : Soil Lab Number: 85220-09

Sample Date :06/19/2013

Sample Date .00/19/2013	Manageman	Method		A a a b sa i a	Data/Times
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.025	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Toluene	0.027	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Ethylbenzene	0.084	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Total Xylenes	0.044	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Methyl-t-butyl ether (MTBE)	< 0.025	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Diisopropyl ether (DIPE)	< 0.025	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Ethyl-t-butyl ether (ETBE)	< 0.025	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Tert-amyl methyl ether (TAME)	< 0.025	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
Tert-Butanol	< 0.15	0.15	mg/Kg	EPA 8260B	06/26/13 11:46
TPH as Gasoline	210	2.5	mg/Kg	EPA 8260B	06/26/13 11:46
Naphthalene	0.47	0.025	mg/Kg	EPA 8260B	06/26/13 11:46
4-Bromofluorobenzene (Surr)	97.2		% Recovery	EPA 8260B	06/26/13 11:46
1,2-Dichloroethane-d4 (Surr)	91.7		% Recovery	EPA 8260B	06/26/13 11:46
Toluene - d8 (Surr)	98.6		% Recovery	EPA 8260B	06/26/13 11:46
2-Bromochlorobenzene (Surr)	87.9		% Recovery	EPA 8260B	06/26/13 11:46
TPH as Diesel (Note: Some hydrocarbons lower-boiling	800 I, some higher-bo	10 piling than Did	mg/Kg esel.)	M EPA 8015	06/27/13 22:35
Octacosane (Diesel Surrogate)	173		% Recovery	M EPA 8015	06/27/13 22:35

% Recovery M EPA 8015 Octacosane (Diesel Surrogate)



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample : **SB5-15' (06-19)** Matrix : Soil Lab Number : 85220-10

Campic Date :00/19/2010		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.25	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Toluene	< 0.25	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Ethylbenzene	6.0	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Total Xylenes	18	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Methyl-t-butyl ether (MTBE)	< 0.25	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Diisopropyl ether (DIPE)	< 0.25	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Ethyl-t-butyl ether (ETBE)	< 0.25	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Tert-amyl methyl ether (TAME)	< 0.25	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
Tert-Butanol	< 1.5	1.5	mg/Kg	EPA 8260B	06/26/13 12:21
TPH as Gasoline	3400	50	mg/Kg	EPA 8260B	06/27/13 13:52
Naphthalene	15	0.25	mg/Kg	EPA 8260B	06/26/13 12:21
4-Bromofluorobenzene (Surr)	98.1		% Recovery	EPA 8260B	06/26/13 12:21
1,2-Dichloroethane-d4 (Surr)	92.4		% Recovery	EPA 8260B	06/26/13 12:21
Toluene - d8 (Surr)	97.0		% Recovery	EPA 8260B	06/26/13 12:21
2-Bromochlorobenzene (Surr)	91.0		% Recovery	EPA 8260B	06/26/13 12:21
TPH as Diesel	1300	10	mg/Kg	M EPA 8015	06/27/13 23:34
(Note: Hydrocarbons are lower-boiling t	han typical Diese	l Fuel.)			
Octacosane (Diesel Surrogate)	82.1		% Recovery	M EPA 8015	06/27/13 23:34



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample: SB6-6' (06-19) Matrix : Soil Lab Number: 85220-11

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 10:36
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 10:36
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	06/26/13 10:36
1,2-Dichloroethane-d4 (Surr)	101		% Recovery	EPA 8260B	06/26/13 10:36
Toluene - d8 (Surr)	97.7		% Recovery	EPA 8260B	06/26/13 10:36
TPH as Diesel (Note: Hydrocarbons are higher-boiling th	8.1 an typical Diese	1.0 Il Fuel.)	mg/Kg	M EPA 8015	06/27/13 15:10
Octacosane (Diesel Surrogate)	86.8		% Recovery	M EPA 8015	06/27/13 15:10



Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Sample : **SB6-15' (06-19)** Matrix : Soil Lab Number : 85220-12

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/13 11:11
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/13 11:11
4-Bromofluorobenzene (Surr)	103		% Recovery	EPA 8260B	06/26/13 11:11
1,2-Dichloroethane-d4 (Surr)	98.4		% Recovery	EPA 8260B	06/26/13 11:11
Toluene - d8 (Surr)	98.0		% Recovery	EPA 8260B	06/26/13 11:11
TPH as Diesel	1.5	1.0	mg/Kg	M EPA 8015	06/27/13 22:06
Octacosane (Diesel Surrogate)	90.7		% Recovery	M EPA 8015	06/27/13 22:06

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

QC Report : Method Blank Data

Project Name: ATT San Jose

Project Number: 149327

Date Analyzed

Analysis Method

Units

Method Reporting Limit U

Report Number: 85220

Date: 07/15/2013

		Method					2
Parameter	Measured Value	Reporting Limit	g Units	Analysis Method	Date Analyzed	Parameter	Measured Value
TPH as Diesel	< 1.0	1.0	mg/Kg	M EPA 8015	06/27/2013		
Octacosane (Diesel Surrogate)	74.1		%	M EPA 8015	06/27/2013		
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/25/2013		
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/25/2013		
1,2-Dichloroethane-d4 (Surr)	91.0		%	EPA 8260B	06/25/2013		
4-Bromofluorobenzene (Surr)	104		%	EPA 8260B	06/25/2013		
Toluene - d8 (Surr)	97.8		%	EPA 8260B	06/25/2013		
Benzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Ethylbenzene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Toluene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Total Xylenes	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Diisopropyl ether (DIPE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Ethyl-t-butyl ether (ETBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Methyl-t-butyl ether (MTBE)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Tert-Butanol	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
Tert-amyl methyl ether (TAME)	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
TPH as Gasoline	< 1.0	1.0	mg/Kg	EPA 8260B	06/26/2013		
Naphthalene	< 0.0050	0.0050	mg/Kg	EPA 8260B	06/26/2013		
1,2-Dichloroethane-d4 (Surr)	92.0		%	EPA 8260B	06/26/2013		
4-Bromofluorobenzene (Surr)	101		%	EPA 8260B	06/26/2013		
Tolnene - d8 (Surr)	91.2		%	EPA 8260B	06/26/2013		

QC Report: Matrix Spike/ Matrix Spike Duplicate

Report Number: 85220

Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	J Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample F Percent F Recov. C	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
TPH as Diesel														
	85220-01	9.	19.7	19.7	20.6	22.0	mg/Kg N	M EPA 8015	6/27/13	95.7	103	7.07	60-140	25
Diisopropyl ether	er													
	85214-02	<0.0050 0.0390	0.0390	0.0388	0.0353	0.0359	mg/Kg E	EPA 8260B	6/25/13	90.5	92.8	2.49	70.0-130	25
Ethyl-tert-butyl ether	ether													
	85214-02	<0.0050	0.0398	0.0396	0.0377	0.0384	mg/Kg E	EPA 8260B	6/25/13	94.6	97.1	2.54	65.0-130	25
Methyl-t-butyl ether	ether													
	85214-02	<0.0050	0.0396	0.0393	0.0359	0.0378	mg/Kg E	EPA 8260B	6/25/13	8.06	96.2	5.81	60.0-130	25
Tert-Butanol														
	85214-02	0.0069	0.200	0.199	0.186	0.181	mg/Kg E	EPA 8260B	6/25/13	89.7	9.78	2.33	70.0-130	25
Tert-amyl-methyl ether	yl ether													
	85214-02	<0.0050	0.0400	0.0398	0.0381	0.0387	mg/Kg E	EPA 8260B	6/25/13	95.2	97.4	2.32	70.0-130	25
Diisopropyl ether	er													
	85214-01	<0.0050	0.0387	0.0393	0.0307	0.0306	mg/Kg	EPA 8260B	6/26/13	79.4	77.8	2.02	70.0-130	25
Ethyl-tert-butyl ether	ether													
	85214-01	<0.0050	0.0395	0.0401	0.0338	0.0323	mg/Kg E	EPA 8260B	6/26/13	85.5	80.5	96.3	65.0-130	25
Methyl-t-butyl ether	ether													
	85214-01	<0.0050	0.0392	0.0399	0.0362	0.0326	mg/Kg E	EPA 8260B	6/26/13	92.2	81.8	11.9	60.0-130	25

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

QC Report : Matrix Spike/ Matrix Spike Duplicate

Report Number: 85220

Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	d Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
Tert-Butanol	05244.04	09000	0.408	202.0	0.465	0.163		a0908 Val	6/26/13	22.4	0 00	996	70.0.430	25
Tert-amyl-methyl ether	5		0.0	0.202	3	3	5 5 6 7 8	EL A 0200B	0/20/		6.00	7.00	0.07	67
	85214-01	<0.0050	0.0397	0.0403	0.0334	0.0322	mg/Kg	EPA 8260B	6/26/13	84.2	6.62	5.28	70.0-130	25
Benzene														
	85214-02	<0.0050	0.0397	0.0394	0.0346	0.0348	mg/Kg	EPA 8260B	6/25/13	87.2	88.3	1.25	70.0-130	25
Ethylbenzene														
	85214-02	<0.0050	0.0397	0.0394	0.0357	0.0356	mg/Kg	EPA 8260B	6/25/13	0.06	90.2	0.212	70.0-130	25
Naphthalene														
	85214-02	<0.0050	0.0397	0.0394	0.0372	0.0398	mg/Kg	EPA 8260B	6/25/13	93.8	101	7.27	70.0-130	25
P + M Xylene														
	85214-02	<0.0050	0.0397	0.0394	0.0366	0.0364	mg/Kg	EPA 8260B	6/25/13	92.1	92.3	0.126	70.0-130	25
Toluene														
	85214-02	<0.0050	0.0397	0.0394	0.0352	0.0355	mg/Kg	EPA 8260B	6/25/13	88.7	90.0	1.39	70.0-130	25
Benzene														
	85214-01	<0.0050	0.0394	0.0400	0.0302	0.0303	ma/Ka	FPA 8260B	6/26/13	767	75.8	1 16	70 0-130	25
Ethylbenzene			-))) - 5 1)) - -)
	85214-01 <0.0050		0.0394	0.0400	0.0298	0.0302	mg/Kg	EPA 8260B	6/26/13	75.7	75.5	0.180	70.0-130	25

QC Report : Matrix Spike/ Matrix Spike Duplicate

Report Number: 85220

Date: 07/15/2013

triv Snike Dunlicate

Project Name: ATT San Jose

Project Number: 149327

Parameter	Spiked	Sample Spike	Spike evel	Spike Dup.	Spiked Sample	Duplicate Spiked Sample	ξ	Analysis Method	Spiked S Sample S Date Percent P Analyzed Recort P	Spiked Sample Percent	Duplicate Spiked Sample Percent	Relative Percent	Duplicate Spiked Sample Sample Relative Percent the Percent Pe	Relative Percent Diff.
Naphthalene		2			5	5			201	:				
D + M XvIene	85214-01	<0.0050	0.0394	0.0400	0.0228	0.0226	mg/Kg	85214-01 <0.0050 0.0394 0.0400 0.0228 0.0226 mg/Kg EPA 8260B	6/26/13 57.9	67.9	56.4	2.61	70.0-130	25
	85214-01	85214-01 <0.0050 0.0394 0.0400	0.0394	0.0400	0.0310	0.0313	mg/Kg	mg/Kg EPA 8260B	6/26/13 78.9	78.9	78.2	0.934	70.0-130	25
Toluene														
	85214-01	85214-01 <0.0050 0.0394 0.0400 0.0263 0.0273	0.0394	0.0400	0.0263	0.0273	mg/Kg	mg/Kg EPA 8260B	6/26/13 66.8	8.99	68.2	2.20	70.0-130	25

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

QC Report : Laboratory Control Sample (LCS)

Report Number: 85220

Date: 07/15/2013

Project Name: ATT San Jose

Project Number: 149327

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
TPH as Diesel	20.0	mg/Kg	M EPA 8015	6/27/13	85.8	70-130
Diisopropyl ether	0.0385	mg/Kg	EPA 8260B	6/25/13	95.4	70.0-130
Ethyl-tert-butyl ether	0.0393	mg/Kg	EPA 8260B	6/25/13	8.66	65.0-130
Methyl-t-butyl ether	0.0391	mg/Kg	EPA 8260B	6/25/13	7.76	60.0-130
Tert-Butanol	0.198	mg/Kg	EPA 8260B	6/25/13	92.3	70.0-130
Tert-amyl-methyl ether	0.0396	mg/Kg	EPA 8260B	6/25/13	101	70.0-130
Benzene	0.0392	mg/Kg	EPA 8260B	6/25/13	8.06	70.0-130
Ethylbenzene	0.0392	mg/Kg	EPA 8260B	6/25/13	93.0	70.0-130
Naphthalene	0.0392	mg/Kg	EPA 8260B	6/25/13	95.2	70.0-130
P + M Xylene	0.0392	mg/Kg	EPA 8260B	6/25/13	92.0	70.0-130
Toluene	0.0392	mg/Kg	EPA 8260B	6/25/13	93.1	70.0-130
Diisopropyl ether	0.0392	mg/Kg	EPA 8260B	6/26/13	83.4	70.0-130
Ethyl-tert-butyl ether	0.0400	mg/Kg	EPA 8260B	6/26/13	87.0	65.0-130
Methyl-t-butyl ether	0.0398	mg/Kg	EPA 8260B	6/26/13	94.6	60.0-130
Tert-Butanol	0.201	mg/Kg	EPA 8260B	6/26/13	88.7	70.0-130
Tert-amyl-methyl ether	0.0403	mg/Kg	EPA 8260B	6/26/13	89.1	70.0-130
Benzene	0.0399	mg/Kg	EPA 8260B	6/26/13	81.2	70.0-130
Ethylbenzene	0.0399	mg/Kg	EPA 8260B	6/26/13	9.88	70.0-130
Naphthalene	0.0399	mg/Kg	EPA 8260B	6/26/13	92.0	70.0-130
P + M Xylene	0.0399	mg/Kg	EPA 8260B	6/26/13	92.1	70.0-130

KIFF ANALYTICAL, LLC

Date: 07/15/2013

QC Report: Laboratory Control Sample (LCS)

Project Name: ATT San Jose

Project Number: 149327

					CS	LCS Percent
	Spike		Analysis	Date	Percent	Recov.
Parameter	Lèvel	Units	Method	Analyzed	Recov.	Limit
Toluene	0.0399	mg/Kg	EPA 8260B	6/26/13	79.2	70.0-130

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

9 69 ि g 3 B 8 6 Z ā For Lab Use Only □₹ 12 hr 2⁴ ₽ 24.7 ₽ ☐ § TAT Chain-of-Custody Record and Analysis Request Page MR Gasdine (CPA BOISM W.E.T. Lead (STLC) Total Lead (EPA 200.7 / 6010) CIRCLE METHOD Mercury (EPA 245.1 / 7470 / 7471) Analysis Request 5 Waste Oil Metals (Cd,Cr,Ni,Pb,Zn) (EPA 200.7 / 6010) CAM 17 Metals (EPA 200.7 / 6010) TPH as Motor Oil (EPA 8015M) -1800 time Reporting (M2108 A93) lesel (EPA 8015M) 02258 Volatile Organics (EPA 524.2 Drinking Water) Volatile Organics Full List (EPA 8260B) Volatile Halocarbons (EPA 8260B) -Bandard Lead Scav. (1,2 DCA & 1,2 EDB) (EPA 8260B) Cxygenates (5 oxy + EtOH, MeOH) (EPA 8260B) Remarks: Oxygenates (MTBE, DIPE, ETBE, TAME, TBA) (EPA 8260B) TPH Gas (EPA 8260B) BTEX (EPA 8260B) SRG # / Lab No. MTBE @ 0.5 ppb (EPA 8260B) EDF Deliverable To (Email Address). Rob Oclnago ηİΑ Matrix and Joseph, pickord @ C&1. COTA Billito: ≗ □ lio2 Water Direct Bill - Titan /ATI Preservative □ Yes 371 9uoN. > Shula B. Kennedy Sampling Company Log Code EONH Received by Received by HCI California EDF Report? Sampler Print Name: Sampler Signature: Tedlar Container Class Time S S \$ me Poly 450 Global ID 2795 2nd Street, Suite 300 Sleeve S11130 AOV Im 04 Cholis Davis, CA 95618 Lab: 530.297.4800 530,297,4802 1030 3454 4330 80 4015 **€**2€ 至 <u>ج</u> P.O. #. NiOII/W.G. [SI3CB] Date Sampling Company Address: 40574 Date **6/1**9 5. 2/18 Fax: Project Contact (Hardcopy or PDF To): GOOS fort Chicago Harry 4-80 (81-90) (20-19) ATT San Jose 61-90 8 tribution: White - Lab; Pink - Originator (06617) Project Address: 95 S. Almaden Are (06.17 (At-17) 06 B 6-90 Sample Designation 716.288 2103 Project #: (49 32 + Analytical LLC Sin any e 23 of 1805-91 Jr-485 585-15 Relinquished by: Phone Number Relinquished by: Project Name: , o - hus Fax Number: 1503-583--205

Page 2 of 2	is Request	TAT	12 hr		24 hr	\$ 49.	[v13.	⊐ [*]	3	7)									
85220	Chain-of-Custody Record and Analysis	Analysis Request	CIRCLE METHOD	SeoB)	8 A93) 03S8 A9 (8)	0828 A93 (Na) (Ma) (0108 \) (A93) (ns.c)	2, r 8 2, r 8 4 524 6 801 7 500 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	\$200.000 \$200.0000 \$200.000 \$200.000 \$200.000 \$200.000 \$200.000 \$200.000 \$200.0000 \$200.000 \$200.000 \$200.000 \$200.000 \$200.000 \$200.000 \$200.0000 \$200.000 \$200.0000 \$200.000 \$200.0000 \$200.000 \$200.000 \$200.00	othes (5) (2) (1,2 [7] (2) (1,2 [7] (2) (2) (2) (2) (2) (2) (2) (2) (2) (2)	Coxygent Cox	**		-					741	_	Standard 1A1	
SRG # / Lab No.	0N 🗌			800	T-14810/444		928 /	Matrix (EP)	0928 A9 8 A93)	Vater Jir Air MTBE @ 3TEX (EF			/				<u></u>	Remarks			I And find
300	California EDF Report?	Sampling Company Log Code:	Global ID:	EDF Deliverable To (Email Address):	1) 0 F + Bill	Sampler Print Name:		Container Preservative		youe HNO ³ HO ³ HCI Gellat Goly Sieeve	H H			/				Time Received by:	Time Received by:	1 1	12 of the
2795 2nd Street, Suite 300 Davis, CA 95618 Lab: 530.297.4800	0+.762.000	Carlos Con Sam	o Hasy		P.O. #. 75/3684 Bill to	Jose House		Sampling		2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -) is 1/4 . 4 . 5/4	5/19/11	3			/	/	Date (Tholin	Date		067(3
KIFF &	ntact (Hardcopy of	Company / Address:		725 225 105 Fax Number:	Project #.	3		ject Address:	10861 C		Col / Col. 19	151 (947)						Relinquished by:	Shula 15 tines	P 22	:\forage 24 co



SAMPLE RECEIPT CHECKLIST

Method of Receipt: □ Courier □ Over-the-counter Temp °C ઃ ઃ ·	No Comments: Shipping Custody Seals Coolant present Ares In Sample ID X X X X X X X X X X X X X X X X X X	No Water Intact	Temp Excursion ncies:
Yes Vime (2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	No	, _ ; , , , , , , , , , ,
A N N N N N N N N N N N N N N N N N N N	9 9	Suffe-12 har	
W W W	9 2	Sayle-12 har	
A A A	O Z	Sayle-12 has	
AN A	9	XNA	
NA N	o Z	XNA	
A N N N N N N N N N N N N N N N N N N N	9	M N/A	N
NA	0 2		
NA NA			
N/A			
N/A			
N/A			
Are preservatives acceptable?	S No		
Are samples within holding time?			
Are sample container types correct?			
Is there adequate sample volume?			
Receipt Details:			
Matrix Container Type # of Contain	ners		
Stown (2			
		CSI	CS Required:
Page] YES NO Init/Date:	



(612)607-1700



July 03, 2013

Rob Delnagro Shaw Environmental 4005 Port Chicago Hwy Concord, CA 94520

RE: Project: ATT San Jose - 95 S. Almaden

Pace Project No.: 10234247

Dear Rob Delnagro:

Enclosed are the analytical results for sample(s) received by the laboratory on June 25, 2013. The results relate only to the samples included in this report. Results reported herein conform to the most current TNI standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

Some analyses have been subcontracted outside of the Pace Network. The subcontracted laboratory report has been attached.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Jennifer Gross

jennifer.gross@pacelabs.com Project Manager

ENNI (-POSS

Enclosures

cc: Sheila Richgels, Shaw Environmental





Minneapolis, MN 55414 (612)607-1700



SAMPLE SUMMARY

Project: ATT San Jose - 95 S. Almaden

Pace Project No.: 10234247

Lab ID	Sample ID	Matrix	Date Collected	Date Received
10234247001	Subbed to Kiff	Water	06/21/13 14:45	06/25/13 11:03



Date: 07/01/2013

Laboratory Results

Jenni Gross Pace Analytical Services, Inc. 940 South Harney Street Seattle, WA 98108

Subject: 4 Water Samples

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

P.O. Number: N1011/W.O.TS13CBI 01

Dear Ms. Gross,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed. Testing procedures comply with the 2003 NELAC and TNI 2009 standards. Laboratory results relate only to the samples tested. This report may be freely reproduced in full, but may only be reproduced in part with the express permission of Kiff Analytical, LLC. Kiff Analytical, LLC is certified by the State of California under the National Environmental Laboratory Accreditation Program (NELAP), lab # 08263CA. If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,

Troy Turpen

Troy D. Turpen



Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Sample : **MW-11(06-21)** Matrix : Water Lab Number : 85237-01

Sample Date .00/21/2013		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Toluene	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	06/27/13 09:52
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	06/27/13 09:52
TPH as Gasoline	550	50	ug/L	EPA 8260B	06/27/13 09:52
1,2-Dichloroethane-d4 (Surr)	95.4		% Recovery	EPA 8260B	06/27/13 09:52
Toluene - d8 (Surr)	97.5		% Recovery	EPA 8260B	06/27/13 09:52
TPH as Diesel	3200	50	ug/L	M EPA 8015	06/28/13 09:51
Octacosane (Diesel Surrogate)	104		% Recovery	M EPA 8015	06/28/13 09:51



Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Sample: MW-12(06-21) Matrix: Water Lab Number: 85237-02

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	91	0.50	ug/L	EPA 8260B	06/28/13 01:42
Toluene	7.0	0.50	ug/L	EPA 8260B	06/28/13 01:42
Ethylbenzene	14	0.50	ug/L	EPA 8260B	06/28/13 01:42
Total Xylenes	27	0.50	ug/L	EPA 8260B	06/28/13 01:42
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 01:42
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 01:42
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 01:42
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 01:42
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	06/28/13 01:42
TPH as Gasoline	2400	50	ug/L	EPA 8260B	06/28/13 01:42
1,2-Dichloroethane-d4 (Surr)	97.7		% Recovery	EPA 8260B	06/28/13 01:42
Toluene - d8 (Surr)	97.7		% Recovery	EPA 8260B	06/28/13 01:42
TPH as Diesel	4700	50	ug/L	M EPA 8015	06/28/13 09:14
Octacosane (Diesel Surrogate)	104		% Recovery	M EPA 8015	06/28/13 09:14



Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Sample: MW-10(06-21) Matrix: Water Lab Number: 85237-03

Sample Date .00/21/2013		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Toluene	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:17
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	06/28/13 02:17
TPH as Gasoline	760	50	ug/L	EPA 8260B	06/28/13 02:17
1,2-Dichloroethane-d4 (Surr)	92.6		% Recovery	EPA 8260B	06/28/13 02:17
Toluene - d8 (Surr)	97.7		% Recovery	EPA 8260B	06/28/13 02:17
TPH as Diesel	2400	50	ug/L	M EPA 8015	06/28/13 09:48
Octacosane (Diesel Surrogate)	108		% Recovery	M EPA 8015	06/28/13 09:48



Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Sample: MW-13(06-21) Matrix: Water Lab Number: 85237-04

Sample Date :06/21/2013		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Toluene	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	06/28/13 02:52
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	06/28/13 02:52
TPH as Gasoline	290	50	ug/L	EPA 8260B	06/28/13 02:52
1,2-Dichloroethane-d4 (Surr)	96.2		% Recovery	EPA 8260B	06/28/13 02:52
Toluene - d8 (Surr)	98.8		% Recovery	EPA 8260B	06/28/13 02:52
TPH as Diesel	5300	50	ug/L	M EPA 8015	06/28/13 09:22
Octacosane (Diesel Surrogate)	88.7		% Recovery	M EPA 8015	06/28/13 09:22

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

QC Report : Method Blank Data

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Date Analyzed

Report Number: 85237 Date: 07/01/2013

Parameter	Measured	Method Reporting	og Units	Analysis Method	Date Analvzed	Parameter	Measured Value	Method Reporting Limit Units	Analysis Method
TPH as Diesel	< 50	50	ug/L	M EPA 8015	06/27/2013				
Octacosane (Diesel Surrogate)	87.5		%	M EPA 8015	06/27/2013				
Benzene	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Ethylbenzene	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Toluene	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Total Xylenes	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Diisopropyl ether (DIPE)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Tert-Butanol	< 5.0	5.0	ng/L	EPA 8260B	06/27/2013				
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
TPH as Gasoline	< 50	20	ng/L	EPA 8260B	06/27/2013				
1,2-Dichloroethane-d4 (Surr)	102		%	EPA 8260B	06/27/2013				
Toluene - d8 (Surr)	98.2		%	EPA 8260B	06/27/2013				
Benzene	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Ethylbenzene	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Toluene	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Total Xylenes	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Diisopropyl ether (DIPE)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
Tert-Butanol	< 5.0	2.0	ng/L	EPA 8260B	06/27/2013				
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ng/L	EPA 8260B	06/27/2013				
TPH as Gasoline	< 50	20	ng/L	EPA 8260B	06/27/2013				
1,2-Dichloroethane-d4 (Surr)	97.1		%	EPA 8260B	06/27/2013				
Toluene - d8 (Surr)	97.4		%	EPA 8260B	06/27/2013				

QC Report : Matrix Spike/ Matrix Spike Duplicate

Report Number: 85237 Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	e ed Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample I Percent I Recov. I	Relative Percent Diff.	Spiked Sample Percent Recov.	Relative Percent Diff. Limit
TPH as Diesel	BLANK	<50	1000	1000	1100	1110	ng/L	M EPA 8015	6/27/13	110	11	0.788	70-130	25
Benzene														
: : (85229-07	4.1	40.0	39.8	38.6	39.6	ng/L	EPA 8260B	6/27/13	93.1	92.8	2.86	70.0-130	25
Ullsopropyl etner	eL													
852 Ethyl-tert-butyl ether	85229-07 ether	<0.50	39.3	39.1	36.8	37.9	ng/L	EPA 8260B	6/27/13	93.8	6.96	3.28	70.0-130	25
	85229-07	<0.50	40.1	40.0	36.8	37.8	ng/L	EPA 8260B	6/27/13	91.7	94.6	3.14	70.0-130	25
Ethylbenzene							ı							
	85229-07	4.7	40.0	39.8	43.3	44.4	ng/L	EPA 8260B	6/27/13	96.5	8.66	3.35	70.0-130	25
Methyl-t-butyl ether	ther													
	85229-07	12	39.9	39.7	43.2	43.9	ng/L	EPA 8260B	6/27/13	79.2	81.3	2.59	70.0-130	25
P + M Xylene														
	85229-07	7.8	40.0	39.8	47.2	48.4	ng/L	EPA 8260B	6/27/13	98.6	102	3.36	70.0-130	25
Tert-Butanol														
	85229-07	860	202	201	1020	1030	ng/L	EPA 8260B	6/27/13	79.7	85.7	7.29	70.0-130	25
Tert-amyl-methyl ether	yl ether													
	85229-07	<0.50	40.3	40.2	36.5	37.2	ng/L	EPA 8260B	6/27/13	90.4	97.6	2.32	70.0-130	25

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

QC Report: Matrix Spike/ Matrix Spike Duplicate

Report Number: 85237 Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	d Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
Toluene	85229-07	0.54	40.0	39.8	38.6	39.6	ng/L	EPA 8260B	6/27/13	95.2	98.2	3.09	70.0-130	25
Benzene														
	85237-01	<0.50	40.0	40.0	39.2	39.0	ng/L	EPA 8260B	6/27/13	97.9	97.4	0.509	70.0-130	25
Diisopropyl ether	er													
	85237-01	<0.50	39.3	39.3	36.2	36.0	ng/L	EPA 8260B	6/27/13	92.0	91.5	0.579	70.0-130	25
Ethyl-tert-butyl ether	ether													
	85237-01	<0.50	40.1	40.1	39.3	39.6	ng/L	EPA 8260B	6/27/13	98.0	98.7	0.698	70.0-130	25
Ethylbenzene														
	85237-01	<0.50	40.0	40.0	41.4	41.3	ng/L	EPA 8260B	6/27/13	104	103	0.232	70.0-130	25
Methyl-t-butyl ether	ther													
	85237-01	<0.50	39.9	39.9	37.7	38.1	ng/L	EPA 8260B	6/27/13	94.6	95.5	0.982	70.0-130	25
P + M Xylene							ı							
	85237-01	<0.50	40.0	40.0	40.4	40.4	ng/L	EPA 8260B	6/27/13	101	101	0.192	70.0-130	25
Tert-Butanol														
	85237-01	<5.0	202	202	205	203	ng/L	EPA 8260B	6/27/13	102	101	0.700	70.0-130	25
Tert-amyl-methyl ether	yl ether													
	85237-01	<0.50	40.3	40.3	41.0	40.6	ng/L	EPA 8260B	6/27/13	102	101	0.913	70.0-130	25

2795 2nd Street, Suite 300 Davis, CA 95618 530-297-4800

QC Report : Matrix Spike/ Matrix Spike Duplicate

Report Number: 85237

Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

tive ent	
Relative Percent Diff. Limit	25
Spiked Sample /e Percent nt Recov. Limit	70.0-130
Relativ Percer Diff.	0.702
Duplicate Spiked Sample Percent Recov.	99.3
Spiked Sample Percent Recov.	100
Spiked Sample Sa	6/27/13
Analysis Method	EPA 8260B
d Units	ng/L
Duplicate Spiked Sample Value	39.7
Spiked Sample Value	40.0
Spike Dup. Level	40.0
Spike Level	40.0
Sample Value	<0.50
Spiked Sample	85237-01
Parameter	Toluene

QC Report: Laboratory Control Sample (LCS)

Report Number: 85237 Date: 07/01/2013

Project Name: AT&T S. Almaden, San Jose

Project Number: 149327

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
Benzene	40.0	ng/L	EPA 8260B	6/27/13	92.0	70.0-130
Diisopropyl ether	39.3	ng/L	EPA 8260B	6/27/13	92.8	70.0-130
Ethyl-tert-butyl ether	40.1	ng/L	EPA 8260B	6/27/13	93.1	70.0-130
Ethylbenzene	40.0	ng/L	EPA 8260B	6/27/13	0.96	70.0-130
Methyl-t-butyl ether	39.9	ng/L	EPA 8260B	6/27/13	86.0	70.0-130
P + M Xylene	40.0	ng/L	EPA 8260B	6/27/13	98.3	70.0-130
Tert-Butanol	202	ng/L	EPA 8260B	6/27/13	92.0	70.0-130
Tert-amyl-methyl ether	40.3	ng/L	EPA 8260B	6/27/13	2.06	70.0-130
Toluene	40.0	ng/L	EPA 8260B	6/27/13	94.5	70.0-130
Benzene	40.1	ng/L	EPA 8260B	6/27/13	2.96	70.0-130
Diisopropyl ether	39.4	ng/L	EPA 8260B	6/27/13	92.9	70.0-130
Ethyl-tert-butyl ether	40.2	ng/L	EPA 8260B	6/27/13	98.4	70.0-130
Ethylbenzene	40.1	ng/L	EPA 8260B	6/27/13	105	70.0-130
Methyl-t-butyl ether	40.0	ng/L	EPA 8260B	6/27/13	94.5	70.0-130
P + M Xylene	40.1	ng/L	EPA 8260B	6/27/13	102	70.0-130
TPH as Gasoline	503	ng/L	EPA 8260B	6/27/13	2.66	70.0-130
Tert-Butanol	202	ng/L	EPA 8260B	6/27/13	99.0	70.0-130
Tert-amyl-methyl ether	40.4	ng/L	EPA 8260B	6/27/13	101	70.0-130
Toluene	40.1	ng/L	EPA 8260B	6/27/13	9.66	70.0-130

KIFF ANALYTICAL, LLC

03 40 8 For Lab Use Only -6 voas per semple location (se-24 voas) 12 hr 24 hr □₹ ₽ □ \rightar{\pi}{\pi} □2hr TAT Chain-of-Custody Record and Analysis Request as governu (EPA BOLM HOLL W.E.T. Lead (STLC) Total Lead (EPA 200.7 / 6010) CIRCLE METHOD Tunamond Mercury (EPA 245.1 / 7470 / 7471) Analysis Request 5 Waste Oil Metals (Cd.Cr.Ni,Pb.Zn) (EPA 200.7 / 6010) CAM 17 Metals (EPA 200.7 / 6010) TPH as Motor Oil (EPA 8015M) Report TPH as Diesel (EPA 8015M) Volatile Organics (EPA 524.2 Drinking Water) Volatile Organics Full List (EPA 8260B) standord Volatile Halocarbons (EPA 8260B) Lostine Lead Scav. (1,2 DCA & 1,2 EDB) (EPA 8260B) Oxygenates (5 oxy + EtOH, MeOH) (EPA 8260B) Remarks: MTBE, DIPE, ETBE, TAME, TBA) (EPA 82608) 301/17/ H Gas (EPA 8260B) EX (EPA 8260B) SRG # / Lab No. EPA 8260B) ged 9 a @ EDF Deliverable To (Email Address): Rob. De Inag Matrix ٦iA 2 □ lioS Died billto Titan /ATT Water PACA ROSA +Joseph, Pickard @CB1. com □ Yes Received by Laboratory: AnoN Sampling Company Log Code ^{6}ONH / SC ime Received by: Received by: HCI Project Contact (Hardcopy or PDF To): Ref. Ochagh California EDF Report? Sampler Print Name Tedlar Sampler Signa 82513 1103 Class Time Poly Global ID. 2795 2nd Street, Suite 300 Sleeve AOV Im 04 120× Davis, CA 95618 Lab: 530.297.4800 530,297,4802 7200 15.00 75,75 Time NIOITH O. TSIXE Sampling ATAT S. Almado, Sa, Josc 22 なる び Date 17/9 2 Fax: P.O. #: Distribution: White - Lab; Pink - Originator Rev: 060409 2012. Sample Designation MW - 10 (05-21) M-13/06-21 MW-11 (06-21) MW-42 (06-21) Charlett Phone Number: 925, 288. Company / Address: Project #: 4**49327** Project Name: 4 60c Project Address: ed by: ished by: =ax Number: Relinquishe



SAMPLE RECEIPT CHECKLIST

	SRG#: 85237	37	TAT:	X Standard	p		Rush	Split		None				
0,	Sample Receipt Initials/Date:	Initials/Date:		TJB 062513	Store	ige Tin	Storage Time: //0/3	Sample Login		Initials/D	ate: WAP	Initials/Date: MAS/002513	513	
	Method of Receipt:	: Courier		Over-the-counter	unter	X	Shipped	Shipping Custody Seals	Sustody	Seals	N/A	⊠1ntact	☐ Broken	ken
	Temp °C [0.2	N/A The	Therm ID \mathcal{IR} - /		Time 1058	90	Coolant present		⊠Yes	° □	☐ Water		Temp Excursion	ursion
0	Chain-of-Custody:			Yes	Z	9	Documented on		CÓC	Labels		Discrepancies:	ncies:	
<u> </u>	Is COC present?			\times			Sample ID		×	X				
	Is COC signed by relinquisher?	elinquisher?		X			Project ID		~ `	X				
<u> </u>	Is COC dated by relinquisher?	inquisher?		×			Sample Date	ate	Ž	X	Triemplete	(m -03	16/256/	donkish
<u>~</u>	Is the sampler's name on the COC?	ne on the COC	23	>			Sample Time	me /	· ✓	ズ				
_∢	Are there analyses or hold for all samples?	or hold for all s	samples?	*			Does COC	Does COC match project history?	ject hist	6ry?	N/A	Yes	□ No	
_ G	Samples:			A/N	Yes	8	Commen	Comments: Temp exception - samples	2	ception	, - Samo		were semat	inted
Q	Are sample custody seals intact?	seals intact?		×			ton	ندو کیر م	Ducking	19 pape.	v. 75B	062513	'	. ,
4	Are sample containers intact?	ers intact?			×			10	-					1
<u> </u>	Is preservation documented?	umented?			×									
	In-house Analysis:			A X	Yes	2								
٩	Are preservatives acceptable?	cceptable?			×									
٩	Are samples within holding time?	holding time?			\times								;	
٩	Are sample container types correct?	er types correc	ıt?		X									
<u>"</u>	Is there adequate sample volume?	ample volume	~		メ							estato .		400
	Receipt Details:													
	Matrix	Container Type	r Type	# of Container	ntaine	ည						į	ļ	
İ	MA	NOA		24										
P												Ö	CS Required: ∠	ed:
P age 12							Proceed V Client Con	Proceed With Analysis: $oxed{X}$ YES $oxed{\Pi}$ NO Client Communication: $e_{M \cap \mathcal{U}} = (b \not> 1) \setminus S = 0 \not S \supset S$	S. XY	ES □ NO / 6/25/13	0 Init	Init/Date: 100	518290 7	1.3
age of 1														
] 14 2														

o Usold_ed\samprec\Forms\ Sample Receipt Checklist 05/13 rmh



(612)607-1700



July 15, 2013

Rob Delnagro Shaw Environmental 4005 Port Chicago Hwy Concord, CA 94520

RE: Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

Dear Rob Delnagro:

Enclosed are the analytical results for sample(s) received by the laboratory on June 21, 2013. The results relate only to the samples included in this report. Results reported herein conform to the most current TNI standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

Revised Report, REV-1 07/12/13. Per client request Naphthalene was added to the TO-15 list.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Jennifer Gross

ENNI (-PROSS

jennifer.gross@pacelabs.com Project Manager

Enclosures

cc: Sheila Richgels, Shaw Environmental







1700 Elm Street - Suite 200 Minneapolis, MN 55414 (612)607-1700

CERTIFICATIONS

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

Minnesota Certification IDs

1700 Elm Street SE Suite 200, Minneapolis, MN 55414

A2LA Certification #: 2926.01 Alaska Certification #: UST-078 Alaska Certification #MN00064 Arizona Certification #: AZ-0014 Arkansas Certification #: 88-0680 California Certification #: 01155CA Colorado Certification #Pace

Connecticut Certification #: PH-0256 EPA Region 8 Certification #: Pace Florida/NELAP Certification #: E87605


Georgia Certification #: 959
Hawaii Certification #Pace
Idaho Certification #: MN00064
Illinois Certification #: 200011
Kansas Certification #: E-10167
Louisiana Certification #: 03086
Louisiana Certification #: LA080009
Maine Certification #: 222

Maine Certification #: 2007029 Maryland Certification #: 322 Michigan DEQ Certification #: 9909 Minnesota Certification #: 027-053-137 Mississippi Certification #: Pace

Montana Certification #: MT CERT0092 Nebraska Certification #: Pace Nevada Certification #: MN_00064 New Jersey Certification #: MN-002 New York Certification #: 11647 North Carolina Certification #: 530 North Dakota Certification #: R-036 Ohio VAP Certification #: CL101 Oklahoma Certification #: 9507 Oregon Certification #: MN200001 Oregon Certification #: MN300001 Pennsylvania Certification #: 68-00563

Puerto Rico Certification

Tennessee Certification #: 02818
Texas Certification #: T104704192
Utah Certification #: MN00064
Virginia/DCLS Certification #: 002521
Virginia/VELAP Certification #: 460163
Washington Certification #: C754
West Virginia Certification #: 382
Wisconsin Certification #: 999407970






SAMPLE SUMMARY

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

Lab ID	Sample ID	Matrix	Date Collected	Date Received
10233236001	SV-1 (06-18)	Air	06/18/13 14:00	06/21/13 08:45
10233236002	SV-2 (06-18)	Air	06/18/13 14:10	06/21/13 08:45
10233236003	SV-3 (06-18)	Air	06/18/13 14:15	06/21/13 08:45
10233236004	Do Not Analyze Can 1485	Air	06/18/13 00:00	06/21/13 08:45






SAMPLE ANALYTE COUNT

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

Lab ID	Sample ID	Method	Analysts	Analytes Reported
10233236001	SV-1 (06-18)	TO-15	CJR	3
10233236002	SV-2 (06-18)	TO-15	CJR	3
10233236003	SV-3 (06-18)	TO-15	CJR	3






ANALYTICAL RESULTS

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

Date: 07/15/2013 12:48 PM

Sample: SV-1 (06-18)	Lab ID: 102	33236001	Collected: 06/18	3/13 14:00	Received: 0	6/21/13 08:45 N	Matrix: Air	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qua
TO15 MSV AIR - Ambient	Analytical Met	hod: TO-15						
Benzene	6.3 ug	g/m3	3.	1.92		07/03/13 15:48	71-43-2	
Methyl-tert-butyl ether	ND ug	g/m3	7.0	1.92		07/03/13 15:48	1634-04-4	
Naphthalene	ND ug	g/m3	5.	1.92		07/03/13 15:48	91-20-3	
Sample: SV-2 (06-18)	Lab ID: 102	33236002	Collected: 06/18	3/13 14:10	Received: 0	6/21/13 08:45 N	Matrix: Air	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qua
TO15 MSV AIR - Ambient	Analytical Met	hod: TO-15						
Benzene	7.6 ug	g/m3	3.0	1.83		07/03/13 15:19	71-43-2	
Methyl-tert-butyl ether	ND ug	g/m3	6.	7 1.83		07/03/13 15:19	1634-04-4	
Naphthalene	ND ug	g/m3	4.9	1.83		07/03/13 15:19	91-20-3	
Sample: SV-3 (06-18)	Lab ID: 102	33236003	Collected: 06/18	3/13 14:15	Received: 0	6/21/13 08:45 N	Matrix: Air	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qua
TO15 MSV AIR - Ambient	Analytical Met	hod: TO-15						
Benzene	7.6 ug	g/m3	3.	1.92		07/03/13 14:20	71-43-2	
Methyl-tert-butyl ether	ND ug	g/m3	7.0	1.92		07/03/13 14:20	1634-04-4	
Naphthalene	ND ug	n/m3	5.	1.92		07/03/13 14:20	91-20-3	





QUALITY CONTROL DATA

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

QC Batch: AIR/17725 Analysis Method: TO-15

QC Batch Method: TO-15 Analysis Description: TO15 MSV AIR - AMBIENT

Associated Lab Samples: 10233236001, 10233236002, 10233236003

METHOD BLANK: 1471471 Matrix: Air

Associated Lab Samples: 10233236001, 10233236002, 10233236003

		Blank	Reporting		
Parameter	Units	Result	Limit	Analyzed	Qualifiers
Benzene	ug/m3	ND	1.6	07/03/13 12:57	
Methyl-tert-butyl ether	ug/m3	ND	3.7	07/03/13 12:57	
Naphthalene	ug/m3	ND	2.7	07/03/13 12:57	

LABORATORY CONTROL SAMPLE: 1471472

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Benzene	ug/m3	34.4	35.0	102	72-136	
Methyl-tert-butyl ether	ug/m3	35.2	36.2	103	71-134	
Naphthalene	ug/m3	49.6	59.4	120	30-150	

SAMPLE DUPLICATE: 1471599

Date: 07/15/2013 12:48 PM

		10233236003	Dup		Max	
Parameter	Units	Result	Result	RPD	RPD	Qualifiers
Benzene	ug/m3	7.6	7.7	2	25	
Methyl-tert-butyl ether	ug/m3	ND	ND		25	
Naphthalene	ug/m3	ND	ND		25	



(612)607-1700

QUALIFIERS

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PRL - Pace Reporting Limit.

RL - Reporting Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up


U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

Date: 07/15/2013 12:48 PM





QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233236

Date: 07/15/2013 12:48 PM

Lab ID	Sample ID	QC Batch Method	QC Batch	Analytical Method	Analytical Batch
10233236001	SV-1 (06-18)	TO-15	AIR/17725		
10233236002	SV-2 (06-18)	TO-15	AIR/17725		
10233236003	SV-3 (06-18)	TO-15	AIR/17725		

AIR: CHAIN-OF-CUSTODY / Analytical Request Document

The Chain-of-Custody is a LEGAL DOCUMENT. All relovant fields must be completed accurately.

Section	Section B	Section C	11400	Page: \ of \	
Required Client Information:	Required Project Information:	Invoice Information:			1
	Report To: Rob Delnasio	Attention of Rote Data nage Direct Bill	to Tity Program		
Notices 4005 fort this eago the con to be six seed	copy to Joe nickers	Company Name: ATT Shada, Bolan	177) Tust Superfund	Clean	4
Email To: _ L : AUS TO Joseph Action Cochi, com	Joseph Adland Shile	To scale Richard Coschi com Peso Cumo Refineros 11/1/10, Tic 12CA 1010	7 Tocation of	Dry Clean RCRA Other	- II
Phone: 47 700 Fax	Project Name:	Pace Project Manager/Sales Rep.	Sampling by State	PPBV PPMV Other	ĺ
Requested Duo DeterTAT:	Project Numbor: 149327-06	Paca Profile 4:	Report Level II. II. IV.		1
'Section D Required Clort Information	S SOCO WIEN	COLLECTED E 3 E 3	Method: / / / / / /		
	ag IB	rossu d - pel rossu d - pol Summa	rey		
Sample IDs MUST BE UNIQUE	ODE	Fleic ter P Fleic Can	mber / /38 / 38/83/33/		
TEM #	Other Parts A Re Compount street	Canis (Initia	N/N /8/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/	2 / 23/ 25/ 25/ Pace Lab ID	-
(81-1/2/2)	2	1400	\	7	00
2 (SV-2106-18)			5	5	20
SV3 (06/18)	(d) (d) (d) (d)	HIS		5	ر د د
DO NOT AMOLY FE CAN	- 772 SBA1 COS	- 2841		(
۰		1			
		7	7		
10					
11		/	7		
12	RELIKONISHED SY / AFFILIATION	DATE TIME ACCEPTED	Y AFFILIATION DATE TIME	SAMPLE CONDITIONS	<u>ت</u>
Can 1485 was faulty, no pressure		and 0900 Ac St	6/21/13 0845	ARS S	(A)
you receipt do not analy		_		Y/N	Y/N
				YAN	YN
Parkie Prorr					YAN
		SAMPLER MAME WHO SIGNATURE FOR HELD		od on ody Coolnr	Intac
		Chila P-cencely			nples
		STOWN DE OF SAMPLER	DATO CALIBORNIA GOLDO	Ro Ses	San

1700 Elm Street SE. Suite 200. Minneapolis, MN 55414 Air Technical Phone: 612.607.6386

	7		Documen			Document Revise]
Taga and the same	ice Analyticai*	Alf Sar	npie Cenditi Docume	nt No.:	respt	Page 1 o	nority:	1
			F-MN-A-10			Pace Minnesota C	juality Office	<u></u>
An Sample Condition C Upon Receipt	llent Name: Shaw E-4	- \		Project f	" WO:	#:10233	236	
	Commercial Pace	USPS Other:	□a	lent	10233			
Tracking Number:	802G 4735 8	979	·					
Custody Seal on Cooler/I	Box Present? Yes	Mo	Seals In	tact?.]Yes	Optional: Proj. Due u	Mar. 110,1	
Packing Material: B	ubble Wrap Bubble	Bags 🔲 Fo	oam 🔀	None	Other:_			
Temp. (TO17 and TO13 samp Temp should be above freez	ples only) (°C): AMB ting to 6°C Correction Fed	Corrected Ten	φ('C):		Thermom. Use Date & Initials	id: []B88A912167504 of Person Examining Conta	□80512447 □723: nts: <u>G -2.1 13</u>	37080 <u>A</u> E
						Commen	ts:	
Chain of Custody Present		es	□No	□n/A	1.	-		
Chain of Custody Filled O		Yes	No	□N/A	2.			
Chain of Custody Relinqu		∑ Ves	_ □No	□N/A	3.	-		
Sampler Name and/or Sig			No	□N/A	4.			· · · · · · · · · · · · · · · · · · ·
Samples Arrived within H		∠Yes	No	□N/A	5. 6.			
Short Hold Time Analysis Rush Turn Around Time I			Y⊇Ko	□N/A	7.			
Sufficient Volume?	Requesteor	VZ/Yes	No		8.			
Correct Containers Used?)	¥≦Yes	□No	□n/A	9.			· · · · · · · · · · · · · · · · · · ·
-Pace Containers Used		Zes	□No	□N/A	•			
Containers Intact?		VZiyes	□No	N/A	10.			
Media:	Δ.ς		-		11.			
Sample Labels Match CO	7	Yes	_ □№	□n/a	12.			
Samples Received:	4 cans	7						
	sters		Flow	Controllers		s	tand Alone G	
Sample Number	Can ID	Sample !			Can ID	Sample Numbe		D
SV-1	0702							
SV -2	0804							
SV-3	0044							•
No Analy 5:5	1485							
				_	•			
			•	-				
				+				
				-				
CLIENT NOTIFICATION/RE	,	1			Data /Tima:		red? Yes No	
	ution:			'	Date/Time:			
- Changing neson					-			
Muslant Bitana and A	denn 6	2000			Bar-	6/25/13		
Project Manager Review: Note: Whenever there is a dig hold, incorrect preservative, o	crepancy affecting No.th Car ut of temp, incorrect contain		e samples, t	copy of t	nis form will be	sent to the North Carolina D	EHNR Certification Office	ce (i.e out

Page 10 of 10



(612)607-1700



July 15, 2013

Rob Delnagro Shaw Environmental 4005 Port Chicago Hwy Concord, CA 94520

RE: Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

Dear Rob Delnagro:

Enclosed are the analytical results for sample(s) received by the laboratory on June 21, 2013. The results relate only to the samples included in this report. Results reported herein conform to the most current TNI standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

Revised Report, REV-1 07/12/13. Per client request Naphthalene was added to the TO-15 list.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Jennifer Gross

ENNI (-PROSS

jennifer.gross@pacelabs.com Project Manager

Enclosures

cc: Sheila Richgels, Shaw Environmental







1700 Elm Street - Suite 200 Minneapolis, MN 55414 (612)607-1700

CERTIFICATIONS

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

Minnesota Certification IDs

1700 Elm Street SE Suite 200, Minneapolis, MN 55414

A2LA Certification #: 2926.01 Alaska Certification #: UST-078 Alaska Certification #MN00064 Arizona Certification #: AZ-0014 Arkansas Certification #: 88-0680 California Certification #: 01155CA Colorado Certification #Pace

Connecticut Certification #: PH-0256 EPA Region 8 Certification #: Pace Florida/NELAP Certification #: E87605


Georgia Certification #: 959
Hawaii Certification #Pace
Idaho Certification #: MN00064
Illinois Certification #: 200011
Kansas Certification #: E-10167
Louisiana Certification #: 03086
Louisiana Certification #: LA080009
Maine Certification #: 2007029

Maryland Certification #: 322 Michigan DEQ Certification #: 9909 Minnesota Certification #: 027-053-137 Mississippi Certification #: Pace

Montana Certification #: MT CERT0092 Nebraska Certification #: Pace Nevada Certification #: MN_00064 New Jersey Certification #: MN-002 New York Certification #: 11647 North Carolina Certification #: 530 North Dakota Certification #: R-036 Ohio VAP Certification #: CL101 Oklahoma Certification #: 9507 Oregon Certification #: MN200001 Oregon Certification #: MN300001 Pennsylvania Certification #: 68-00563

Puerto Rico Certification

Tennessee Certification #: 02818
Texas Certification #: T104704192
Utah Certification #: MN00064
Virginia/DCLS Certification #: 002521
Virginia/VELAP Certification #: 460163
Washington Certification #: C754
West Virginia Certification #: 382
Wisconsin Certification #: 999407970






SAMPLE SUMMARY

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

Lab ID	Sample ID	Matrix	Date Collected	Date Received
10233237001	SV-4 (06-19)	Air	06/19/13 13:30	06/21/13 08:45





SAMPLE ANALYTE COUNT

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

Lab ID	Sample ID	Method	Analysts	Analytes Reported
10233237001	SV-4 (06-19)	TO-15	AEJ	3





ANALYTICAL RESULTS

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

Date: 07/15/2013 12:46 PM

Sample: SV-4 (06-19)	Lab ID: 102	233237001	Collected: 06/19/	13 13:30	Received: 06	6/21/13 08:45 N	Matrix: Air	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
TO15 MSV AIR - Ambient	Analytical Me	thod: TO-15						
Benzene	20.5 u	g/m3	2.3	1.39		07/03/13 06:24	71-43-2	
Methyl-tert-butyl ether	ND u	g/m3	5.1	1.39		07/03/13 06:24	1634-04-4	
Naphthalene	7.0 u	g/m3	3.7	1.39		07/03/13 06:24	91-20-3	

(612)607-1700



QUALITY CONTROL DATA

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

QC Batch: AIR/17722

722 Analysis Method: TO-15

QC Batch Method: TO-15 Analysis Description: TO15 MSV AIR - AMBIENT

Associated Lab Samples: 10233237001

METHOD BLANK: 1471167 Matrix: Air

Associated Lab Samples: 10233237001

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Benzene	ug/m3	ND	1.6	07/02/13 12:01	
Methyl-tert-butyl ether	ug/m3	ND	3.7	07/02/13 12:01	
Naphthalene	ug/m3	ND	2.7	07/02/13 12:01	

LABORATORY CONTROL SAMPLE: 1471168

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Benzene	ug/m3	34.4	29.3	85	72-136	
Methyl-tert-butyl ether	ug/m3	35.2	30.0	85	71-134	
Naphthalene	ug/m3	49.6	58.4	118	30-150	

SAMPLE DUPLICATE: 1471169

Date: 07/15/2013 12:46 PM

		10233237001	Dup		Max	
Parameter	Units	Result	Result	RPD	RPD	Qualifiers
Benzene	ug/m3	20.5	21.1	3	25	
Methyl-tert-butyl ether	ug/m3	ND	ND		25	
Naphthalene	ug/m3	7.0	7.2	4	25	

(612)607-1700



QUALIFIERS

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PRL - Pace Reporting Limit.

RL - Reporting Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

Date: 07/15/2013 12:46 PM

Minneapolis, MN 55414 (612)607-1700



QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: ATT San Jose 95 S.Almaden REV1

Pace Project No.: 10233237

Date: 07/15/2013 12:46 PM

Lab ID	Sample ID	QC Batch Method	QC Batch	Analytical Method	Analytical Batch
10233237001	SV-4 (06-19)	TO-15	AIR/17722		



AIR: CHAIN-OF-CUSTODY / Analytical Request Document

The Chain-of-Custody is a LEGAL DOCUMENT, All relevant fields must be completed accurately.

ORIGINAL		* Routine Report	Comments:	:2					6	(5)	£	3	/	(PI-4106-19)	ITEM#	Sample IDs MUST BE UNDOUG 60W	g S		Phone: 19k1102 Face Project Chil. Com	Email To: 1 Cal Carpor Purch	chappe		Section A Sect Required Client Information: Required	****
ř		Stip last	RELINGUISHED BY / AFFILIATION	_									\	111/19	MEDIA C	ding (Clian	t cnly)	149277,06	Project Namo: ATI S. Almada	"Wanters "	Pickage	la Delnasion	Section B Required Project Information:	
SAMPLER HAME AND SIGNATURE PRINT SAME SAMPLER SEGMITHER OF SAMPLER SEGMI		2/20/1 0900	FFILIATION DATE TIME											39_	TIME DATE TIME CELLS		etg)	Pace Profile #:		Pace Quale Reference:	Company Namo	Attention: Dwell and	Section C Invoice information:	
DATE SE		Acres Low Prom	ACCEPTED BY / AFFILIATION										-	1563	(Final	Field - p			017/00-151304	,		to Titan 1955		
Temp in °C		6 21 113 0845 AG	DATE TIME			7	/	/	/							Gee (X)		Report Level II. III. IV.	Sampling by State CA	T Volumenty Clean Up T Dry Clean i	UST Superfund Enteriors	Program	10519	
Received on Ice	 N Y/	· v6	CONDITION												Paco Lab ID	on los Trace		othera\r\	PPBV PPWV	RCRA			Page: 1 of 1	

1700 Firm Street SF Sutha 200 Minneannalia. MN 55414 Air Technical Phone: 612.607.6386

FC046Rev.01. 03Fcb2010

Pace Analytical*
/ Xaca Anamicai
المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع المنابع

Document Name: Air Sample Condition Upon Receipt

Document Revised: 28Jan2013 Page 1 of 1

	1	toamiaiyucai		F-MN-A-1			Pace Minnesota Quality	Office					
Air Sample Upon R		lient Name:			Project #	" WO:	#:1023323	7					
oponk		Shaw	E+1			40010000		•					
	Courler: 🛣	Fed Ex	JPS USPS		Client ()								
	_		Pace Other:			10233	237						
Tracking i	Number:	7957 914	2 1884			Ĺ		<u> </u>					
Custody S	eal on Cooler/	Box Present?	es No		ntact?.	Yes 🗀 N	Optional: Proj. Due Date:	Proj. Name:					
Packing M	laterial: 🔲 🖺	lubble Wrap 🔲 🔲	Bubble Bags 🔲 Fo	oam 🔀	None	Other:		٠.					
Temp. (TO17 and TO13 samples only) ('C): AAG Corrected Temp ('C): Thermom. Used: B88A912167504 B80512447 72337080 Temp should be above freezing to 6'C Correction Factor: Date & initials of Person Exemining Contents: 4/2/1/3 AT													
					,		Comments:	··					
Chain of	Custody Presen	17	Yes	□No	□N/A	1.							
Chain of	Custody Filled C	out?	Yes	No	□N/A	2.							
Chain of	Custody Relinqu	ilshed?	Yes_	□No	□n/A	3.							
Sampler	Name and/or S1	gnature on COC?	Yes	□No	□n/a	4.							
Samples	Arrived within }	told Time?	Yes	□No	□N/A	5.							
Short Ho	id Time Analysi	s (<72 hr)?	Yes	₩.	□N/A	6.		, 					
Rush Tur	n Around Time	Requested?	Yes	No	□N/A	7.		•					
Sufficient	Volume?	z	Yes	□No	. □N/A	8.							
Correct C	Containers Used	7	Yes	□No	□n/A	9.							
	Containers Use	17	Yes	No	□N/A			·					
Containe		A	✓Yes	□No	□n/A	10.	·		 -				
						11.							
Sample L	abels Match CO	<u>C7</u>	K Yes_	□No	□N/A	12.							
Samples	Received:	1 60	<u> </u>										
	Car	isters		Flow	Controllers	<u></u>	Stand /	Alone G					
	ole Number	Can ID	Sample (Number		Can ID	Sample Number	Can II)				
54-41	(०६नव)	1563			_	•							
								· ·					
	· · · · · · · · · · · · · · · · · · ·	ļ											
		<u> </u>				<u></u>		 					
	•!	 				_ 		 					
— —		 											
	 	 			+								
		 				•	· ·						
					+			 					
L					· I								
CLIENT NO	TIFICATION/R					•	Field Data Required?	□Yes □No	•				
	Person Con		·		I	Date/Time:			· ·				
Cr	omments/Reso	Jution:											

Project Manager Review: ENUL STARS Date: 62513

Note: Whenever there be discrepandy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office (i.e. out of hold, incorrect preservative, out of temp, incorrect centainers)

APPENDIX F DRUM DISPOSAL DOCUMENTATION

A	NON-HAZARDOUS	1. Generator ID Number	2. Page 1 of	3. Emergency Respon	se Phone	4. Waste Tracking Number					
1	WASTE MANIFEST	CAT080023021	1 No	800-424-9364).	NH32530-N					
	5. Generator's Name and Mailin	ng Address		Generator's Site Addre							
	PO 5095 ROOM 3 SAN RAMON, CA			95 S. ALM SAN JOSE							
Ш	Generator's Phone:	-823-0200 ne				U.S. EPA ID	Number				
Ш	ENVIRONMENTAL						1000217	5.12			
	7. Transporter 2 Company Nan					U.S. EPA ID		J13			
	1,750										
	180 WEST MONT RIALTO, CA 923	NG SERVICES. INC. E AVENUE 16. USA				U.S. EPA ID	Number 1982444	1481			
Ш	Facility's Phone: 600-698	-4377									
	9. Waste Shipping Name	e and Description		10. Cor No.	Type	11. Total Quantity	12. Unit Wt./Vol.				
GENERATOR -	1. NON HAZARI	DOUS WASTE LIQUID (PURGE WA	TER)	04	DM /	220	0				
ENE	2. NON HAZARI	DOUS WASTE SOLID (SOIL CUTTI	VGS)		DM		P				
				09		5600	7				
	3.										
	4.										
	13. Special Handling Instruction 9B1) PURGE WAT 9B2) SOIL CUTTII	TER 4X55	WEAR	PROPER PPE		WO# 328	30-N				
	EMERGENCY RE	SPONSE CHEMTREC 1-800-42	4-9300 CCN6	68232							
	14. GENERATOR'S CERTIFIC	ATION: I certify the materials described above on the	is manifest are not subje	ct to federal regulations for	or reporting pro	ner disposal of H	azardous W	aste			
	Generator's/Offeror's Printed/Ty			gnature	or roporting pro	por diopodai oi rii	azaraodo VI	Month Day Year			
*		R.E. Cuiz	1	- January Comment		2.4		12 112112			
٦	15. International Shipments	Import to U.S.	Export from	UC Post of	auto (auto	-					
INT'L	Transporter Signature (for expo		Export from	3.7%	entry/exit: aving U.S.:						
	16. Transporter Acknowledgme			1	aring oron						
R	Transporter 1 Printed/Typed Na		Sig	gnature	attar a			Month Day Year			
SPC	altino -	OboN		1300	Fight.			07 17 13			
TRANSPORTER	Transporter 2 Printed/Typed Na	me./	Się	gnature				Month Day Year			
A	17. Discrepancy										
	17a. Discrepancy Indication Spa	Quantity	Туре	Residue		Partial Rej	ection	Full Rejection			
LITY -	17b. Alternate Facility (or Gene	rator)		Manifest Reference	Number:	U.S. EPA ID I	Number				
-AC	Facility's Phone:					1					
DESIGNATED FACILITY	17c. Signature of Alternate Faci	lity (or Generator)	Ī					Month Day Year			
DESIGN							-				
1						or the promise of					
	18. Designated Facility Owner of	or Operator: Certification of receipt of materials cover		ot as noted in Item 17a							
	Printed/Typed Name			gnature				Month Day Year			
*											