

## **Media Filter Cartridge Sizing for Approved Design Operating Rate**

| Technology*                         | Vendor                                | Design Operating Rate**                         | Cartridge Height (inches) | Cartridge Design<br>Flowrate (gpm/cartridge) |
|-------------------------------------|---------------------------------------|---|---------------------------|--|
| FloGard Perk Filter                 | Kristar/Oldcastle Precast, Inc.       | 1.5 gpm/ft² of filter surface area              | 12                        | 6.8  |
| FloGard Perk Filter                 | Kristar/Oldcastle Precast, Inc.       | 1.5 gpm/ft² of filter surface area              | 18                        | 10.2   |
| Media Filtration System (MFS)       | CONTECH Engineered Solutions, LLC.    | 1 gpm per 2.44 inches in height                 | 12                        | 4.9  |
| Media Filtration System (MFS)       | CONTECH Engineered Solutions, LLC.    | 1 gpm per 2.44 inches in height                 | 18                        | 7.4  |
| Media Filtration System (MFS)       | CONTECH Engineered Solutions, LLC.    | 1 gpm per 2.44 inches in height                 | 22                        | 9  |
| StormFilter using PhosphoSorb Media | CONTECH Engineered Solutions, LLC.    | 1.67 gpm/ft <sup>2</sup> of filter surface area | 12                        | 8.35   |
| StormFilter using PhosphoSorb Media | CONTECH Engineered Solutions, LLC.    | 1.67 gpm/ft <sup>2</sup> of filter surface area | 18                        | 12.53  |
| StormFilter using PhosphoSorb Media | CONTECH Engineered Solutions, LLC.    | 1.67 gpm/ft <sup>2</sup> of filter surface area | 27                        | 18.79  |
| StormFilter using ZPG<br>Media      | CONTECH Engineered<br>Solutions, LLC. | 1 gpm/ft² of filter surface area                | 12                        | 5  |
| StormFilter using ZPG<br>Media      | CONTECH Engineered Solutions, LLC.    | 1 gpm/ft² of filter surface area                | 18                        | 7.5  |
| StormFilter using ZPG<br>Media      | CONTECH Engineered Solutions, LLC.    | 1 gpm/ft² of filter surface area                | 27                        | 11.3   |

200 East Santa Clara St. • San José, CA 95113 • tel (408) 793-4383 • fax (408) 271-1930 • www.sanjoseca.gov

| Technology*   | Vendor                                    | Design Operating Rate**                                  | Cartridge Height (inches) | Cartridge Design<br>Flowrate (gpm/cartridge) |
|---|---|--|---------------------------|--|
| BayFilter Cartridge   | Baysaver Technologies, Inc.               | 0.70 gpm/ft² of filter surface area                      | N/A                       | N/A  |
| Enhanced Media<br>Cartridge***                                    | Baysaver Technologies, Inc.               | 0.50 gpm/ft² of filter surface area                      | N/A                       | N/A  |
| MWS-Linear Modular<br>Wetland- Basic Prefilter<br>Media Cartridge | Bio Clean Environmental<br>Services, Inc. | Low-Medium: 3 gpm/ft <sup>2</sup> of filter surface area | N/A                       | N/A  |
| MWS-Linear Modular<br>Wetland- Basic Prefilter<br>Media Cartridge | Bio Clean Environmental<br>Services, Inc. | High: 2.1 gpm/ft <sup>2</sup> of filter surface area     | N/A                       | N/A  |

<sup>\*</sup>The listed media filter products are certified as General Use Level Designation (GULD) for Basic Treatment (TSS) by the State of Washington Department of Ecology TAPE Program.

<sup>\*\*</sup>Design operating rate established by the State of Washington Department of Ecology TAPE Program.

<sup>\*\*\*</sup>The Enhanced Media Cartridge is approved with GULD for basic treatment (TSS) and with Conditional Use Level Designation for phosphorus treatment.