TABLE A - BACKFLOW UNIT DIMENSIONS

SIZE	WILKINS RP BACKFLOW PREVENTER			MINIMUM ENCLOSURE DIMENSIONS			
	MODEL	LENGTH	TYPE	W	L	Н	TYPE
3/4 "	575 RP	11 3/8 "	SCREWED	12"	30"	30"	SINGLE - SWING HINGE
1"	575 RP	11 3/8 "	SCREWED	12"	30"	30"	SINGLE - SWING HINGE
11/2 "	575 RP	16 1/4 "	SCREWED	18"	42"	30"	SINGLE - SWING HINGE
2"	575 RP	16 1/4 "	SCREWED	18"	42"	30"	SINGLE - SWING HINGE
3"	575 RP	36"	FLANGED	30"	72"	42"	DOUBLE - SWING HINGE
4"	575 RP	46 1/2 "	FLANGED	30"	84"	42"	DOUBLE - SWING HINGE

TABLE B - STRAINER UNIT DIMENSIONS

	BAILEY NO	. 100-A Y-STRAINE	R	REQUIRED CONCRETE BOX & TRAFFIC LID		
SIZE	LENGTH	CONN.	BLOW-OFF	CHRISTY MODEL	INSIDE DIMENSIONS	
3/4 "-1"	4 1/2 "	SCREWED	1/2 "- 3/4 "	B-3	9 7/8 " x 16 1/4 "	
1 1/2 "	6"	SCREWED	3/4 "	B-3	9 7/8 " x 16 1/4 "	
2"	7 3/8 "	SCREWED	3/4 "	B-30	13 1/4 " x 24"	
2 1/2 "	10 1/2 "	FLANGED	1 1/4 "	B-30	13 1/4 " x 24"	
3"	12"	FLANGED	1 1/4 "	B-30	13 1/4 " x 24"	
4"	14 9/16 "	FLANGED	1 1/2 "	B-30	13 1/4 " x 24"	

APPROVED BY

DATE

DIMENSION TABLES

OF SAN CONTROL OF SAN

DRAWING NO.

L-10

DEPARTMENT OF PUBLIC WORKS