


CORP. STOP	TYPE 1 & 2	TYPE 3 & 4 F1000G	
FORD	F1100G		
MUELLER	H15024	H15006	



NOTES:

- 1. TYPE 1-INSTALL ANODE AS SHOWN IN STANDARD DETAIL W-15.
- 2. TYPES 1 & 2-WRAP CORPORATION STOP AND 5' OF COPPER TUBING WITH 10 MIL PVC TAPE (1/2 LAPPED).
- 3. TYPE 1-IF WATER MAIN IS COATED,
 REPLACE COATING ON MAIN AND COAT
 WELD-ON SERVICE SADDLE AND INSULATING BUSHING WITH 1/4" MIN. COATING
 OF SAME MATERIAL (OR 10 MIL PVC TAPE)
- 4. TYPE 2– IF MAIN IS POLYWRAPPED, REPAIR AND EXTEND POLYWRAP TO COVER CORPORATION STOP.
- 5. FOR WATER METER INSTALLATION SEE STANDARD DETAIL W-2.
- 6. ALL BRASS CORPS FOR BRASS SADDLES SHALL HAVE CC THREADS (SADDLES AND CORPS)


	SE	RVICE CONNEC	TION SCHEDUL	E		
SERVICE	WATER MAIN MATERIAL					
SIZE	STEEL	D.I.P.	A.C.P.	R.P.M.	P.V.C.	
3/4"	TYPE 1	TYPE 2	TYPE 3	TYPE 3	TYPE 4	
1″	п		н	н	11	
1- 1/2"	311	W W	II.	0	ü	
2"	11		и	н	11	

APPROVED BY

DATE

CONNECTION TYPES FOR 3/4" - 2" SERVICE TAPS

DEPARTMENT OF PUBLIC WORKS



DRAWING NO.

W-1