

San José Reach Code

December 17, 2019

nbi new buildings institute





Agenda


- Background
- Reach CodeRequirements
- Review of Requirements
- Examples of Requirements





nbi new buildings institute

Background



What is a Reach Code?



Minimum Base Codes

 Set minimum levels of efficiency for building design and construction



Reach Codes

- Overlays the base code
- Includes additional requirements, such as:
 - Energy efficiency
 - Water efficiency
 - Electrification
 - EV charging infrastructure
 - Solar PV





CLIMATE SMART SAN JOSE

A People-Centered Plan for a Low-Carbon City



Why has San José Adopted a Reach Code?

Goals for 2030

- 47% of homes are all-electric
- 37,975 zero net carbon (ZNC) homes
- 70M sf of ZNC commercial buildings
- 61% of all passenger vehicles are electric
- 668 MW of solar installed



CLIMATE SMART SAN JOSE

A People-Centered Plan for a Low-Carbon City



Building Electrification

- 47% of homes are all-electric
- 37,975 zero net carbon (ZNC) homes
- 70M sf of ZNC commercial buildings

EV charging infrastructure

61% of all passenger vehicles are electric

Solar PV

668 MW of solar installed



What's already included in the Title 24?

	2016	2019
Building Electrification	None	Electrification-ready water heating for low-rise residential
Electric Vehicle Charging Infrastructure	EV parking requirements for single family, multifamily and commercial (San Jose CAL Green)	More extensive EV parking requirements
Solar PV	Solar readiness for single-family, multi-family (up to 10 stories) & low-rise commercial (except healthcare)	+ Mandatory PV for low-rise residential







nbi new buildings institute

Reach Code Requirements

Reach Code Requirements



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



Building Electrification Components


- 1. Gas Ban in Low-Rise Residential
- 2. Increased Compliance Margin in all other Mixed-Fuel Buildings
- 3. Electrification Readiness





	All-Electric	Mixed-Fuel	Code Reference
Single Family	Meet Title 24 - 2019	Not Permitted	Gas Ban Ordinance
Low-Rise Multifamily	Meet Title 24 - 2019	Not Permitted	Gas Ban Ordinance
High Rise MF / Hotel / Motel	Meet Title 24 - 2019	6% better than T24 + Electrification Readiness Solar Ready	Section 150.1
Office / Retail	Meet Title 24 - 2019	14% better than T24 + Electrification Readiness Solar Ready	Section 150.1
Industrial / Manufacturing	Meet Title 24 - 2019	Electrification Readiness Solar Ready	Section 150.1

Modeled Performance



Project Name:	LargeOffice	NRCC-PRF-01-E	Page 2 of 20
Project Address:	San Jose	Calculation Date/Time:	23:10, Mon, Nov 18, 2019
Input File Name:	Prototype_Office_Large - Reach.cibd19		

C1. COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual TDV Energy Use, kBtu/ft ²-yr)

COMPLIES

351111 2123				
Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV) ¹	
Space Heating	10.09	9.64	0.45	
Space Cooling	17.15	17.15		
Indoor Fans	17.08	16.66	0.42	
Heat Rejection	2.17	2.50	-0.33	
Pumps & Misc.	6.01	7.49	-1.48	
Domestic Hot Water	7.38	2.08	5.30	
Indoor Lighting	33.24	33.24	-	
ENERGY STANDARDS COMPLIANCE TOTAL	93.12	88.76	4.36 (4.7%)	

Notes: The number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.

C2. RESULTS FOR 'ABOVE CODE' QUALIFICATIONS'

project is pursuing CalGreen Tier 1		t is pursuing CalGreen Tier 2	
Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV) ¹	
119.41	119.41	0.0	
3.21	3.21	0.0	
	944		
-		-	
215.74	211.38	4.4 (2.0%)	
	Standard Design (TDV) 119.41 3.21	119.41 119.41 3.21 3.21 	

Notes: This table is used to document compliance with programs OTHER THAN Title 24 Part 6, if applicable.

D. EXCEPTIONAL CONDITIONS

The aged solar reflectance and aged thermal emittance must be listed in the Cool Roof Rating Council database of certified products. For projects where initial reflectance is used, the initial reflectance must be listed, and the aged reflectance is calculated by the software program and used in the compliance model.

This project includes Domestic Hot Water in the analysis. Please verify that Domestic Hot Water is included in the design for the permitted scope of work.



Prescriptive Compliance – Hotel/Motel

- SHGC ≤ 0.22
- Efficient VAV airflow design
- Economizer (≥ 33,000 Btu/h cooling)
- 10% Lighting Power Density reduction
- Drain water heat recovery
- Improved Daylighting Controls
- Institutional Lighting Controls Tuning





Prescriptive Compliance – Other Non-Res

- SHGC ≤ 0.22
- 50% reduction of East & West fenestration area
- Efficient VAV airflow design
- Economizer (≥ 33,000 Btu/h cooling)
- 10% Lighting Power Density reduction
- Drain water heat recovery
- Improved Daylighting Controls
- Institutional Lighting Controls Tuning
- Occupancy Controls in open area offices





Electrification Readiness







Electrification Readiness – Non-Residential

- Water Heater: 240V 30A circuit, condensate drain, 700 CFM of make-up air
- Clothes Dryer: 240V 30A circuit
- Cooking: 240V 50A circuit
- All Other: Designated Raceway + equivalent electrical capacity





Electrification Readiness – Non-Residential





• All Other: Designated Raceway + equivalent electrical capacity





Reach Code Requirements



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



EVCI Definitions


Electric Vehicle Charging Infrastructure

Level 1



15-20 Amp, 120v AC (standard household outlet)
Driving Distance provided: 3-4 miles/hour

Level 2



208/240v AC

Driving Distance provided: 25-30 miles/hour

DC Fast Charge



80-400 Amp, 200-600v DC

Driving Distance provided: 125-1000 miles/hour






EVCI Definitions

Electric Vehicle Charging Infrastructure

EV Capable (Some assembly required)



Raceway (conduit), electrical capacity (breaker space)

EV Ready (Plug & Play)



Raceway (conduit), electrical service capacity, overcurrent protection devices, wire and outlet (i.e. full circuit)

EV Supply
Equipment
(EVSE) Installed
(Level 2
Charge!)



All the equipment needed to deliver electrical energy from an electricity source to the EV



Courtesy TRC, PCE & SVCE



	2019 Base Code	San Jose Reach Code	Code Languag
Single Family	1 EV Ready space	1 EV Ready space	Section 4.106.4.1
Low Rise Multifamily	10% spaces EV Capable	10% spaces EVSE 20% spaces EV Ready 70% EV Capable	Section 4.106.4.2
Low-Rise Hotel / Motel	4-6% spaces EV Capable	10% spaces EVSE 50% spaces EV Capable	Section 4.106.4.3.1
All Non-Res	4-6% spaces EV Capable	10% spaces EVSE 40% spaces EV Capable	Section 5.106.5.3.1

Reach Code Requirements



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



	2019 Base Code	San Jose Reach Code	Code Language
Low-Rise Residential	Solar PV -OR- Solar-Ready	Same	Section 110.10 (a) 1 & 2
High Rise MF	Solar-Ready up to 10 stories	Solar-Ready for all	Section 110.10 (a) 3
All Other	Solar-Ready except healthcare or over 3 stories	Solar-Ready for all	Section 110.10 (a) 4





Solar Readiness



Now Included

- MF over 3 stories
- Non-Res over 3 stories
- Healthcare







nbi new buildings institute

Examples of Reach Code Requirements

Reach Code Building Electrification



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV scenario



Building Electrification








Electrification



Electrification Readiness







Electrification Readiness

Electrification-Ready

- Water Heater
- Range
- Residential Space Heating
- Clothes Dryer

Electrification-Capable

- Central Water Heating
- Other Gas Loads





Reach Code Electric Vehicle Charging



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



EV Capable



For each EV Capable Space

Conduit from panel to space





For each EV Capable Space

- Physical space for breaker
- 8A of capacity



EV Ready





For each EV Ready Space:

• Full circuit with 40A of capacity





DC Fast Chargers (EVSE)










Electric Vehicle Service Equipment (EVSE)












Electric Vehicle Service Equipment (EVSE)









32A Output




Reach Code Solar PV



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



Solar Readiness









Questions?










nbi new buildings institute

San Jose Reach Code


Flow Chart – Step 1








Reach Code Flow Chart







Mixed Fuel Flow Chart








Reach Code



- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



	All-Electric	Mixed-Fuel	Code Reference
Single Family	Meet Title 24 - 2019	Not Permitted	Gas Ban Ordinance
Low-Rise Multifamily	Meet Title 24 - 2019	Not Permitted	Gas Ban Ordinance
High Rise MF / Hotel / Motel	Meet Title 24 - 2019	6% better than T24 + Electrification Readiness	Section 150.1
Office / Retail	Meet Title 24 - 2019	14% better than T24 + Electrification Readiness	Section 150.1
Industrial / Manufacturing	Meet Title 24 - 2019	Electrification Readiness	Section 150.1





CAPITAL OF SILICON VALLEY

Page 2

Project Name:	LargeOffice	NRCC-PRF-01-E	Page 2 of 20	
Project Address:	San Jose	Calculation Date/Time:	23:10, Mon, Nov 18, 2019	
Input File Name:	Prototype_Office_Large - Reach.cibd19			

COMPLIES							
Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV) ¹				
Space Heating	10.09	9.64	0.4				
Space Cooling	17.15	17.15					
Indoor Fans	17.08	16.66	0.4				
Heat Rejection	2.17	2.50	-0.3				
Pumps & Misc.	6.01	7.49	-1.4				
Domestic Hot Water	7.38	2.08	5.3				
Indoor Lighting	33.24	33.24					
ENERGY STANDARDS COMPLIANCE TOTAL	93.12	88.76	4.36 (4.7%				

☐ This project is pursuing CalGreen Tier 1		This project is pursuing CalGreen Tier 2	
Carries project is pursuing cardreen rier 1		This project is pursuing Caldreen Her 2	
Miscellaneous Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV) ¹
Receptacle	119.41	119.41	0.0
Process	3.21	3.21	0.0
Other Ltg	-		
Process Motors	-		2
COMPLIANCE TOTAL PLUS MISCELLANEOUS COMPONENTS	215.74	211.38	4.4 (2.0%

D. EXCEPTIONAL CONDITIONS

The aged solar reflectance and aged thermal emittance must be listed in the Cool Roof Rating Council database of certified products. For projects where initial reflectance is used, the initial reflectance must be listed, and the aged reflectance is calculated by the software program and used in the compliance model.

This project includes Domestic Hot Water in the analysis. Please verify that Domestic Hot Water is included in the design for the permitted scope of work.





Compliance – Non-Residential

All-Electric

Project Name:	LargeOffice	NRCC-PRF-01-E	Page 2 of 20
Project Address:	San Jose	Calculation Date/Time:	23:10, Mon, Nov 18, 2019
Input File Name:	Prototype_Office_Large - Reach.cibd19		

C1. COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Ann	nual TDV Energy Use, kBtu/ft 2-yr)		
	COMPLIES		
Energy Component	scandard design (10V)	Proposed Design (TDV)	Compliance Margin (TDV) ¹
Space Heating	10.09	9.64	0.45
Space Cooling	17.15	17.15	
Indoor Fans	17.08	16.66	0.42
Heat Rejection	2.17	2.50	-0.33
Pumps & Misc.	Øj 6.01	7.49	-1.48
Domestic Hot Water	7.38	2.08	5.30
Indoor Lighting	33.24	33.24	-
ENERGY STANDARDS COMPLIANCE TOTAL	93.12	88.76	4.36 (4.7%)
I Notes: The number in parentheris following the Compliance Margin	in column 4 convergets the Operant Con-	tas than Standard	

Notes: The number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.

0	☐ This project is pursuing CalGreen Tier 2			
Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV) ¹		
119.41	119.41	0.0		
3.21	3.21	0.0		
-				
		74		
215.74	211.38	4.4 (2.0%)		
	Standard Design (TDV) 119.41 3.21	Standard Design (TDV) Proposed Design (TDV) 119.41		

D. EXCEPTIONAL CONDITIONS

The aged solar reflectance and aged thermal emittance must be listed in the Cool Roof Rating Council database of certified products. For projects where initial reflectance is used, the initial reflectance must be listed, and the aged reflectance is calculated by the software program and used in the compliance model.

This project includes Domestic Hot Water in the analysis. Please verify that Domestic Hot Water is included in the design for the permitted scope of work.





Heat Rejection

Pumps & Misc.

Domestic Hot Water

Mixed-Fuel

Project Name:	LargeOffice	NRCC-PRF-01	-E	Page 2 of 20			
Project Address:	San Jose		ate/Time:	23:10, Mon, Nov 18, 2019			
Input File Name:	Prototype_Office_Large - Reach.cibd19	<u> </u>		No.			
	RESOLIS FOR PERFORMANCE COMPONEN	TS (Annual TDV Energy Use, kBtu/ft ² -yr) COMPLIES					
	ACSOCIS FOR PERFORMANCE COMPONEN						
	Energy Component		Prog	oosed Design (TDV)	Compliance Margin (TDV) ¹		
Space Heating		COMPLIES	Prop	oosed Design (TDV)			
		COMPLIES Standard Design (TDV)	Proj		Compliance Margin (TDV) ¹ 0.4		

2.17

6.01

7.38

C2. RESULTS FOR 'ABOVE CODE' QUALIFICATIONS ¹	6				
□This project is pursuing CalGreen Tier 1 □This project is pursuing CalGreen Tier 2					
Miscellaneous Energy Component	Standard Design (TDV)	Proposed Design (TDV)	Compliance Margin (TDV) ¹		
Receptacle	119.41	119.41	0.0		
Process	3.21	3.21	0.0		
Other Ltg	-				
Process Motors 0	-		72		

Notes: This table is used to document compliance with programs OTHER THAN Title 24 Part 6, if applicable.

D. EXCEPTIONAL CONDITIONS

COMPLIANCE TOTAL PLUS MISCELLANEOUS COMPONENTS

The aged solar reflectance and aged thermal emittance must be listed in the Cool Roof Rating Council database of certified products. For projects where initial reflectance is used, the initial reflectance must be listed, and the aged reflectance is calculated by the software program and used in the compliance model.

This project includes Domestic Hot Water in the analysis. Please verify that Domestic Hot Water is included in the design for the permitted scope of work.





2.50

7.49

2.08


211.38

-1.48


5.30

4.36 (4.7%)

4.4 (2.0%)









Check Efficiency Level – Low-Rise Residential

Page 2

CERTIFICATE OF COMPLIANCE

Project Name: 2019 Prototype 2700ft2 Std Mixed

Calculation Date/Time: 2019-11-18T15:21:35-08:00

(Page 2 of 11)

Calculation Description: TDSv30 V02R04 V02 R04 EGLASS20 NGAS PVSTD Input File Name: 2019_CZ04_2700ft2_Std_NGAS - Reach,ribd19

	Energy Design Ratings		Compliance Margins	
	Efficiency ¹ (EDR)	Total ² (EDR)	Efficiency' (EDR)	Total ² (EDR)
Standard Design	44.7	44.7 23.3		
Proposed Design	40.9	19.5	3.8	3.8

RESULT: 3: COMPLIES

Efficiency measures include improvements like a better building envelope and more efficient equipment

² Total EDR includes efficiency, photovoltaics and batteries

^a Building complies when all efficiency and total margins are greater than or equal to zero

Standard Design PV Capacity: 2.91 kW

PV System resized to 2.90 kWdc (a factor of 2.900) to achieve 'Maximum PV for Compliance Credit' PV scaling

	ENERGY USE SUMMARY								
Energy Use (kTDV/ft ² -yr)	Standard Design	Proposed Design	Compliance Margin	Percent Improvement					
Space Heating	16.09	13.23	2.86	17.8					
Space Cooling	5.08	3.32	1.76	34.6					
IAQ Ventilation	2,53	2.53	0	0					
Water Heating	10.46	7.99	2.47	23.6					
Self Utilization Credit	n/a	0	0	n/a					
Compliance Energy Total	34.16	27.07	7.09	20.8					

REQUIRED PV SYSTE	MS	- 29								
01	02	03	04	05	06	07	08	09	10	11
DC System Size (kWdc)	Exception	Module Type	Array Type	Power Electronics	CFI	Azimuth (deg)	Tilt Input	Array Angle (deg)	Tilt: (x in 12)	Inverter Eff. (%)
2.9	NA	Standard	Fixed (open rack)	none	true	n/a	n/a	n/a	n/a	96

Registration Number:

Registration Date/Time:

HERS Provider:


CA Building Energy Efficiency Standards - 2019 Residential Compliance

Report Version: 2019.1.002 Schema Version: rev 20190401 Report Generated: 2019-11-18 15:24:12





Check Efficiency Level – Low Rise





LIVING BETTER TODAY FOR TOMORROW


Electrification Readiness

- Water Heater: 240V 30A circuit, condensate drain, 700 CF of air
- Clothes Dryer: 240V 30A circuit
- Cooking: 240V 50A circuit
- All Other: Designated Raceway + equivalent electrical capacity






Electrification Readiness







Electrification Readiness







Check Electrification Readiness











Reach Code




- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



	2019 Base Code	San Jose Reach Code	Code Language
Single Family	1 EV Ready space	1 EV Ready space	Section 4.106.4.1
Multifamily	10% spaces EV Capable	10% spaces EVSE 20% spaces EV Ready 70% spaces EV Capable	Section 4.106.4.2
Low-Rise Hotel / Motel	4-6% spaces EV Capable	10% spaces EVSE 50% spaces EV Capable	Section 4.106.4.3.1
All Non-Res	4-6% spaces EV Capable	10% spaces EVSE 40% spaces EV Capable	Section 5.106.5.3.1

EVCI







EVCI – EVSE Spaces

- Space Count
- Charger Specifications
- Circuit Size and Location







EVCI – EV Ready Spaces

Space Count
Circuit Size & Location







EVCI – EV Capable Spaces

- Space Count
- Conduit size and Location
- Available Capacity







8 EV Capable Spaces



20 EV Capable Spaces





8 EV Capable Spaces

64A @
240V
Additional
Capacity



20 EV Capable Spaces

160A @ 240V Additional Capacity





Reach Code




- BuildingElectrification
- Electric VehicleChargingInfrastructure
- Solar PV



Solar Readiness

- Identify Solar-Ready Zone
- Interconnection Pathway
- Physical Space at Electrical Panel
- Structural Support for Panels










Solar-Ready Zone



- Minimum Zone Size:
 - Single Family 250 SF
 - All Other 15%
- Minimum segment size:

 - >10,000 sf roof: 160 sf





Questions?





