

Structural Engineering & Code Inspections

Grease Interceptor Sizing Form

The Plumbing Plan Review Section has reviewed the plans for the project shown below and has determined that the grease removal requirements shall comply with the following grease pretreatment device or devices, per the California Plumbing Code and as required by the Building Department, prior to plan review approval or permit issuance.

The sanitary and grease waste piping plans shall be revised as necessary to comply with the pretreatment requirements as indicated on this review document and shall be approved by the County of Santa Clara Department of Environmental Health prior to final approval of Plumbing plans.

All grease retention pretreatment devices shall be listed by a recognized and approved listing agency and shall be installed in accordance with the manufacturer's installation instructions and terms of the listing.

Any deviation from the requirements of this document will require a Variance approval from the Environmental Services Department Regional Wastewater Facility and Watershed Protection section.

Plan Check #		
Project Name:		
Address:		
Plans submitted show the following	g Sources of Wastewater:	
Wok Range Dishwasher Mop Sinks	Floor Drains Garbage Grinder Hand Sinks	Floor Sinks 3-Comp Pot Sinks 2-Comp Sinks
Pretreatment Requirements:		
Quantity Quantity Quantity	Pound Hydro-Mechanical Grease Trap Gallon Gravity Grease Interceptor Power Operated Grease Removal Device No Requirements	
Grease control device or system	ns is to be plumbed to accept the wastewater	flow from these fixtures:
Wok Ranges Dishwasher Mop Sinks Other	Floor Drains Garbage Grinder Hand Sinks	Floor Sinks 3-Comp Pot Sinks 2-Comp Sinks
· ·	otor must be cleaned completely at le solids, whichever comes first.	ast every 90 days or when it
Plan Reviewer:		
Date:		